

Page 1/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

1 Identification

- · Product identifier
- · Trade name: 5000 SUPER FAST CLEAR
- · Article number: 5000
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

General Paint Company S.A.L.

P.O.Box 7623

Beirut, Lebanon

info@generalpaint.biz

www.generalpaint.biz

Importer:

Payless Services Pty. Ltd.

A Pacific Express Group Company

103 Eldridge Road

Bankstown, NSW, 2200

Australia

- · Further information obtainable from: Product Safety Department
- · Emergency telephone number:

Phone: +61 297085698 Mobile: +61 413703038

2 Hazard(s) Identification

· Classification of the substance or mixture



GHS02 flame

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.



GHS08 health hazard

Reproductive toxicity – Category 1A

H360 May damage fertility or the unborn child.
(Contd. on page 2)



Page 2/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 1)



Specific target organ toxicity (single exposure) – H336 May cause drowsiness or dizziness. Category 3

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

toluene (>2.5-≤10 %)

n-butyl acetate (>25-≤50 %)

· Hazard statements

Highly flammable liquid and vapour.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

ΑU



Page 3/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 2)

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
123-86-4	n-butyl acetate	>25- <i>≤</i> 50%		
108-88-3	toluene	>2.5- <i>≤</i> 10%		
108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%		
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<i>≤</i> 2.5%		
	methyl methacrylate	<i>≤</i> 2.5%		
	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	<i>≤</i> 2.5%		
26761-45-5	2,3-epoxypropyl neodecanoate	<i>≤</i> 2.5%		
	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	<i>≤</i> 2.5%		
868-77-9	2-hydroxyethyl methacrylate	<i>≤</i> 2.5%		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

ΑIJ



Page 4/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 3)

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

		(Contd. of page 4)
· Ingre	dients with limit values that require monitoring at the workplace:	
123-8	36-4 n-butyl acetate	
WES	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm	
108-8	88-3 toluene	
WES	Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm Sk	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WES	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
80-62	2-6 methyl methacrylate	
WES	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sen	

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Page 6/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information

· Appearance:

Form: LiquidColour: Clear

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: 110 °C · Flash point: 4 °C

Flammability (solid, gas): Highly flammable.

• Auto-ignition temperature: 370 °C

· Decomposition temperature: Not determined.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower:
Upper:
Vapour pressure at 20 °C:
Density at 20 °C:
Relative density
Vapour density
Vapour density
Evaporation rate

Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

(Contd. on page 7)



Page 7/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 6)

Solvent content:
 Organic solvents:
 VOC (EC)
 Solids content:
 53.1 %
 520.3 g/l
 45.6 %

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

 Oral
 LD50
 13,100 mg/kg (rat)

 Dermal
 LD50
 >5,000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 >21 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity May damage fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

...



Page 8/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 7)

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· **ADG, IMDG, IATA** UN1263

· UN proper shipping name

· **ADG** 1263 PAINT · **IMDG, IATA** PAINT

(Contd. on page 9)



Page 9/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

	(Contd. of pa
Transport hazard class(es)	
ADG, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group ADG, IMDG, IATA	11
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG	El
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II

AU



Page 10/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 9)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	ventory of Industrial Chemicals	
123-86-4	n-butyl acetate	
108-88-3	toluene	
108-65-6	2-methoxy-1-methylethyl acetate	
78-93-3	butanone	
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	
80-62-6	methyl methacrylate	
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyohydroxypoly(oxyethylene);a-3-(3-(2h-	/l)propionol-
26761-45-5	2,3-epoxypropyl neodecanoate	
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	
79-41-4	methacrylic acid	
868-77-9	2-hydroxyethyl methacrylate	
78-83-1	butanol	
77-58-7	dibutyltin dilaurate	
556-67-2	octamethylcyclotetrasiloxane	
100-41-4	ethylbenzene	
1330-20-7	xylene	
· Standard for	the Uniform Scheduling of Medicines and Poisons	
108-88-3 to	luene	S6
78-93-3 bu	ıtanone	S5
80-62-6 m	ethyl methacrylate	S6, S10
868-77-9 2-	hydroxyethyl methacrylate	S5
1330-20-7 xy	da a a	S6

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





None of the ingredients is listed.



GHS02 GHS07 GHS08



Page 11/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 10)

· Signal word Danger

Hazard-determining components of labelling:

toluene (>2.5-≤10 %)

n-butyl acetate (>25-≤50 %)

· Hazard statements

Highly flammable liquid and vapour.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 12)



Page 12/12

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024 Version number 1.1 Revision: 05.07.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 11)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flammable liquids – Category 2: Flammable liquids – Category 2
Reproductive toxicity – Category 1A: Reproductive toxicity – Category 1A
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.