



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

### 1 Identification

- **Product identifier**
- **Trade name:** 6000M 2K CLEAR MATT
- **Article number:** 6000M
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**  
PC9a Coatings and paints, thinners, paint removers  
PC9b Fillers, putties, plasters, modelling clay
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Manufacturer:  
General Paint Company S.A.L.  
P.O.Box 7623  
Beirut, Lebanon  
info@generalpaint.biz  
www.generalpaint.biz  
Importer:  
Payless Services Pty. Ltd.  
A Pacific Express Group Company  
103 Eldridge Road  
Bankstown, NSW, 2200  
Australia
- **Further information obtainable from:** Product Safety Department
- **Emergency telephone number:**  
Phone : +61 297085698  
Mobile: +61 413703038

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flammable liquids – Category 3

H226 Flammable liquid and vapour.



GHS07

(Contd. on page 2)



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 1)

Skin corrosion/irritation – Category 2

H315 Causes skin irritation.

Specific target organ toxicity (single exposure) – Category 3

H335 May cause respiratory irritation.

**Label elements****GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

**Hazard pictograms**

GHS02 GHS07

**Signal word** Warning**Hazard-determining components of labelling:**

xylene (&gt;10-≤25 %)

**Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

May cause respiratory irritation.

**Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

**Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 2)

**· Dangerous components:**

|             |   |           |
|-------------|---|-----------|
| 1330-20-7   | xylene  | >10-≤25%  |
| 123-86-4    | n-butyl acetate   | >10-≤25%  |
| 108-65-6    | 2-methoxy-1-methylethyl acetate   | >2.5-≤10% |
| 112926-00-8 | Precipitated silica (Silica-Amorphous)  | >2.5-≤10% |
| 100-41-4    | ethylbenzene  | >2.5-≤10% |
| 64742-95-6  | Solvent naphtha (petroleum), light arom.  | ≤2.5%     |
| 41556-26-7  | bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | ≤2.5%     |
| 104810-47-1 | s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-<br>ohydroxypoly(oxyethylene);a-3-(3-(2h- | ≤2.5%     |
| 80-62-6     | methyl methacrylate   | ≤2.5%     |
| 26761-45-5  | 2,3-epoxypropyl neodecanoate  | ≤2.5%     |
| 141-32-2    | n-butyl acrylate  | ≤2.5%     |
| 82919-37-7  | methyl 1,2,2,6,6,6-pentamethyl-4-piperidyl sebacate   | ≤2.5%     |

**· Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

AU  
(Contd. on page 4)



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 3)

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene**

|     |  |
|-----|--|
| WES | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 350 mg/m <sup>3</sup> , 80 ppm |
|-----|--|

(Contd. on page 5)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 4)

|   |   |
|---|---|
| <b>123-86-4 n-butyl acetate</b>                           |   |
| WES   | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 713 mg/m <sup>3</sup> , 150 ppm       |
| <b>108-65-6 2-methoxy-1-methylethyl acetate</b>           |   |
| WES   | Short-term value: 548 mg/m <sup>3</sup> , 100 ppm<br>Long-term value: 274 mg/m <sup>3</sup> , 50 ppm<br>Sk  |
| <b>112926-00-8 Precipitated silica (Silica-Amorphous)</b> |   |
| WES   | Long-term value: 10 mg/m <sup>3</sup><br>inhalable dust   |
| <b>100-41-4 ethylbenzene</b>                              |   |
| WES   | Short-term value: 543 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm       |
| <b>80-62-6 methyl methacrylate</b>                        |   |
| WES   | Short-term value: 416 mg/m <sup>3</sup> , 100 ppm<br>Long-term value: 208 mg/m <sup>3</sup> , 50 ppm<br>Sen |
| <b>141-32-2 n-butyl acrylate</b>                          |   |
| WES   | Short-term value: 26 mg/m <sup>3</sup> , 5 ppm<br>Long-term value: 5 mg/m <sup>3</sup> , 1 ppm<br>Sen       |

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- **Respiratory protection:**
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and Chemical Properties

- **General Information**

- **Appearance:**

- **Form:**

Liquid

- **Colour:**

Clear

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

- **Melting point/freezing point:**

Undetermined.

- **Initial boiling point and boiling range:**

124 °C

- **Flash point:**

25 °C

- **Flammability (solid, gas):**

Flammable.

- **Auto-ignition temperature:**

370 °C

- **Decomposition temperature:**

Not determined.

- **Ignition temperature:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

- **Lower:**

1.1 Vol %

- **Upper:**

7.5 Vol %

- **Vapour pressure at 20 °C:**

10.7 hPa

- **Density at 20 °C:**

1.005 g/cm<sup>3</sup>

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

(Contd. on page 7)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 6)

- |  |  |
|--|--|
| · <b>Evaporation rate</b>                        | Not determined.                            |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.          |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.                            |
| · <b>Viscosity:</b>                              |  |
| · <b>Dynamic:</b>                                | Not determined.                            |
| · <b>Kinematic:</b>                              | Not determined.                            |
| · <b>Solvent content:</b>                        |  |
| · <b>Organic solvents:</b>                       | 49.2 %                                     |
| · <b>VOC (EC)</b>                                | 494.1 g/l                                  |
| · <b>Solids content:</b>                         | 49.6 %                                     |
| · <b>Other information</b>                       | No further relevant information available. |

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

##### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)





## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 7)

- **Aspiration hazard** Based on available data, the classification criteria are not met.

### 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                  |            |
|----------------------------------|------------|
| · <b>UN-Number</b>               |            |
| · <b>ADG, IMDG, IATA</b>         | UN1263     |
| · <b>UN proper shipping name</b> |            |
| · <b>ADG</b>                     | 1263 PAINT |
| · <b>IMDG, IATA</b>              | PAINT      |

(Contd. on page 9)

AU





## Safety Data Sheet

according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 8)

**· Transport hazard class(es)****· ADG, IMDG, IATA****· Class**

3 Flammable liquids.

**· Label**

3

**· Packing group****· ADG, IMDG, IATA**

III

**· Environmental hazards:****· Marine pollutant:**

No

**· Special precautions for user**

Warning: Flammable liquids.

**· Hazard identification number (Kemler code):**

30

**· EMS Number:**

F-E, S-E

**· Stowage Category**

A

**· Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

**· Transport/Additional information:****· ADG****· Limited quantities (LQ)**

5L

**· Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**· Transport category**

3

**· Tunnel restriction code**

D/E

**· IMDG****· Limited quantities (LQ)**

5L

**· Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**· UN "Model Regulation":**

UN 1263 PAINT, 3, III

AU

(Contd. on page 10)



## Safety Data Sheet

according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 9)

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

|             |   |
|-------------|---|
| 1330-20-7   | xylene  |
| 123-86-4    | n-butyl acetate   |
| 108-65-6    | 2-methoxy-1-methylethyl acetate   |
| 112926-00-8 | Precipitated silica (Silica-Amorphous)  |
| 100-41-4    | ethylbenzene  |
| 41556-26-7  | bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   |
| 104810-47-1 | s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-<br>ohydroxypoly(oxyethylene);a-3-(3-(2h- |
| 80-62-6     | methyl methacrylate   |
| 26761-45-5  | 2,3-epoxypropyl neodecanoate  |
| 141-32-2    | n-butyl acrylate  |
| 82919-37-7  | methyl 1,2,2,6,6,6-pentamethyl-4-piperidyl sebacate   |
| 103-11-7    | 2-ethylhexyl acrylate   |
| 872-50-4    | N-methyl-2-pyrrolidone  |
| 79-41-4     | methacrylic acid  |
| 868-77-9    | 2-hydroxyethyl methacrylate   |
| 78-83-1     | butanol   |
| 77-58-7     | dibutyltin dilaurate  |
| 7447-41-8   | lithium chloride  |
| 556-67-2    | octamethylcyclotetrasiloxane  |

· **Standard for the Uniform Scheduling of Medicines and Poisons**

|           |                             |         |
|-----------|-----------------------------|---------|
| 1330-20-7 | xylene                      | S6      |
| 80-62-6   | methyl methacrylate         | S6, S10 |
| 872-50-4  | N-methyl-2-pyrrolidone      | S5, S6  |
| 868-77-9  | 2-hydroxyethyl methacrylate | S5      |

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 11)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 10)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word** Warning**· Hazard-determining components of labelling:**

xylene (&gt;10-≤25 %)

**· Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

May cause respiratory irritation.

**· Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category** P5c FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Product safety department**· Contact:** N/A**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 12)



## **Safety Data Sheet** **according to WHS Regulations**

Printing date 08.07.2024

Version number 1.2

Revision: 08.07.2024

**Trade name: 6000M 2K CLEAR MATT**

(Contd. of page 11)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flammable liquids – Category 3: Flammable liquids – Category 3

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

. \* **Data compared to the previous version altered.**

AU