

Page 1/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

1 Identification · Product identifier · Trade name: 634 2K TRANSPARENT YELLOW · Article number: 634 · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. none · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Details of the supplier of the safety data sheet Manufacturer/Supplier: Manufacturer: General Paint Company S.A.L. P.O.Box 7623 Beirut, Lebanon info@generalpaint.biz www.generalpaint.biz Importer: Payless Services Pty. Ltd. A Pacific Express Group Company 103 Eldridge Road Bankstown, NSW, 2200 Australia · Further information obtainable from: Product Safety Department · Emergency telephone number: Phone : +61 297085698 Mobile: +61 413703038

· Classification of the substance or mixture



Flammable liquids – Category 3

H226 Flammable liquid and vapour.

(Contd. on page 2)

AU



Page 2/11


Safety Data Sheet

according to WHS Regulations Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

Printing date 06.07.2024



(Contd. on page 3)



Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

(Contd. of page 2)

Page 3/11

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

•	•	
123-86-4	n-butyl acetate	>25- <i>≤</i> 50%
1330-20-7	xylene	>10- <i>≤</i> 25%
80-62-6	methyl methacrylate	<i>≤</i> 2.5%
868-77-9	2-hydroxyethyl methacrylate	<i>≤</i> 2.5%
· Additional	information: For the wording of the listed hazard phrases refer to section 16.	

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



Page 4/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

(Contd. of page 3)

Trade name: 634 2K TRANSPARENT YELLOW

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Ingre	dients with limit values that require monitoring at the workplace:
123-8	36-4 n-butyl acetate
WES	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm
1330	-20-7 xylene
WES	Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm
80-62	2-6 methyl methacrylate
WES	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sen
· Perse	tional information: The lists valid during the making were used as basis. In protective equipment: In protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

AU



Page 5/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

(Contd. of page 4) Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin. · Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles 9 Physical and Chemical Properties - General Information · Appearance: · Form: Liquid · Colour: Light yellow · Odour: Characteristic

· Odour threshold:

· pH-value:

Not determined. Not determined.

(Contd. on page 6)



Page 6/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

	(Contd. of page s
· Change in condition	
 Melting point/freezing point: 	Undetermined.
 Initial boiling point and boiling range: 	124 °C
· Flash point:	25 °C
· Flammability (solid, gas):	Flammable.
• Auto-ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	1.007 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Solvent content:	
· Organic solvents:	48.3 %
· VÕC (EC)	486.2 g/l
· Solids content:	51.2 %
· Other information	No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

• **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

AU



Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

(Contd. of page 6)

Page 7/11

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small guantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)



Page 8/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

11	Tranci	port	infor	mation	
14	110115	υυιι	πηση	ΠαιιΟΠ	

· UN-Number · ADG, IMDG, IATA	UN1263	
· UN proper shipping name · ADG · IMDG, IATA	1263 PAINT PAINT	
· Transport hazard class(es)		
· ADG, IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
· Packing group		
· ADG, IMĎG, IATA	<i>III</i>	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Warning: Flammable liquids.	
· EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	A	
· Transport in bulk according to Anne	ex II of	
Marpol and the IBC Code	Not applicable.	
		(Contd. on page §



Page 9/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

	(Contd. of page
· Transport/Additional information:	
 ADG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category Tunnel restriction code 	3 D/E
· IMDG	
· Limited quantities (LQ)	5L
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian	Inventory of Industrial Chemicals
123-86-4	n-butyl acetate
1330-20-7	xylene
80-62-6	methyl methacrylate
868-77-9	2-hydroxyethyl methacrylate
100-41-4	ethylbenzene
108-65-6	2-methoxy-1-methylethyl acetate
97-88-1	n-butyl methacrylate
136-53-8	ZINC 2-ETHYLEXANOATE
78-83-1	butanol
64742-88-7	Solvent naphtha (petroleum), medium aliph.
77-58-7	dibutyltin dilaurate
26761-45-5	2,3-epoxypropyl neodecanoate
57-55-6	Propylene glycol
79-41-4	methacrylic acid
556-67-2	octamethylcyclotetrasiloxane
	(Contd. on page 10



Page 10/11

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

Standard f	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7	-	S6
80-62-6	methyl methacrylate	S6, S10
868-77-9	2-hydroxyethyl methacrylate	S5
Australia:	Priority Existing Chemicals	•
None of the	e ingredients is listed.	
GHS label The produc Hazard pic	t is classified and labelled according to the Globally Harmonised System ((GHS).
GHS02 (
Signal wo	-	
n-butyl ace Hazard sta Flammable Causes ski May cause Precaution If medical a Keep out o Read label Keep away Use explos Avoid brea IF ON SKI shower. Store locke	liquid and vapour. n irritation. drowsiness or dizziness. pary statements dvice is needed, have product container or label at hand. f reach of children. before use. from heat/sparks/open flames/hot surfaces. No smoking. ion-proof electrical/ventilating/lighting equipment. thing dust/fume/gas/mist/vapours/spray. N (or hair): Remove/Take off immediately all contaminated clothing. Rins	
Seveso ca Qualifying Qualifying	012/18/EU ngerous substances - ANNEX I None of the ingredients is listed. tegory P5c FLAMMABLE LIQUIDS quantity (tonnes) for the application of lower-tier requirements 5,000 quantity (tonnes) for the application of upper-tier requirements 50,000 safety assessment: A Chemical Safety Assessment has not been carried	00 t

(Contd. on page 11)



Page 11/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 634 2K TRANSPARENT YELLOW

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flammable liquids - Category 3: Flammable liquids - Category 3 Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2 Specific target organ toxicity (single exposure) - Category 3: Specific target organ toxicity (single exposure) - Category 3 * * Data compared to the previous version altered.