

Page 1/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

1 Identification

- · Product identifier
- · Trade name: 636 2K MOLYBDATE ORANGE
- · Article number: 636
- · Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

General Paint Company S.A.L.

P.O.Box 7623

Beirut, Lebanon

info@generalpaint.biz

www.generalpaint.biz

Importer:

Payless Services Pty. Ltd.

A Pacific Express Group Company

103 Eldridge Road

Bankstown, NSW, 2200

Australia

- · Further information obtainable from: Product Safety Department
- · Emergency telephone number:

Phone: +61 297085698 Mobile: +61 413703038

2 Hazard(s) Identification

· Classification of the substance or mixture



GHS02 flame

Flammable liquids – Category 3

H226 Flammable liquid and vapour.



GHS06 skull and crossbones

Acute toxicity - inhalation – Category 3

H331 Toxic if inhaled.

(Contd. on page 2)



Page 2/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 1)



GHS08 health hazard

Germ cell mutagenicity – Category 2 Carcinogenicity – Category 1B

Reproductive toxicity - Category 1A

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.



Skin sensitisation – Category 1

Specific target organ toxicity (single exposure) – Category 3

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Label elements · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS06 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Lead chromate molybdate sulfate red (>2.5-≤10 %) n-butyl acetate (>10-≤25 %) xylene (>2.5-≤10 %)

Solvent naphtha (petroleum), light arom. (≤2.5 %)

· Hazard statements

Flammable liquid and vapour.

Toxic if inhaled.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

(Contd. on page 3)



Page 3/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 2)

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%		
1330-20-7		>2.5-≤10%		
	Lead chromate molybdate sulfate red	>2.5- <i>≤</i> 10%		
	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%		
	Solvent naphtha (petroleum), light arom.	≤2.5%		
	antimony trioxide	≤2.5%		
	methyl methacrylate	≤2.5%		
	2,3-epoxypropyl neodecanoate	<i>≤</i> 2.5%		
868-77-9	2-hydroxyethyl methacrylate	<i>≤</i> 2.5%		

·SVHC

12656-85-8 Lead chromate molybdate sulfate red

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



Page 4/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 3)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: Mouth respiratory protective device.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 5)



Page 5/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 4)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm

12656-85-8 Lead chromate molybdate sulfate red

WES Long-term value: 10 mg/m³ as Mo

108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

1309-64-4 antimony trioxide

WES Long-term value: 0.5 mg/m³ as Sb; handling and use

80-62-6 methyl methacrylate

WES Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sen

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 6)



Page 6/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 5)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not determined.

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information

· Appearance:

· pH-value:

Form: Liquid
Colour: Orange
Odour: Characteristic
Odour threshold: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: 124 °C

(Contd. on page 7)



Page 7/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 6)

Flash point: 25 °C
 Flammability (solid, gas): Flammable.
 Auto-ignition temperature: 315 °C

· Decomposition temperature: Not determined.

· **Ignition temperature:** Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower:
Upper:
Vapour pressure at 20 °C:
Density at 20 °C:
Relative density
Vapour density
Evaporation rate

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

Organic solvents: 42.0 %
 VOC (EC) 462.9 g/l
 Solids content: 57.5 %

· Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

AU -



Page 8/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 7)

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Toxic if inhaled.
- · LD/LC50 values relevant for classification:

12656-85-8 Lead chromate molybdate sulfate red

Oral LD50 >5,000 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Suspected of causing genetic defects.
- · Carcinogenicity May cause cancer.
- · Reproductive toxicity May damage fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Page 9/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 8)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

		mation

· UN-Number

· **ADG, IMDG, IATA** UN1263

· UN proper shipping name

· **ADG** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· **IMDG, IATA** PAINT

- · Transport hazard class(es)
- · ADG, IMDG





· Class 3 Flammable liquids.

· Label

· IATA



· Class 3 Flammable liquids.

· Label

Packing group

· ADG, IMDG, IATA |||

· Environmental hazards:

· Marine pollutant: No

Symbol (fish and tree)

· **Special marking (ADG):** Symbol (fish and tree)

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E

· Stowage Category A

(Contd. on page 10)





Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

	(Contd. of page 9
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
, , , ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY
	HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian l	Inventory of Industrial Chemicals		
123-86-4	n-butyl acetate		
1330-20-7	xylene		
12656-85-8	Lead chromate molybdate sulfate red		
108-65-6	2-methoxy-1-methylethyl acetate		
100-41-4	ethylbenzene		
14808-60-7	Quartz (SiO2)		
1309-64-4	antimony trioxide		
80-62-6	methyl methacrylate		
26761-45-5	2,3-epoxypropyl neodecanoate		
868-77-9	2-hydroxyethyl methacrylate		
79-41-4	methacrylic acid		
136-53-8	ZINC 2-ETHYLEXANOATE		
78-83-1	butanol		
97-88-1	n-butyl methacrylate		
	(Contd. on page 1)		

______/



Page 11/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

		(Contd. of page 10)		
77-58-7	dibutyltin dilaurate			
64742-88-7	Solvent naphtha (petroleum), medium aliph.			
556-67-2	octamethylcyclotetrasiloxane			
Standard for the Uniform Scheduling of Medicines and Poisons				
1330-20-7	xylene	S6		
80-62-6	methyl methacrylate	S6, S10		
868-77-9	2-hydroxyethyl methacrylate	S5		
· Australia: Priority Existing Chemicals				
12656-85-8	Lead chromate molybdate sulfate red			

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS06 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Lead chromate molybdate sulfate red (>2.5-≤10 %)

n-butyl acetate (>10-≤25 %)

xylene (>2.5-≤10 %)

Solvent naphtha (petroleum), light arom. (≤2.5 %)

· Hazard statements

Flammable liquid and vapour.

Toxic if inhaled.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

(Contd. on page 12)



Page 12/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 11)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

12656-85-8 Lead chromate molybdate sulfate red

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flammable liquids – Category 3: Flammable liquids – Category 3

Acute toxicity - inhalation - Category 3: Acute toxicity - Category 3

Skin sensitisation - Category 1: Skin sensitisation - Category 1

(Contd. on page 13)



Page 13/13

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024 Version number 1.1 Revision: 06.07.2024

Trade name: 636 2K MOLYBDATE ORANGE

(Contd. of page 12)

Germ cell mutagenicity – Category 2: Germ cell mutagenicity – Category 2
Carcinogenicity – Category 1B: Carcinogenicity – Category 1B
Reproductive toxicity – Category 1A: Reproductive toxicity – Category 1A
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.