

Page 1/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

1 Identification · Other means of identification · Trade name: H200 2K HARDENER SUPER FAST · Article number: H200 · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. none · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Details of the supplier of the safety data sheet Manufacturer/Supplier: Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 info@generalpaint.biz · Further information obtainable from: Product Safety Department · Emergency telephone number: During normal opening times:(961) 9 925990 /1/2 009619925990

2 Hazard(s) Identification

Classification of the substance or mixture GHS02 flame		
Flammable liquids – Category 3	H226	Flammable liquid and vapour.
GHS08 health hazard		
Respiratory sensitisation – Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
		(Contd. on page 2)



Page 2/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024



(Contd. of page 1) GHS07 Skin corrosion/irritation – Category 2 H315 Causes skin irritation. Eye damage/irritation – Category 2A H319 Causes serious eye irritation. Specific target organ toxicity (single exposure) -H335-H336 May cause respiratory irritation. May Category 3 cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: xylene (>25-≤50 %) Isophorone Diisocyanate homopolymer (>2.5-≤10 %) Homopolymer of hexamethylene diisocyanate (>25-≤50 %) n-butyl acetate (>10-≤25 %) · Hazard statements Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3) AU



Page 3/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

(Contd. of page 2)

Trade name: H200 2K HARDENER SUPER FAST

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

•	components:	
1330-20-7	xylene	>25- <i>≤</i> 50%
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25- <i>≤</i> 50%
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%
53880-05-0	Isophorone Diisocyanate homopolymer	>2.5- <i>≤</i> 10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
Additional	information: For the wording of the listed hazard phrases refer to section 16	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

Trade name: H200 2K HARDENER SUPER FAST

· Protective equipment: No special measures required.

(Contd. of page 3)

Page 4/11

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Appropriate engineering controls No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm

Long-term value: 350 mg/m³, 80 ppm

(Contd. on page 5)

AU -



Page 5/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

(Contd. of page 4)

Trade name: H200 2K HARDENER SUPER FAST

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

AU



Safety Data Sheet according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024



· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

Liquid Clear Characteristic Not determined. Not determined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Clear Characteristic Not determined. Not determined. Undetermined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Clear Characteristic Not determined. Not determined. Undetermined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Characteristic Not determined. Not determined. Undetermined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Not determined. Not determined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Not determined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Undetermined. 124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
124 °C 25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
25 °C Flammable. 370 °C Not determined. Product is not selfigniting.
Flammable. 370 °C Not determined. Product is not selfigniting.
370 °C Not determined. Product is not selfigniting.
Not determined. Product is not selfigniting.
Product is not selfigniting.
Deschart is not some a size it lands on formation of some lastice size
Product is not explosive. However, formation of explosive air/
vapour mixtures are possible.
1.1 Vol %
7.5 Vol %
10.7 hPa
0.99652 g/cm ³
Not determined.
Not determined.
Not determined.
Not miscible or difficult to mix.
Not determined.
Not determined.
Not determined.
60.6 %
604.3 g/l

(Contd. of page 5)

Page 6/11

AU



Page 7/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

(Contd. of page 6)

Trade name: H200 2K HARDENER SUPER FAST

· Solids content:

40.1 %

Other information

Particle characteristics
 Physical state

Not applicable. Fluid

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

AU



Page 8/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

(Contd. of page 7)

Trade name: H200 2K HARDENER SUPER FAST

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADG, IMDG, IATA	UN1263	
· UN proper shipping name		
· ADG	1263 PAINT	
· IMDG, IATA	PAINT	
· Transport hazard class(es)		
· ADG, IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
		(Contd. on page



Page 9/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

Trade name: H200 2K HARDENER SUPER FAST

	(Contd. of page 8
· Packing group · ADG, IMDG, IATA	<i>III</i>
 Environmental hazards: Marine pollutant: 	No
 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category Tunnel restriction code 	3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7 xylene

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 10)

S6



Page 10/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

Trade name: H200 2K HARDENER SUPER FAST

(Contd. of page 9) Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: xylene (>25-≤50 %) Isophorone Diisocyanate homopolymer (>2.5-≤10 %) Homopolymer of hexamethylene diisocyanate (>25- ≤50 %) n-butyl acetate (>10-≤25 %) Hazard statements Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Directive 2012/18/EU · Named dangerous substances - ANNEX I None of the ingredients is listed. · Seveso category P5c FLAMMABLE LIQUIDS • Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

⁻ AU



Page 11/11

Safety Data Sheet according to WHS Regulations

Date of issue: 08.11.2024

Version number 1.1

Revision: 08.11.2024

Trade name: H200 2K HARDENER SUPER FAST

	(Contd. of page
	Department issuing SDS: Product safety department
	Contact: N/A
	Abbreviations and acronyms:
	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern
	the International Transport of Dangerous Goods by Rail)
	ICAO: International Civil Aviation Organisation
	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning
	International Carriage of Dangerous Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	Flammable liquids – Category 3: Flammable liquids – Category 3
3	Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2
E	Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
F	Respiratory sensitisation – Category 1: Respiratory sensitisation – Category 1
3	Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3
	* Data compared to the previous version altered.