

Page 1/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

1 Identification

- · Other means of identification
- · Trade name: <u>H500 2K HARDENER FAST</u>
- · Article number: H500
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- none

· Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and r

PC9a Coatings and paints, thinners, paint removersPC9b Fillers, putties, plasters, modelling clay

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Générale de Peinture 3 rue du Velay 91090 LISSES, France

• Further information obtainable from: Product Safety Department • Emergency telephone number: Tel: +33(0)160867765

2 Hazard(s) Identification

Classification of the substance or mixture	
Flammable liquids – Category 3	H226 Flammable liquid and vapour.
GHS08 health hazard	
Respiratory sensitisation – Category 1	H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled.
GHS07	
Acute toxicity - dermal – Category 4	H312 Harmful in contact with skin.
Skin corrosion/irritation – Category 2	H315 Causes skin irritation. (Contd. on page



Page 2/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST (Contd. of page 1) Eye damage/irritation – Category 2A H319 Causes serious eye irritation. Specific target organ toxicity (single exposure) – H335 May cause respiratory irritation. Category 3 · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: Homopolymer of hexamethylene diisocyanate (>25-≤50 %) Isophorone Diisocyanate homopolymer (>2.5-≤10 %) xylene (>25-≤50 %) · Hazard statements Flammable liquid and vapour. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

(Contd. on page 3)



Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 2)

Page 3/11

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25- <i>≤</i> 50%		
1330-20-7	xylene	>25- <i>≤</i> 50%		
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%		
	Isophorone Diisocyanate homopolymer	>2.5- <i>≤</i> 10%		
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%		
Additional	information: For the wording of the listed hazard phrases refer to section 16			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

(Contd. on page 4)

AU



Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 3)

Page 4/11

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautiener De pet of leave to enter equipment of argument of the persons argument of the pe
- \cdot Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Appropriate engineering controls No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm

(Contd. on page 5)

AU



Page 5/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 4)

108-65-6 2-methoxy-1-methylethyl acetate WES Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)



Safety Data Sheet according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 5)

Page 6/11

General Information	
Appearance: Form:	Fluid
Colour:	
	According to product description Characteristic
· Odour:	
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	
Flash point:	25 °C
Flammability	Flammable.
Auto-ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive a
	vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.02697 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/w	ater: Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	50.1 %
VÕC (EC)	514.8 g/l
Solids content:	50.7 %
Other information	
Particle characteristics	Not applicable.
Physical state	Fluid

(Contd. on page 7)



Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 6)

Page 7/11

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Harmful in contact with skin.
- · Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)

AU



Page 8/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

· Other adverse effects No further relevant information available.

(Contd. of page 7)

3 Disposal considerations

- Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sowage sys
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number ADG, IMDG, IATA	UN1263
UN proper shipping name ADG IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	
ADG, IMDG, IATA	
Class Label	3 Flammable liquids. 3
	5
Packing group ADG, IMDG, IATA	<i>III</i>
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
	(Contd. on pag



Page 9/11

Safety Data Sheet

according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

	(Contd. of page 8)
· Transport/Additional information:	
 ADG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
 Transport category Tunnel restriction code 	Maximum net quantity per outer packaging: 1000 ml 3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7 xylene

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). • **Hazard pictograms**



· Signal word Danger

 Hazard-determining components of labelling: Homopolymer of hexamethylene diisocyanate (>25-≤50 %) Isophorone Diisocyanate homopolymer (>2.5-≤10 %) xylene (>25-≤50 %)

(Contd. on page 10)

S6

AU



Page 10/11

Safety Data Sheet according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Trade name: H500 2K HARDENER FAST

(Contd. of page 9)	
· Hazard statements	
Flammable liquid and vapour.	
Harmful in contact with skin.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause respiratory irritation.	
· Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
Use explosion-proof electrical/ventilating/lighting equipment.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/	
shower.	
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and	
easy to do. Continue rinsing.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
 Directive 2012/18/EU Named dangerous substances - ANNEX I None of the ingredients is listed. Seveso category P5c FLAMMABLE LIQUIDS Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 	
16 Other information	-
This information is based on our present knowledge. However, this shall not constitute a guarantee for	
any specific product features and shall not establish a legally valid contractual relationship.	
 Department issuing SDS: Product safety department Contact: N/A 	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning	
the International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the	
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	

- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

AU



Safety Data Sheet according to WHS Regulations

Date of issue: 11.11.2024

Version number 1.2

Revision: 11.11.2024

Page 11/11

Trade name: H500 2K HARDENER FAST

(Contd. of page 10)

AU

Flammable liquids – Category 3: Flammable liquids – Category 3 Acute toxicity - dermal – Category 4: Acute toxicity – Category 4 Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2 Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A Respiratory sensitisation – Category 1: Respiratory sensitisation – Category 1 Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3 * * Data compared to the previous version altered.