

Page 1/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

1 Identification · Product identifier · Trade name: 4465 2K RAPID PRIMER RED · Article number: 4465 · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. none · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Details of the supplier of the safety data sheet Manufacturer/Supplier: Manufacturer: General Paint Company S.A.L. P.O.Box 7623 Beirut, Lebanon info@generalpaint.biz www.generalpaint.biz Importer: Payless Services Pty. Ltd. A Pacific Express Group Company 103 Eldridge Road Bankstown, NSW, 2200 Australia · Further information obtainable from: Product Safety Department · Emergency telephone number: Phone : +61 297085698 Mobile: +61 413703038 2 Hazard(s) Identification

Classification of the substance or mixture
 GHS02 flame

Flammable liquids – Category 3 H226 Flammable liquid and vapour.

(Contd. on page 2)

AU



Page 2/11


Safety Data Sheet

according to WHS Regulations Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

Printing date 05.07.2024





Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

· vPvB: Not applicable.

(Contd. of page 2)

Page 3/11

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

-	components:	
1330-20-7		>10- <i>≤</i> 25%
	barium sulphate, natural	>10- <i>≤</i> 25%
1332-58-7	Kaolin	>10- <i>≤</i> 25%
123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%
64742-95-6	Solvent naphtha (petroleum), light arom.	<i>≤</i> 2.5%
100-41-4	ethylbenzene	<i>≤</i> 2.5%
77-58-7	dibutyltin dilaurate	<i>≤</i> 2.5%
	information: For the wording of the listed hazard phrases refer to section 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

(Contd. on page 4)



Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

(Contd. of page 3)

Page 4/11

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Function protected persons away.
- \cdot Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- · Precautions for safe handling Open and handle receptacle with care.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

Keep respiratory protective device available.

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm

7727-43-7 barium sulphate, natural

WES Long-term value: 10 mg/m³

inhalable dust

(Contd. on page 5)

AU



Page 5/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

	58-7 Kaolin (Contd. of page 4
	Long-term value: 10 mg/m ³
VVES	inhalable dust
123-8	6-4 n-butyl acetate
	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 713 mg/m³, 150 ppm
100-4	1-4 ethylbenzene
WES	Short-term value: 543 mg/m³, 125 ppm
	Long-term value: 434 mg/m³, 100 ppm
77-58	-7 dibutyltin dilaurate
WES	Short-term value: 0.2 mg/m ³
	Long-term value: 0.1 mg/m ³
	as Sn, Sk: Note (g) fional information: The lists valid during the making were used as basis.
Keep Imme Wash Store Avoid Avoid Resp	ral protective and hygienic measures: away from foodstuffs, beverages and feed. diately remove all soiled and contaminated clothing hands before breaks and at the end of work. protective clothing separately. contact with the skin. contact with the eyes and skin. irratory protection: Not required. action of hands:
THE STATE	Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

⁻ AU



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information	
· Appearance:	
· Form:	Liquid
· Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
Change in condition	
· Melting point/freezing point:	Undetermined.
 Initial boiling point and boiling range: 	124 °C
· Flash point:	25 ℃
Flammability (solid, gas):	Flammable.
· Auto-ignition temperature:	370 °C
 Decomposition temperature: 	Not determined.
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air
	vapour mixtures are possible.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	7 Vol %
 Vapour pressure at 20 °C: 	6.7 hPa
· Density at 20 °C:	1.633 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with 	
· water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Solvent content:	
· Organic solvents:	26.4 %
· VOC (EC)	430.5 g/l

(Contd. of page 5)

Page 6/11

AU



Page 7/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

(Contd. of page 6)

Trade name: 4465 2K RAPID PRIMER RED

· Solids content:

73.1 %

· Other information

No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity May damage fertility. May damage the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

AU



Page 8/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

(Contd. of page 7)

Trade name: 4465 2K RAPID PRIMER RED

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
ADG, IMDG, IATA	UN1263	
UN proper shipping name		
ADG	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
ADG, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group		
ADG, IMDG, IATA	111	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (H		
EMS Number:	F-E, <u>S-E</u>	
Stowage Category	A	



Page 9/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

	(Contd. of page
• Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
 Tunnel restriction code 	D/E
·IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian In	ventory of Industrial Chemicals
14807-96-6	Talc (Mg3H2(SiO3)4)
1330-20-7	xylene
7727-43-7	barium sulphate, natural
1332-58-7	Kaolin
123-86-4	n-butyl acetate
100-41-4	ethylbenzene
57-55-6	Propylene glycol
112945-52-5	silicon dioxide
77-58-7	dibutyItin dilaurate
64-19-7	acetic acid
108-65-6	2-methoxy-1-methylethyl acetate
7647-01-0	hydrogen chloride
78-83-1	butanol
	(Contd. on page 10

AU —



Page 10/11

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

Standard for the Uniform Scheduling of Medicines and Poisons 1330-20-7 xylene	S6
64-19-7 acetic acid	S2, S5, S6
7647-01-0 hydrogen chloride	S5, S6
	30, 30
Australia: Priority Existing Chemicals	
None of the ingredients is listed.	
GHS label elements The product is classified and labelled according to the Globally Harmonised System (Hazard pictograms	(GHS).
GHS02 GHS07 GHS08 Signal word Danger	
 Hazard-determining components of labelling: dibutyltin dilaurate (≤2.5 %) Hazard statements Flammable liquid and vapour. Causes skin irritation. May damage fertility. May damage the unborn child. Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rins shower. Store locked up. Dispose of contents/container in accordance with local/regional/national/international 	
Directive 2012/18/EU Named dangerous substances - ANNEX I None of the ingredients is listed. Seveso category P5c FLAMMABLE LIQUIDS Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 Chemical safety assessment: A Chemical Safety Assessment has not been carried	00 t

(Contd. on page 11)



Page 11/11

Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.1

Revision: 05.07.2024

Trade name: 4465 2K RAPID PRIMER RED

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flammable liquids - Category 3: Flammable liquids - Category 3 Skin corrosion/irritation - Category 2: Skin corrosion/irritation - Category 2 Reproductive toxicity - Category 1B: Reproductive toxicity - Category 1B • * Data compared to the previous version altered.