

Page 1/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

1 Identification

- · Product identifier
- · Trade name: S1918C BASECOAT BLENDING THINNER
- · Article number: S1918C
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour. GHS08 Health hazard Carcinogenicity – Category 2 H351 Suspected of causing cancer. GHS07 Skin Irritation - Category 2 H315 Causes skin irritation. Eye Irritation - Category 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3 · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) CA



Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Page 2/13

Trade name: S1918C BASECOAT BLENDING THINNER

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene methyl acetate ethvlbenzene · Hazard statements Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. (Contd. on page 3)

CA



Page 3/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

(Contd. of page 2) Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 23 Fire = 3FIRE Reactivity = 0**REACTIVITY** 0

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

| - | s components: | |
|-------------|---|--------------|
| | 4-chloro-alpha,alpha,alpha-trifluorotoluene | 30-60% w/w * |
| | methyl acetate | 10-30% w/w * |
| | propylene carbonate | 1-5% w/w * |
| 1330-20-7 | • | 1-5% w/w * |
| 763-69-9 | ethyl 3-ethoxypropionate | 1-5% w/w * |
| 100-41-4 | ethylbenzene | 0.1-1% w/w * |
| * Actual co | ncentration ranges are withheld as a trade secret | , |

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

CA



Page 4/13

(Contd. of page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 5)

CA



Page 5/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

| EL | STEL: 250 ppm TWA: 200 ppm |
|-----|---|
| EV | STEL: 755 mg/m³, 250 ppm TWA: 605 mg/m³, 200 ppm |
| 133 | 30-20-7 xylene |
| EL | STEL: 150 ppm TWA: 100 ppm |
| EV | STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm |
| 763 | 3-69-9 ethyl 3-ethoxypropionate |
| EV | TWA: 300 mg/m³, 50 ppm |
| 100 |)-41-4 ethylbenzene |
| EL | TWA: 20 ppm IARC 2B |
| EV | STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm |
| Ad | ditional information: The lists that were valid during the creation were used as basis. |
| Exi | posure controls |

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

(Contd. on page 6)



Page 6/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

(Contd. of page 5)

Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

| Information on basic physic General Information Appearance: | and chemical properties | |
|---|-------------------------|--------------------|
| Form: | Liquid | |
| Color: | Colorless | |
| · Odor: | Characteristic | |
| · Odor threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| | | (Contd. on page 7) |



Page 7/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

| | (Contd. of page |
|---|---|
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 57 ℃ |
| Flash point: | -10 °C |
| Flammability: | Highly flammable. |
| Auto igniting: | 455 °C |
| Decomposition temperature: | Not determined. |
| Ignition temperature: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive ai vapor mixtures are possible. |
| Explosion limits: Lower: Upper: | 3.1 Vol % 16 Vol % |
| Vapor pressure at 20 °C: | 220 hPa |
| Density at 20 °C: Relative density Vapor density Evaporation rate | 1.146 g/cm ³ Not determined. Not determined. Not determined. |
| Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/wa | ater): Not determined. |
| Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
| Solvent content: | |
| Organic solvents: Coating VOC content: | 85.2 % 8.83 % 417.4 c// (2.49.lb/cc) |
| Material VOC content: | 417.4 g/l / 3.48 lb/gal 101.2 g/l / 0.84 lb/gal |
| Solids content: | 14.8 % |
| Other information | No further relevant information available. |

(Contd. on page 8)



Page 8/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

(Contd. of page 7)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

| · IARC (Inte | rnational Agency for Research on Cancer) | |
|--------------|---|----|
| 98-56-6 | 4-chloro-alpha,alpha,alpha-trifluorotoluene | 2B |
| 1330-20-7 | • | 3 |
| 100-41-4 | ethylbenzene | 2B |
| • | onal Toxicology Program) | |
| None of the | e ingredients is listed. | |

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 9)

CA



Page 9/13

(Contd. of page 8)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

| UN-Number DOT/TDG, ADR, IMDG, IATA | UN1263 | |
|---------------------------------------|------------|--|
| UN proper shipping name | | |
| DOT/TDG | Paint | |
| ADR | 1263 Paint | |
| IMDG, IATA | PAINT | |
| Transport hazard class(es) | | |
| DOT/TDG (Transport dangerous go | oods): | |
| | | |
| | | |
| 2 | | |
| V | | |



Page 10/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

| | (Contd. of page |
|--|--|
| Label | 3 |
| ADR, IMDG, IATA | |
| Class Label | 3 Flammable liquids 3 |
| Packing group DOT/TDG, ADR, IMDG, IATA | |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user EMS Number: Stowage Category | Warning: Flammable liquids F-E, <u>S-E</u> A |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. | |
| Transport/Additional information: | |
| DOT/TDG Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| ADR Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| <i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i> | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 1263 PAINT, 3, III |

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 11)

[—] CA



Page 11/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

| Sara | (Contd. of page |
|---|-----------------|
| Sara Section 355 (extremely hazardous substances): | |
| None of the ingredients is listed. | |
| | |
| Section 313 (Specific toxic chemical listings): | |
| 1330-20-7 xylene | |
| 100-41-4 ethylbenzene | |
| TSCA (Toxic Substances Control Act): | |
| All components have the value ACTIVE. | |
| Canadian substance listings: | |
| Canadian Domestic Substances List (DSL) | |
| 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene | |
| 79-20-9 methyl acetate | |
| 108-32-7 propylene carbonate | |
| 1330-20-7 xylene | |
| 763-69-9 ethyl 3-ethoxypropionate | |
| 108-65-6 2-methoxy-1-methylethyl acetate | |
| 100-41-4 ethylbenzene | |
| Canadian Non-Domestic Substances List (NDSL) | |
| None of the ingredients is listed. | |
| Canadian Ingredient Disclosure list (limit 0.1%) | |
| 100-41-4 ethylbenzene | |
| Canadian Ingredient Disclosure list (limit 1%) | |
| 79-20-9 methyl acetate | |
| 108-32-7 propylene carbonate | |

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

• *Hazard-determining components of labeling:* 4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate ethylbenzene

(Contd. on page 12)

CA



Page 12/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

| | (Contd. of page 17 |
|---|---|
| Hazard statements | |
| Highly flammable liquid and vapour. | |
| Causes skin irritation. | |
| Causes serious eye irritation. | |
| Suspected of causing cancer. | |
| May cause drowsiness or dizziness. | |
| Precautionary statements | |
| If medical advice is needed, have product container or label at I | hand. |
| Keep out of reach of children. | |
| Read label before use. | |
| Obtain special instructions before use. | |
| Do not handle until all safety precautions have been read and u | |
| Keep away from heat, hot surfaces, sparks, open flames and or | ther ignition sources. No smoking. |
| Ground and bond container and receiving equipment. | |
| Use explosion-proof [electrical/ventilating/lighting] equipment. | |
| Use non-sparking tools. | |
| Take actions to prevent static discharges. | |
| Avoid breathing dust/fume/gas/mist/vapours/spray. | |
| Wash thoroughly after handling. | |
| Use only outdoors or in a well-ventilated area. | |
| Wear protective gloves/protective clothing/eye protection/face p | protection. |
| IF ON SKIN (or hair): Take off immediately all contaminated clo | thing. Rinse skin with water [or shower |
| IF INHALED: Remove person to fresh air and keep comfortable | e for breathing. |
| IF IN EYES: Rinse cautiously with water for several minutes. | Remove contact lenses, if present an |
| easy to do. Continue rinsing. | |
| IF exposed or concerned: Get medical advice/attention. | |
| Call a poison center/doctor if you feel unwell. | |
| Specific treatment (see on this label). | |
| Take off contaminated clothing and wash it before reuse. | |
| If skin irritation occurs: Get medical advice/attention. | |
| If eye irritation persists: Get medical advice/attention. | |
| In case of fire: Use CO2, powder or water spray to extinguish. | |
| Store in a well-ventilated place. Keep container tightly closed. | |
| Store in a well-ventilated place. Keep cool. | |
| Store locked up. | |
| Dispose of contents/container in accordance with local/regional | l/national/international regulations. |
| Chemical safety assessment: A Chemical Safety Assessmen | |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: N/A

(Contd. on page 13)

CA



Page 13/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 12/02/2024

Trade name: S1918C BASECOAT BLENDING THINNER

Reviewed on 12/02/2024

| | (Contd. of page 1 |
|---|-------------------|
| · Date of the latest revision of the safety data sheet 12/02/2024 / 1.0 | |
| • Abbreviations and acronyms: | |
| IMDG: International Maritime Code for Dangerous Goods | |
| DOT: US Department of Transportation | |
| IATA: International Air Transport Association | |
| EINECS: European Inventory of Existing Commercial Chemical Substances | |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) | |
| NFPA: National Fire Protection Association (USA) | |
| HMIS: Hazardous Materials Identification System (USA) | |
| VOC: Volatile Organic Compounds (USA, EU) | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| vPvB: very Persistent and very Bioaccumulative | |
| \cdot * Data compared to the previous version altered. | |