

Page 1/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 655 2K RUBY RED
- · Article number: 655
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. S.A.L.
- P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids - Category 3

H226 Flammable liquid and vapour.

GHS07

Skin Sensitizer - Category 1 Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3

H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 2)

CA



Page 2/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

	(Contd. of page 1)
methyl methacrylate	
2-hydroxyethyl methacrylate • Hazard statements	
Flammable liquid and vapour.	
May cause an allergic skin reaction.	
May cause drowsiness or dizziness.	
Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	All and the second second
Keep away from heat, hot surfaces, sparks, open flames and other ignition s	ources. No smoking.
Ground and bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take actions to prevent static discharges.	
Avoid breathing dust/fume/gas/mist/vapours/spray.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing should not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse s	
IF INHALED: Remove person to fresh air and keep comfortable for breathing	<i>J.</i>
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	meetic nel ne muletie ne
Dispose of contents/container in accordance with local/regional/national/inte	mational regulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 0	
Fire = 3	
0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{\text{O}} \text{Health} = 0$	
FIRE 3 Fire = 3	
REACTIVITY Reactivity = 0	
	CA

(Contd. on page 3)



according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

(Contd. of page 2)

Page 3/13

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:
-------------------------------	-------------

	n-butyl acetate	10-30% w/w *
1330-20-7		5-10% w/w *
	2-methoxy-1-methylethyl acetate	3-7% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	1-5% w/w *
	methyl methacrylate	0.1-1% w/w *
	2-hydroxyethyl methacrylate	0.1-1% w/w *
* Actual con	centration ranges are withheld as a trade secret.	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

Page 4/13

(Contd. of page 3)



according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Page 5/13

Trade name: 655 2K RUBY RED

	(Contd. of page 4)
	ntrol parameters
	mponents with limit values that require monitoring at the workplace:
123	-86-4 n-butyl acetate
EL	STEL: 150 ppm TWA: 50 ppm
EV	STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm
133	0-20-7 xylene
EL	STEL: 150 ppm TWA: 100 ppm
EV	STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm
108	-65-6 2-methoxy-1-methylethyl acetate
EL	STEL: 75 ppm TWA: 50 ppm
ΕV	TWA: 270 mg/m ³ , 50 ppm
80-	62-6 methyl methacrylate
EL	STEL: 100 ppm TWA: 50 ppm S(D)
EV	STEL: 100 ppm TWA: 50 ppm
Add	ditional information: The lists that were valid during the creation were used as basis.
· Per · Ger Imn Wa: · Bre In c	posure controls sonal protective equipment: meral protective and hygienic measures: mediately remove all soiled and contaminated clothing. sh hands before breaks and at the end of work. athing equipment: mase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe osure use respiratory protective device that is independent of circulating air.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)



Page 6/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

(Contd. of page 5) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and General Information	chemical properties
· General Information · Appearance:	
Form:	Fluid
Color:	According to product description
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 °C
· Flash point:	25 °C
· Flammability:	Flammable.
· Auto igniting:	315 ℃
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
	(Contd. on page 7)



according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

	(C	contd. of page
Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.5 Vol %	
Vapor pressure at 20 °C:	10.7 hPa	
Density at 20 °C:	1.00185 g/cm ³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/v	vater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	45.0 %	
Coating VOC content:	44.96 %	
5	450.5 g/l / 3.76 lb/gal	
Material VOC content:	450.5 g/l / 3.76 lb/gal	
Solids content:	54.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

Page 7/13



Page 8/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

(Contd. of page 7)

	xicity:		
· LD/LC50	values that	at are relevant for classification:	
123-86-4	n-butyl ac		
Oral	LD50	13,100 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	e LC50/4 h	>21 mg/l (rat)	
 on the sl on the ey Sensitization Addition The procession 	al toxicolo luct shows	ant effect.	on methods i
 on the sl on the eg Sensitization Addition The proception preparation Irritant Carcinog 	kin: No irrita /e: No irrita ation: Sens al toxicolo luct shows ons: genic categ	ant effect. ating effect. sitization possible through skin contact. o gical information: the following dangers according to internally approved calculation gories	on methods :
 on the sl on the eg Sensitization Addition The proceparation Irritant Carcinog IARC (Integration) 	kin: No irrita /e: No irrita ation: Sens al toxicolo luct shows ons: genic categ ternational	ant effect. ating effect. sitization possible through skin contact. a gical information: the following dangers according to internally approved calculations.	
 on the sl on the ey Sensitization Addition The proceparation preparation Irritant Carcinog IARC (Intra 1330-20- 	kin: No irrita /e: No irrita ation: Sens al toxicolo luct shows ons: genic categ ternational 7 xylene	ant effect. ating effect. sitization possible through skin contact. o gical information: the following dangers according to internally approved calculation g ories I Agency for Research on Cancer)	3
 on the sl on the eg Sensitization Addition The proceparation preparation Irritant Carcinog IARC (Integration) 80-62- 	kin: No irrita /e: No irrita ation: Sens al toxicolo luct shows ons: genic categ ternational 7 xylene 6 methyl m	ant effect. ating effect. sitization possible through skin contact. o gical information: the following dangers according to internally approved calculation gories	

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)

CA



Page 9/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT/TDG, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT/TDG	Paint	
ADR	1263 Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT/TDG (Transport dangerous go	ods):	
Class	3 Flammable liquids	
Class Label	3 Flammable liquids 3	
Label		
Label		
Label		

(Contd. of page 8)



Page 10/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

	(Contd. of pag
Packing group DOT/TDG, ADR, IMDG, IATA	<i>III</i>
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	<i>I</i> I of Not applicable.
Transport/Additional information:	
DOT/TDG Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 35	5 (extremely hazardous substances):
None of the	e ingredients is listed.
· Section 31	3 (Specific toxic chemical listings):
1330-20-7	xylene
	methyl methacrylate
872-50-4	N-methyl-2-pyrrolidone
100-41-4	ethylbenzene
	(Contd. on page 11)
	CA CA



Page 11/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

123-86-4	1 n-butyl acetate	ACT/N
1330-20-7		ACTIN
	2-methoxy-1-methylethyl acetate	ACTIV
	6 methyl methacrylate	ACTIV
	2-hydroxyethyl methacrylate	ACTIV
	1 n-butyl methacrylate	ACTIV
	ZINC 2-ETHYLEXANOATE	ACTIN
872-50-4	N-methyl-2-pyrrolidone	ACTIN
	t ethylbenzene	ACTIN
	l butanol	ACTIN
64742-88-7	Solvent naphtha (petroleum), medium aliph.	ACTIN
	7 dibutyltin dilaurate	ACTIN
	lithium chloride	ACTIN
Canadian	substance listings:	
Canadian	Domestic Substances List (DSL)	
	1 n-butyl acetate	
1330-20-7	7 xylene	
108-65-6	2-methoxy-1-methylethyl acetate	
80-62-6	6 methyl methacrylate	
868-77-9	2-hydroxyethyl methacrylate	
97-88-1	n-butyl methacrylate	
136-53-8	3 ZINC 2-ETHYLEXANOATE	
872-50-4	N-methyl-2-pyrrolidone	
100-41-4	t ethylbenzene	
78-83-1	1 butanol	
64742-88-7	7 Solvent naphtha (petroleum), medium aliph.	
	7 dibutyltin dilaurate	
7447-41-8	3 lithium chloride	
Canadian	Non-Domestic Substances List (NDSL)	
	e ingredients is listed.	
	Ingredient Disclosure list (limit 0.1%)	
None of the	e ingredients is listed.	
Canadian	Ingredient Disclosure list (limit 1%)	
	n-butyl acetate	



Page 12/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Trade name: 655 2K RUBY RED

Reviewed on 07/29/2024

(Contd. of page 11) · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard-determining components of labeling: n-butyl acetate methyl methacrylate 2-hydroxyethyl methacrylate · Hazard statements Flammable liquid and vapour. May cause an allergic skin reaction. May cause drowsiness or dizziness. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 13)



Page 13/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 655 2K RUBY RED

(Contd. of page 12) • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 10/09/2024 / 1.1

 Abbreviations and acronyms: ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative * Data compared to the previous version altered.