

Page 1/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

1 Identification

- · Product identifier
- · Trade name: GRRAL9005 2K DEEP BLACK
- · Article number: GRRAL9005
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids - Category 3 H226 Flammable liquid and vapour. GHS08 Health hazard H351 Suspected of causing cancer. Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs - Category 2 through prolonged or repeated exposure. GHS07 Skin Irritation - Category 2 H315 Causes skin irritation. Skin Sensitizer - Category 1 H317 May cause an allergic skin reaction. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) CA



according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Page 2/14

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: ethylbenzene methyl methacrylate · Hazard statements Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3) CA



according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Page 3/14

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 2) • Classification system: • NFPA ratings (scale 0 - 4) 4 = 1Fire = 3 Reactivity = 0 • HMIS-ratings (scale 0 - 4) HEALTH 1 FIRE 3 REACTIVITY 0 HEALTH 2 Health = 1 Fire = 3 Reactivity = 0 HEALTH 2 Fire = 3 Reactivity = 0

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:	
1330-20-7	xylene	10-30% w/w *
123-86-4	n-butyl acetate	10-30% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	3-7% w/w *
100-41-4	ethylbenzene	1-5% w/w *
80-62-6	methyl methacrylate	0.1-1% w/w *
* Actual con	contration ranges are withheld as a trade secret	

Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

CA



Page 4/14

(Contd. of page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

CA



Page 5/14

(Contd. of page 4)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

	non parameters nponents with limit values that require monitoring at the workplace:
133	0-20-7 xylene
EL	STEL: 150 ppm TWA: 100 ppm
EV	STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm
123	-86-4 n-butyl acetate
EL	STEL: 150 ppm TWA: 50 ppm
EV	STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm
100	-41-4 ethylbenzene
EL	TWA: 20 ppm IARC 2B
EV	STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm
80-	62-6 methyl methacrylate
EL	STEL: 100 ppm TWA: 50 ppm S(D)
EV	STEL: 100 ppm TWA: 50 ppm
· Add	ditional information: The lists that were valid during the creation were used as basis. (Contd. on page 6) Contd. on page 6)



Page 6/14

(Contd. of page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)



Safety Data Sheet according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 6)

Page 7/14

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Black
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C
Flash point:	25 °C
Flammability:	Flammable.
Auto igniting:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive an vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.992 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

CA



according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Page 8/14

Trade name: GRRAL9005 2K DEEP BLACK

		(Contd. of page 7)
· Solvent content:		
Organic solvents:	50.7 %	
Coating VOC content:	50.70 %	
-	503.0 g/l / 4.20 lb/gal	
Material VOC content:	503.0 g/l / 4.20 lb/gal	
Solids content:	49.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 9)





Page 9/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 8)

3

3

2B

2B

· carcinoge	nic calegories
· IARC (Inte	rnational Agency for Research on Cancer)
4000 00 7	

1330-20-7 xylene 100-41-4 ethylbenzene

Carainagania astagarias

80-62-6 methyl methacrylate

97-88-1 n-butyl methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 10)



Page 10/14

Safety Data Sheet according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 9)

CA

· UN-Number · DOT/TDG, ADR, IMDG, IATA	UN1263	
· UN proper shipping name · DOT/TDG · ADR · IMDG, IATA	Paint 1263 Paint PAINT	
· Transport hazard class(es)		
· DOT/TDG (Transport dangerous go	oods):	
- Class - Label	3 Flammable liquids 3	
ADR, IMDG, IATA	3 Flammable liquids	
Label	3	
· Packing group · DOT/TDG, ADR, IMDG, IATA	<i>III</i>	
• Environmental hazards: • Marine pollutant:	No	
 Special precautions for user EMS Number: Stowage Category 	Warning: Flammable liquids F-E, <u>S-E</u> A	
 Transport in bulk according to Ann MARPOL73/78 and the IBC Code 	ex II of Not applicable.	
· Transport/Additional information:		
· DOT/TDG · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L	



Page 11/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

 ADR
 Excepted quantities (EQ)
 Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG
 Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 UN "Model Regulation":

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara

None of the	e ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
80-62-6	methyl methacrylate	
872-50-4	N-methyl-2-pyrrolidone	
TSCA (Tox	ic Substances Control Act):	
1330-20-7	7 xylene	ACTIV
123-86-4	n-butyl acetate	ACTIV
100-41-4	ethylbenzene	ACTIV
80-62-6	methyl methacrylate	ACTIV
868-77-9	2-hydroxyethyl methacrylate	ACTIV
136-53-8	ZINC 2-ETHYLEXANOATE	ACTIV
872-50-4	N-methyl-2-pyrrolidone	ACTIV
97-88-1	n-butyl methacrylate	ACTIV
64742-88-7	Solvent naphtha (petroleum), medium aliph.	ACTIV
77-58-7	dibutyltin dilaurate	ACTIV
7447 44 0	lithium chloride	ACTIV



Page 12/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

. Canadian s	(Contd. of page
	omestic Substances List (DSL)
1330-20-7	
123-86-4	n-butyl acetate
100-41-4	ethylbenzene
80-62-6	methyl methacrylate
868-77-9	2-hydroxyethyl methacrylate
136-53-8	ZINC 2-ETHYLEXANOATE
872-50-4	N-methyl-2-pyrrolidone
97-88-1	n-butyl methacrylate
64742-88-7	Solvent naphtha (petroleum), medium aliph.
77-58-7	dibutyltin dilaurate
7447-41-8	lithium chloride
· Canadian N	on-Domestic Substances List (NDSL)
None of the	ingredients is listed.
· Canadian Iı	ngredient Disclosure list (limit 0.1%)
100-41-4 ei	hylbenzene
· Canadian II	ngredient Disclosure list (limit 1%)
123-86-4 n·	butyl acetate
• GHS label e The product • Hazard pict	is classified and labeled according to the Globally Harmonized System (GHS).

GHS02 GHS07 GHS08

· Signal word Warning

Hazard-determining components of labeling: ethylbenzene methyl methacrylate
Hazard statements
Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 13)

- CA



Page 13/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

(Contd. of page 12) · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 12/02/2024 / 1.0
- Abbreviations and acronyms: ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 14)

CA



according to HPR, Schedule 1

Printing date 12/02/2024

Reviewed on 12/02/2024

Trade name: GRRAL9005 2K DEEP BLACK

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

(Contd. of page 13)

Page 14/14

CA -