

Page 1/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 729 BASECOAT BRIGHT YELLOW
- · Article number: 729
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids - Category 3 H226 Flammable liquid and vapour. GHS08 Health hazard H351 Suspected of causing cancer. Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs - Category 2 through prolonged or repeated exposure. GHS07 Skin Irritation - Category 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3 · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) CA



Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Page 2/13

Trade name: 729 BASECOAT BRIGHT YELLOW

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapour. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. (Contd. on page 3)



Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

Dispose of contents/container in accordance with local/regional/national/international regulations.

• NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE3Fire = 3REACTIVITY0Reactivity = 0

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	n-butyl acetate	30-60% w/w *
1330-20-7	xylene	10-30% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	3-7% w/w *
108-65-6	2-methoxy-1-methylethyl acetate	3-7% w/w *
100-41-4	ethylbenzene	0.5-1.5% w/w *
* Actual con	centration ranges are withheld as a trade secret.	•

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

CA

Page 3/13

(Contd. of page 2)



Page 4/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

• Indication of any immediate medical attention and special treatment needed No further relevant information available. (Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.

 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

(Contd. on page 5)

CA



Page 5/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Co	ntrol parameters
· Co	mponents with limit values that require monitoring at the workplace:
123	8-86-4 n-butyl acetate
EL	STEL: 150 ppm TWA: 50 ppm
	TWA: 50 ppm
EV/	STEL: 050 ma/m ³ 200 ppm

V STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm

1330-20-7 xylene

- EL STEL: 150 ppm TWA: 100 ppm EV STEL: 650 mg/m³, 150 ppm
- TWA: 435 mg/m³, 100 ppm

108-65-6 2-methoxy-1-methylethyl acetate

- EL STEL: 75 ppm TWA: 50 ppm
- EV TWA: 270 mg/m³, 50 ppm

100-41-4 ethylbenzene

- EL TWA: 20 ppm IARC 2B
- EV STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

(Contd. on page 6)



Page 6/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

(Contd. of page 5)

ely. skin. / pollution use respiratory filter de	vice. In case of intensive or longer rculating air.
nmendation to the glove material e. on consideration of the penetration wes does not only depend on the m acturer to manufacturer. As the p e glove material can not be calcula on. erial his to be found out by the manufactu	uct/ the substance/ the preparation. can be given for the product/ the on times, rates of diffusion and the naterial, but also on further marks of product is a preparation of several ted in advance and has therefore to urer of the protective gloves and has
operties	
and chemical properties Liquid Yellow	
	ive device that is independent of cill permeable and resistant to the prod mendation to the glove material e. on consideration of the penetration ves does not only depend on the macturer to manufacturer. As the p e glove material can not be calcula on. erial as to be found out by the manufacturer operties and chemical properties Liquid

· Odor threshold:

Not determined.

(Contd. on page 7)

CA



Page 7/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

pH-value:	(Contd. of page 6 Not determined.
•	Not determined.
Change in condition	Undetermined
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 120 °C
0, 00	
Flash point:	27 °C
Flammability:	Flammable.
Auto igniting:	315 ℃
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air
5	vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.962 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	75.2 %
Coating VOC content:	75.18 %
	723.3 g/l / 6.04 lb/gal
Material VOC content:	723.3 g/l / 6.04 lb/gal
Solids content:	22.9 %
Other information	No further relevant information available.

(Contd. on page 8)



Page 8/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

(Contd. of page 7)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:
--

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)
--

1330-20-7 xylene

100-41-4 ethylbenzene

111-76-2 2-butoxyethanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)

3

3

2B



Page 9/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

(Contd. of page 8)

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT/TDG, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT/TDG	Paint	
ADR	1263 Paint	
IMDG, IATA	PAINT	



Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

	(Contd. of pag
Transport hazard class(es)	
DOT/TDG (Transport dangerous good	ls):
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT/TDG, ADR, IMDG, IATA	<i>III</i>
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number: Stowage Category	F-E, <u>S-E</u> A
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT/TDG	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ)	5L
	(Contd. on page

Page 10/13

CA 🚽



Page 11/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

	(Contd. of page 10)
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

None of the	ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
111-76-2	2-butoxyethanol	
TSCA (Tox	ic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
Canadian s	ubstance listings:	1
Canadian D	Domestic Substances List (DSL)	
123-86-4	n-butyl acetate	
1330-20-7	xylene	
108-65-6	2-methoxy-1-methylethyl acetate	
100-41-4	ethylbenzene	
111-76-2	2-butoxyethanol	
107-98-2	1-methoxy-2-propanol	
70657-70-4	2-methoxypropyl acetate	
Canadian N	Ion-Domestic Substances List (NDSL)	
None of the	ingredients is listed.	
		(Contd. on page 1



Page 12/13

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 729 BASECOAT BRIGHT YELLOW

Canadian Ingredi	ent Disclosure list (limit 0.1%)	(Contd. of page 1
100-41-4 ethylber	• • •	
Canadian Ingredi	ent Disclosure list (limit 1%)	
123-86-4 n-butyl a	icetate	
GHS label elemen The product is class Hazard pictogram	sified and labeled according to	the Globally Harmonized System (GHS).
GHS02 GHS07	GHS08	
Signal word Warr	ling	
n-butyl acetate ethylbenzene Hazard statemen Flammable liquid a Causes skin irritati Suspected of caus May cause drowsi May cause drowsi Mean potentiation IF ON SKIN (or ha IF INHALED: Rem IF exposed or con Call a poison cent	and vapour. on. ing cancer. ness or dizziness. e to the hearing organs through atements s needed, have product contained of children. use. ructions before use. I all safety precautions have bee eat, hot surfaces, sparks, open f container and receiving equipme of [electrical/ventilating/lighting] tools. event static discharges. st/fume/gas/mist/vapours/spray. ofter handling. or in a well-ventilated area. oves/protective clothing/eye pro	en read and understood. lames and other ignition sources. No smoking. ent. equipment. tection/face protection. raminated clothing. Rinse skin with water [or showe. o comfortable for breathing.
Specific treatment	(see on this label).	(Contd. on page 2



Page 13/13

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

(Contd. of page 12)

Trade name: 729 BASECOAT BRIGHT YELLOW

Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Date of the latest revision of the safety data sheet 10/09/2024 / 1.1
- · Abbreviations and acronyms: ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative • * Data compared to the previous version altered.

CA