

Page 1/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 745 BASECOAT OXIDE RED
- · Article number: 745
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

• Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

GHS02 GHS07 GHS08

Classification of the substance or mixture
 GHS02 Flame
 Flammable Liquids - Category 3
 H226 Flammable liquid and vapour.
 GHS08 Health hazard
 Carcinogenicity - Category 2
 H351 Suspected of causing cancer.
 GHS07
 Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3
 Label elements
 GHS label elements
 The product is classified and labeled according to the Globally Harmonized System (GHS).
 Hazard pictograms

(Contd. on page 2)

CA



Page 2/12

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

Signal word	Warning (Contd. of page
•	ermining components of labeling:
n-butyl acet	
ethylbenzen	
Hazard stat	
	liquid and vapour.
	f causing cancer.
	drowsiness or dizziness.
	ary statements
	dvice is needed, have product container or label at hand.
	reach of children.
Read label l	
	ial instructions before use.
	le until all safety precautions have been read and understood.
	from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	bond container and receiving equipment.
	on-proof [electrical/ventilating/lighting] equipment.
Use non-spa	
	s to prevent static discharges.
	ning dust/fume/gas/mist/vapours/spray.
	tdoors or in a well-ventilated area.
	tive gloves/protective clothing/eye protection/face protection.
	(or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower
	: Remove person to fresh air and keep comfortable for breathing.
	or concerned: Get medical advice/attention.
	n center/doctor if you feel unwell.
	e: Use CO2, powder or water spray to extinguish.
	ell-ventilated place. Keep container tightly closed.
	ell-ventilated place. Keep cool.
Store locked	
	contents/container in accordance with local/regional/national/international regulations.
Classificati	
	gs (scale 0 - 4)
•	
	Health = 0
	Fire = 3
	Reactivity = 0
• HMIS-rating	ys (scale 0 - 4)
HEALTH 0	Health = 0
FIRE 3	
	Fire = 3 Reactivity = 0



Page 3/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

(Contd. of page 2)

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

0			
	n-butyl acetate	30-60% w/w *	
1330-20-7	xylene	5-10% w/w *	
108-65-6	2-methoxy-1-methylethyl acetate	3-7% w/w *	
64742-95-6	Solvent naphtha (petroleum), light arom.	1-5% w/w *	
100-41-4	ethylbenzene	0.1-1% w/w *	
* Actual concentration ranges are withheld as a trade secret.			

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)



Page 4/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

(Contd. of page 3)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental procautions: Do not allow to enter sewers/ surface or ground
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

CA



Page 5/12

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

	(Contd. of page 4)
	ntrol parameters
	nponents with limit values that require monitoring at the workplace:
	-86-4 n-butyl acetate
	STEL: 150 ppm TWA: 50 ppm
EV	STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm
133	0-20-7 xylene
EL	STEL: 150 ppm TWA: 100 ppm
EV	STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm
108	-65-6 2-methoxy-1-methylethyl acetate
	STEL: 75 ppm TWA: 50 ppm
EV	TWA: 270 mg/m ³ , 50 ppm
100	-41-4 ethylbenzene
EL	TWA: 20 ppm IARC 2B
EV	STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm
· Add	litional information: The lists that were valid during the creation were used as basis.
· Per · Ger Kee Imn Was Stor · Bre In c exp	osure controls sonal protective equipment: meral protective and hygienic measures: op away from foodstuffs, beverages and feed. nediately remove all soiled and contaminated clothing. sh hands before breaks and at the end of work. re protective clothing separately. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe osure use respiratory protective device that is independent of circulating air. tection of hands:
PHI	Protective gloves
The	glove material has to be impermeable and resistant to the product/ the substance/ the preparation (Contd. on page 6



Page 6/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Red	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	124 °C	
Flash point:	27 °C	
Flammability:	Flammable.	
Auto igniting:	315 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	



Page 7/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

	(Contd. of page
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.04 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/w	ater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	70.1 %
Coating VOC content:	70.07 %
	728.8 g/l / 6.08 lb/gal
Material VOC content:	728.8 g/l / 6.08 lb/gal
Solids content:	29.9 %
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

CA



Page 8/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

(Contd. of page 7)

		at are relevant for classification:	
	n-butyl ace		
Oral	LD50	13,100 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/l (rat)	
• on the eye • Sensitizat	e: No irritat tion: No se	ensitizing effects known.	
• on the eye • Sensitizat • Additiona The produce preparatio	e: No irritat tion: No se al toxicolog uct shows ons:	ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation metho	ods f
 on the eyo Sensitization Additiona The production preparatio Carcinoge 	e: No irritat tion: No se al toxicolog uct shows ns: enic categ	ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation metho gories	ods f
 on the eyo Sensitization Additiona The production preparatio Carcinoge 	e: No irritat tion: No se al toxicolog uct shows ns: enic categ ernational	ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation metho	ods f
 on the eyo Sensitization Additiona The production preparatio Carcinogo IARC (Intel 1330-20-7) 	e: No irritat tion: No se al toxicolog uct shows ns: enic categ ernational	ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation metho gories Agency for Research on Cancer)	

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 9)

CA



Page 9/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

4 Transport information · UN-Number · DOT/TDG, ADR, IMDG, IATA UN1263 · UN proper shipping name · DOT/TDG Paint · ADR 1263 Paint · IMDG, IATA PAINT · Transport hazard class(es) · DOT/TDG (Transport dangerous goods): · Class 3 Flammable liquids · Label 3 · ADR, IMDG, IATA · Class 3 Flammable liquids · Label 3 · Packing group · DOT/TDG, ADR, IMDG, IATA $\parallel \parallel$ (Contd. on page 10) CA

(Contd. of page 8)



Page 10/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

	(Contd. of page
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	II of Not applicable.
<i>Transport/Additional information: DOT/TDG Quantity limitations</i>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

None of the ingredients is listed. Section 313 (Specific toxic chemical listings): 1330-20-7 xylene 100-41-4 ethylbenzene	
1330-20-7 xylene	
100-41-4 ethylbenzene	
111-76-2 2-butoxyethanol	
TSCA (Toxic Substances Control Act):	
123-86-4 n-butyl acetate	ACTIVE
1330-20-7 xylene	ACTIVE
	(Contd. on page 1



Page 11/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

		(Contd. of page 10)
	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
· Canadian	substance listings:	
· Canadian	Domestic Substances List (DSL)	
123-86-4	n-butyl acetate	
1330-20-7	xylene	
108-65-6	2-methoxy-1-methylethyl acetate	
100-41-4	ethylbenzene	
107-98-2	1-methoxy-2-propanol	
111-76-2	2-butoxyethanol	
70657-70-4	2-methoxypropyl acetate	
· Canadian	Non-Domestic Substances List (NDSL)	
None of the	ingredients is listed.	
· Canadian	ngredient Disclosure list (limit 0.1%)	
100-41-4 e	thylbenzene	
· Canadian	ngredient Disclosure list (limit 1%)	
123-86-4 r	-butyl acetate	
GHS Jahol	elements	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: n-butyl acetate ethylbenzene
 Hazard statements
- Flammable liquid and vapour. Suspected of causing cancer. May cause drowsiness or dizziness.
- **Precautionary statements** If medical advice is needed, have product container or label at hand. Keep out of reach of children.

(Contd. on page 12)

⁻ CA



Page 12/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/09/2024

Reviewed on 07/29/2024

Trade name: 745 BASECOAT OXIDE RED

(Contd. of page 11)

Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- Contact: N/A
- · Date of the latest revision of the safety data sheet 10/09/2024 / 1.1

· Abbreviations and acronyms:

- ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent. Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- * Data compared to the previous version altered.