

Page 1/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 764C BASECOAT ORANGE DOME
- · Article number: 764C
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

• Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture



Flammable Liquids - Category 3 Substances and Mixtures Which, in Contact with Water, Emit Flammable Gases - Category 1

H226 Flammable liquid and vapour. H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS08 Health hazard

Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs - Category 2 through prolonged or repeated exposure.

GHS07

Skin Irritation - Category 2
Eye Irritation - Category 2A
Specific Target Organ Toxicity - Single Exposure -
Category 3

H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Page 2/14


Trade name: 764C BASECOAT ORANGE DOME

(Contd. of page 1) Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene methyl acetate ethvlbenzene n-butyl acetate · Hazard statements Flammable liquid and vapour. In contact with water releases flammable gases which may ignite spontaneously. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not allow contact with water. Handle and store contents under inert gas. Protect from moisture. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Brush off loose particles from skin. Immerse in cool water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)



according to HPR, Schedule 1



3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

79-20-9 methyl acetate	10-30% w/w *
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	10-30% w/w *
64742-95-6 Solvent naphtha (petroleum), light arom.	3-7% w/w *
1330-20-7 xylene	1-5% w/w *
123-86-4 n-butyl acetate	1-5% w/w *
763-69-9 ethyl 3-ethoxypropionate	1-5% w/w *
100-41-4 ethylbenzene	0.5-1.5% w/w *
	(Contd. on page 4)

Page 3/14



Page 4/14

(Contd. of page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Extinguishing powder. Do not use water.
 CO2. Do not use water.
 Sand. Do not use water.
 Special powder for metal fires. Do not use water.
 CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 5)



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Page 5/14

Trade name: 764C BASECOAT ORANGE DOME

(Contd. of page 4) · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 7 Handling and storage · Handling: · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols. · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available. · Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: No special requirements. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. · Storage class: 4.3 · Specific end use(s) No further relevant information available. 8 Exposure controls/ Personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

EL STEL: 250 ppm TWA: 200 ppm

(Contd. on page 6)

CA



Page 6/14

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

	(Contd. of page 5)
EV	STEL: 755 mg/m³, 250 ppm
	TWA: 605 mg/m³, 200 ppm
133	80-20-7 xylene
EL	STEL: 150 ppm
	TWA: 100 ppm
EV	STEL: 650 mg/m³, 150 ppm
	TWA: 435 mg/m³, 100 ppm
123	R-86-4 n-butyl acetate
EL	STEL: 150 ppm
	TWA: 50 ppm
ΕV	STEL: 950 mg/m ³ , 200 ppm
	TWA: 710 mg/m ³ , 150 ppm
	B-69-9 ethyl 3-ethoxypropionate
	TWA: 300 mg/m³, 50 ppm
100	-41-4 ethylbenzene
EL	TWA: 20 ppm
	IARC 2B
ΕV	STEL: 540 mg/m³, 125 ppm
	TWA: 435 mg/m³, 100 ppm
Add	ditional information: The lists that were valid during the creation were used as basis.
	posure controls
	sonal protective equipment:
	neral protective and hygienic measures:
	ep away from foodstuffs, beverages and feed.
	nediately remove all soiled and contaminated clothing. sh hands before breaks and at the end of work.
	re protective clothing separately.
	bid contact with the eyes and skin.
	eathing equipment:
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe
	osure use respiratory protective device that is independent of circulating air.
Pro	tection of hands:
11	
	Protective gloves
	Protective gloves
T	
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due	Protective gloves e glove material has to be impermeable and resistant to the product/ the substance/ the preparation. e to missing tests no recommendation to the glove material can be given for the product/ the paration/ the chemical mixture.

(Contd. on page 7)

CA



Page 7/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

(Contd. of page 6) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and c General Information Appearance: 	hemical properties
Form:	Liquid
Color:	Orange
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 57 °C
· Flash point:	27 °C
· Flammability:	Flammable. Contact with water liberates extremely flammable gases.
· Auto igniting:	450 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
	(Contd. on page 8)



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

	(C	ontd. of page
• Explosion limits:		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
· Vapor pressure at 20 °C:	220 hPa	
· Density at 20 °C:	1.09 g/cm³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	71.2 %	
Coating VOC content:	17.43 %	
	416.0 g/l / 3.47 lb/gal	
Material VOC content:	190.0 g/l / 1.59 lb/gal	
Solids content:	28.7 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions Contact with water releases flammable gases.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 9)

Page 8/14



Page 9/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

(Contd. of page 8)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	•	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

- General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 10)



Page 10/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

(Contd. of page 9)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

7					
	146		TATE		tion
1			,,,,,	orma	
	and the second	the second s			

· UN-Number	10//000
· DOT/TDG, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT/TDG	Paint
ADR	1263 Paint
· IMDG, IATA	PAINT
Transport hazard class(es)	
DOT/TDG (Transport dangerous goods):	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT/TDG, ADR, IMDG, IATA	<i>III</i>
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
	(Contd. on page 11



Page 11/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

	(Contd. of page
EMS Number: Stowage Category	F-E, <u>S-E</u> A
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	II of Not applicable.
Transport/Additional information:	
DOT/TDG Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Sara

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): 1330-20-7 xylene 100-41-4 ethylbenzene 7664-38-2 phosphoric acid · TSCA (Toxic Substances Control Act): 79-20-9 methyl acetate ACTIVE 98-56-6 4-chloro-alpha, alpha, alpha-trifluorotoluene ACTIVE 9004-36-8 cellulose acetate butyrate ACTIVE 1330-20-7 xylene ACTIVE 123-86-4 n-butyl acetate ACTIVE (Contd. on page 12)



Page 12/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

		Contd. of page 11
	ethyl 3-ethoxypropionate	ACTIVE
	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
Canadian	substance listings:	·
· Canadian I	Domestic Substances List (DSL)	
79-20-9	methyl acetate	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
1330-20-7	xylene	
123-86-4	n-butyl acetate	
763-69-9	ethyl 3-ethoxypropionate	
100-41-4	ethylbenzene	
107-98-2	1-methoxy-2-propanol	
108-65-6	2-methoxy-1-methylethyl acetate	
7664-38-2	phosphoric acid	
70657-70-4	2-methoxypropyl acetate	
· Canadian I	Non-Domestic Substances List (NDSL)	
None of the	ingredients is listed.	
· Canadian I	ngredient Disclosure list (limit 0.1%)	
100-41-4 e	thylbenzene	
· Canadian I	ngredient Disclosure list (limit 1%)	
79-20-9 n	nethyl acetate	
123-86-4 n	-butyl acetate	
· GHS label	elements t is classified and labeled according to the Globally Harmonized System (GHS	

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

• *Hazard-determining components of labeling:* 4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate ethylbenzene

(Contd. on page 13)

CA



Page 13/14

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

	(Contd. of page 1
n-butyl acetate	
Hazard statements	
Flammable liquid and vapou	
	es flammable gases which may ignite spontaneously.
Causes skin irritation.	
Causes serious eye irritatio	
Suspected of causing cance	
May cause drowsiness or d	
	earing organs through prolonged or repeated exposure.
Precautionary statements	
	have product container or label at hand.
Keep out of reach of childre	n.
Read label before use.	
Obtain special instructions l	
	/ precautions have been read and understood.
	urfaces, sparks, open flames and other ignition sources. No smoking.
Do not allow contact with wa	
	Inder inert gas. Protect from moisture.
Ground and bond container	
	cal/ventilating/lighting] equipment.
Use non-sparking tools.	
Take actions to prevent stat	•
Do not breathe dust/fume/g	
Wash thoroughly after hand	
Use only outdoors or in a w	
	ective clothing/eye protection/face protection.
	e particles from skin. Immerse in cool water.
F INHALED: Remove perso	off immediately all contaminated clothing. Rinse skin with water [or shower on to fresh air and keep comfortable for breathing.
F IN EYES: Rinse cautiou	sly with water for several minutes. Remove contact lenses, if present ar
easy to do. Continue rinsing	
	et medical advice/attention.
Call a poison center/doctor	
Specific treatment (see on t	
Get medical advice/attention	
	ing and wash it before reuse.
f skin irritation occurs: Get	
f eye irritation persists: Get	
	nd, extinguishing powder to extinguish.
Store in a dry place. Store i	
	ace. Keep container tightly closed.
Store in a well-ventilated pla	ice. Keep cool.
Store locked up.	
Dispose of contents/contain	er in accordance with local/regional/national/international regulations. (Contd. on page 1



Page 14/14

(Contd. of page 13)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 764C BASECOAT ORANGE DOME

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 10/16/2024 / 1.1

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative

* * Data compared to the previous version altered.