

Page 1/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 771C BASECOAT GOLD DOME
- · Article number: 771C
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut **LEBANON** info@generalpaint.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids - Category 3 Substances and Mixtures Which, in Contact with Water, Emit Flammable Gases - Category 1

H226 Flammable liquid and vapour. H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS08 Health hazard

Germ Cell Mutagenicity - Category 1B H340 May cause genetic defects. Carcinogenicity - Category 1B H350 May cause cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs Category 2 through prolonged or repeated exposure.

GHS07

Skin Irritation - Category 2 Eye Irritation - Category 2A Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3

H315 Causes skin irritation. H319 Causes serious eye irritation.

(Contd. on page 2)



Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Page 2/14

(Contd. of page 1)

· Label elements · GHS label elements

Trade name: 771C BASECOAT GOLD DOME

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: 4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate Naphtha (petroleum), hydrotreated heavy ethylbenzene Hazard statements Flammable liquid and vapour. In contact with water releases flammable gases which may ignite spontaneously. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not allow contact with water. Handle and store contents under inert gas. Protect from moisture. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Brush off loose particles from skin. Immerse in cool water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (Contd. on page 3)



Page 3/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 2) IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, sand, extinguishing powder to extinguish. Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 2The substance demonstrates unusual reactivity with water. · HMIS-ratings (scale 0 - 4) HEALTH *2 Health = *23 Fire = 3FIRE Reactivity = 2**REACTIVITY** 2 3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
79-20-9	methyl acetate	15-40% w/w *
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-30% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	3-7% w/w *
7429-90-5	aluminium powder (stabilised)	1-5% w/w *
1330-20-7	xylene	1-5% w/w *
		(Contd. on page 4)



Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

		(Contd. of page 3)
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1-5% w/w *
763-69-9	ethyl 3-ethoxypropionate	1-5% w/w *
		0.5-1.5% w/w *
* Actual con	centration ranges are withheld as a trade secret.	

4 First-aid measures

- · Description of first aid measures
- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Extinguishing powder. Do not use water. CO2. Do not use water.
- Sand. Do not use water.

Special powder for metal fires. Do not use water.

- CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 5)

Page 4/14



Page 5/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 4)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 Reference to other sections Soo Soction 7 for information on safe handling
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Storage class: 4.3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

• Additional information about design of technical systems: No further data; see section 7.



Page 6/14

Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

	(Contd. of page 5
	ntrol parameters
	mponents with limit values that require monitoring at the workplace:
	20-9 methyl acetate
	STEL: 250 ppm TWA: 200 ppm
EV	STEL: 755 mg/m³, 250 ppm TWA: 605 mg/m³, 200 ppm
133	0-20-7 xylene
EL	STEL: 150 ppm TWA: 100 ppm
EV	STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm
763	-69-9 ethyl 3-ethoxypropionate
ΕV	TWA: 300 mg/m ³ , 50 ppm
100	-41-4 ethylbenzene
EL	TWA: 20 ppm IARC 2B
EV	STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm
· Ade	ditional information: The lists that were valid during the creation were used as basis.
Ex	posure controls
	sonal protective equipment:
	neral protective and hygienic measures:
	ep away from foodstuffs, beverages and feed.
	nediately remove all soiled and contaminated clothing.
	sh hands before breaks and at the end of work. re protective clothing separately.
	bid contact with the eyes and skin.
	eathing equipment:
	case of brief exposure or low pollution use respiratory filter device. In case of intensive or longe
exp	osure use respiratory protective device that is independent of circulating air.
· Pro	tection of hands:
PH	Protective gloves
Due	e glove material has to be impermeable and resistant to the product/ the substance/ the preparation e to missing tests no recommendation to the glove material can be given for the product/ th paration/ the chemical mixture.
סיק	

(Contd. on page 7) CA



Page 7/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 6) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and c General Information Appearance:	hemical properties
Form:	Liquid
Color:	0011
· pH-value:	Not determined.
Melting point/Melting range:	
· Flash point:	27 °C
· Flammability:	
· Auto igniting:	450 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
	(Contd. on page 8)



Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

	(Contd. of p	page
Explosion limits:		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
Vapor pressure at 20 °C:	220 hPa	
Density at 20 °C:	1.09 g/cm ³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	73.7 %	
Coating VOC content:	15.54 %	
	418.7 g/l / 3.49 lb/gal	
Material VOC content:	169.4 g/l / 1.41 lb/gal	
Solids content:	28.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions Contact with water releases flammable gases.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 9)

Page 8/14



Page 9/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 8)

2B

3 2B

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· Carcinogenic categories

IARC (International Agency for Research on Cancer)
 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene
 1330-20-7 xylene
 100-41-4 ethylbenzene
 NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 10)



Page 10/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 9)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

7			
	Iranc	nort.	mation
1			rmation

· UN-Number	
· DOT/TDG, ADR, IMDG, IATA	UN1263
 UN proper shipping name 	
· DOT/TDG	Paint
· ADR	1263 Paint
· IMDG, IATA	PAINT
 Transport hazard class(es) 	
· DOT/TDG (Transport dangerous goods):	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
Label	3
· Packing group	
· DOT/TDG, ADR, IMDG, IATA	<i>III</i>
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
	(Contd. on page 11)



Page 11/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

	(Contd. of page 7
EMS Number: Stowage Category	F-E, <u>S-E</u> A
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	Il of Not applicable.
Transport/Additional information:	
· DOT/TDG	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

	5 (extremely hazardous substances):	
	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
· TSCA (Tox	ic Substances Control Act):	
79-20-9	methyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
9004-36-8	cellulose acetate butyrate	ACTIVE
1330-20-7	zylene	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
		(Contd. on page 12)



Page 12/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

		d. of page 1
	ethylbenzene	ACTIVE
	1-methoxy-2-propanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
	phosphoric acid	ACTIVE
	ıbstance listings:	
· Canadian D	omestic Substances List (DSL)	
79-20-9	methyl acetate	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
1330-20-7	xylene	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	
763-69-9	ethyl 3-ethoxypropionate	
100-41-4	ethylbenzene	
107-98-2	1-methoxy-2-propanol	
108-65-6	2-methoxy-1-methylethyl acetate	
7664-38-2	phosphoric acid	
70657-70-4	2-methoxypropyl acetate	
· Canadian N	on-Domestic Substances List (NDSL)	
None of the	ingredients is listed.	
· Canadian In	gredient Disclosure list (limit 0.1%)	
100-41-4 et	hylbenzene	
· Canadian In	gredient Disclosure list (limit 1%)	
79-20-9 me	hyl acetate	
• GHS label e The product • Hazard pict	is classified and labeled according to the Globally Harmonized System (GHS).	



· Signal word Danger

• *Hazard-determining components of labeling:* 4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate Naphtha (petroleum), hydrotreated heavy ethylbenzene

(Contd. on page 13)

⁻ CA



Page 13/14

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

(Contd. of page 12) · Hazard statements Flammable liquid and vapour. In contact with water releases flammable gases which may ignite spontaneously. Causes skin irritation. Causes serious eve irritation. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not allow contact with water. Handle and store contents under inert gas. Protect from moisture. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Brush off loose particles from skin. Immerse in cool water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, sand, extinguishing powder to extinguish. Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 14)



Page 14/14

Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Trade name: 771C BASECOAT GOLD DOME

- (Contd. of page 13)
- National regulations:
 Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).
- Information about limitation of use:
 Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 10/16/2024 / 1.1
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative * Data compared to the previous version altered.