

Page 1/14

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## 1 Identification

- · Product identifier
- · Trade name: 781C BASECOAT CARBON BLACK
- · Article number: 781C
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids - Category 3 H226 Flammable liquid and vapour. GHS08 Health hazard H351 Suspected of causing cancer. Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs - Category 2 through prolonged or repeated exposure. GHS07 Skin Irritation - Category 2 H315 Causes skin irritation. H319 Causes serious eye irritation. Eye Irritation - Category 2A Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3 · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Page 2/14

#### Trade name: 781C BASECOAT CARBON BLACK

(Contd. of page 1) Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene methyl acetate ethylbenzene n-butyl acetate · Hazard statements Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. (Contd. on page 3)

CA




according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK



## 3 Composition/Information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	methyl acetate	15-40% w/w *
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	15-40% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	1-5% w/w *
1330-20-7	xylene	1-5% w/w *
123-86-4	n-butyl acetate	1-5% w/w *
100-41-4	ethylbenzene	0.5-1.5% w/w *
* Actual concentration ranges are withheld as a trade secret.		

#### 4 First-aid measures

## · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)



Page 4/14

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

#### Trade name: 781C BASECOAT CARBON BLACK

(Contd. of page 3)

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
   Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 5)



Page 5/14

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

#### Trade name: 781C BASECOAT CARBON BLACK

(Contd. of page 4)

## 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Cor	ontrol parameters	
· Cor	<ul> <li>Components with limit values that require monitoring at the workplace:</li> </ul>	
79-2	-20-9 methyl acetate	
EL	STEL: 250 ppm TWA: 200 ppm	
EV	/ STEL: 755 mg/m³, 250 ppm TWA: 605 mg/m³, 200 ppm	
133	30-20-7 xylene	
EL	STEL: 150 ppm TWA: 100 ppm	
EV	/ STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm	
123	3-86-4 n-butyl acetate	
EL	STEL: 150 ppm TWA: 50 ppm	
EV	/ STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm	
		(Contd. on page 6)



Page 6/14

(Contd. of page 5)

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

## 100-41-4 ethylbenzene

EL TWA: 20 ppm

IARC 2B

EV STEL: 540 mg/m<sup>3</sup>, 125 ppm TWA: 435 mg/m<sup>3</sup>, 100 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.
- Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

CA



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

Page 7/14

(Contd. of page 6)

## Trade name: 781C BASECOAT CARBON BLACK

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Color:	Black
Odor:	Characteristic Not determined
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C
Flash point:	25 °C
Flammability:	Flammable.
Auto igniting:	455 ℃
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C:	220 hPa
Density at 20 °C:	1.076 g/cm³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.



Page 8/14

## Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

	(Contd. d	of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	76.6 %	
Coating VOC content:	15.24 %	
-	412.5 g/l / 3.44 lb/gal	
Material VOC content:	164.0 g/l / 1.37 lb/gal	
Solids content:	23.4 %	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 9)



Page 9/14

(Contd. of page 8)

2B

3

2B

# Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 10)



Page 10/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

(Contd. of page 9)

· UN-Number · DOT/TDG, ADR, IMDG, IATA	UN1263	
UN proper shipping name	011200	
DOT/TDG	Paint	
ADR	1263 Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT/TDG (Transport dangerous go	oods):	
Class	3 Flammable liquids	
Label	3	
ADR, IMDG		
Class Label	3 Flammable liquids 3	
IATA	5	
Class	6.1 Toxic substances	
Label	3	
Packing group		
DOT/TDG, IMDG	Void	
ADR, IATA	III	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-E	

CA



Page 11/14

## Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

	(Contd. of page
Stowage Category	A
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	r <b>II of</b> Not applicable.
Transport/Additional information:	
DOT/TDG	
Quantity limitations	On passenger aircraft/rail: 60 L
-	On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

## 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
100-41-4 ethylbenzene	
TSCA (Toxic Substances Control Act):	
79-20-9 methyl acetate	ACTIVE
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
9004-36-8 cellulose acetate butyrate	ACTIVE
1330-20-7 xylene	ACTIVE
123-86-4 n-butyl acetate	ACTIVE
	ACTIVE
100-41-4 ethylbenzene	



Page 12/14

## Safety Data Sheet

according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

107-98-2	1-methoxy-2-propanol (Contd. of page 11 ACTIVE
	substance listings:
· Canadian	Domestic Substances List (DSL)
79-20-9	methyl acetate
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
1330-20-7	xylene
123-86-4	n-butyl acetate
100-41-4	ethylbenzene
108-65-6	2-methoxy-1-methylethyl acetate
107-98-2	1-methoxy-2-propanol
· Canadian	Non-Domestic Substances List (NDSL)
None of the	e ingredients is listed.
· Canadian	Ingredient Disclosure list (limit 0.1%)
100-41-4	ethylbenzene
· Canadian	Ingredient Disclosure list (limit 1%)
79-20-9 i	methyl acetate
123-86-4	n-butyl acetate
GHS label	elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling:
4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate ethylbenzene n-butyl acetate
Hazard statements Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 13)

CA



Page 13/14

## Safety Data Sheet

according to HPR, Schedule 1

#### Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

(Contd. of page 12) · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 10/16/2024 / 1.0

 Abbreviations and acronyms: ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 14)

<sup>-</sup> C,



according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

## Trade name: 781C BASECOAT CARBON BLACK

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative

• \* Data compared to the previous version altered.

#### \_\_\_\_

(Contd. of page 13)

Page 14/14