

Page 1/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024

Reviewed on 07/29/2024

### 1 Identification

- · Product identifier
- · Trade name: 794C BASECOAT MET. COARSE
- · Article number: 794C
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON
- info@generalpaint.biz
- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure H372-H373 Causes damage to the central

- Category 1 nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated

exposure.



Skin Irritation - Category 2 H315 Causes skin irritation.

Eye Irritation - Category 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness.

Category 3

(Contd. on page 2)



Page 2/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 1)

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene

methyl acetate

Stoddard solvent

ethylbenzene

### · Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take actions to prevent static discharges.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)



Page 3/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

#### Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 2)

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

## 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:		
79-20-9	methyl acetate	15-40% w/w *	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	15-40% w/w *	
64742-95-6	Solvent naphtha (petroleum), light arom.	3-7% w/w *	
7429-90-5	aluminium powder (stabilised)	1-5% w/w *	
1330-20-7	xylene	1-5% w/w *	
763-69-9	ethyl 3-ethoxypropionate	0.5-1.5% w/w *	
8052-41-3	Stoddard solvent	0.5-1.5% w/w *	
100-41-4	ethylbenzene	0.5-1.5% w/w *	
		(Contd. on page 4)	

CA



Page 4/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

\* Actual concentration ranges are withheld as a trade secret.

(Contd. of page 3)

### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- $\cdot$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Page 5/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 4)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

### 79-20-9 methyl acetate

EL STEL: 250 ppm

TWA: 200 ppm

EV STEL: 755 mg/m³, 250 ppm TWA: 605 mg/m³, 200 ppm

### 1330-20-7 xylene

EL STEL: 150 ppm TWA: 100 ppm

(Contd. on page 6)



Page 6/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

	(Contd. of page 5)
EV	STEL: 650 mg/m³, 150 ppm
	TWA: 435 mg/m³, 100 ppm
763	-69-9 ethyl 3-ethoxypropionate
EV	TWA: 300 mg/m³, 50 ppm
805	2-41-3 Stoddard solvent
EL	STEL: 580 mg/m³
	TWA: 290 mg/m³
100	-41-4 ethylbenzene
EL	TWA: 20 ppm
	IARC 2B
EV	STEL: 540 mg/m³, 125 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:

TWA: 435 mg/m<sup>3</sup>, 100 ppm

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)



Page 7/14

according to HPR, Schedule 1

Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

· Penetration time of glove material

(Contd. of page 6)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Printing date 10/16/2024



Tightly sealed goggles

9 Physical and chemical properties		
<ul> <li>Information on basic physical and</li> <li>General Information</li> <li>Appearance:</li> <li>Form:</li> <li>Color:</li> </ul>	chemical properties  Liquid Silver grey	
· Odor: · Odor threshold:	Characteristic Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 57 °C	
· Flash point:	-10 °C	
· Flammability:	Highly flammable.	
· Auto igniting:	450 °C	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits: Lower: Upper:	3.1 Vol % 16 Vol %	
· Vapor pressure at 20 °C:	220 hPa	
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapor density</li> </ul>	1.1 g/cm³ Not determined. Not determined.	
	(Contd. on page 8)	

(Contd. on page 8)



Page 8/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

	(Contd.	of page
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/w	vater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	74.9 %	
Coating VOC content:	12.79 %	
•	375.1 g/l / 3.13 lb/gal	
Material VOC content:	140.7 g/l / 1.17 lb/gal	
Solids content:	23.7 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 9)



Page 9/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 8)

### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7		3
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

CA



Page 10/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 9)

Transport information	
UN-Number DOT/TDG, ADR, IMDG, IATA	UN1263
UN proper shipping name DOT/TDG ADR IMDG, IATA	Paint 1263 Paint PAINT
Transport hazard class(es)	
DOT/TDG (Transport dangerous god	ods):
Class Label	3 Flammable liquids 3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3 Tiaminable liquids 3
Packing group DOT/TDG, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	<b>ex II of</b> Not applicable.
Transport/Additional information:	

(Contd. on page 11)





# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 10)

· ADR
· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG
· Limited quantities (LQ)
· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	' hazardous	subsi	tances).	:
---------------	------------	-------------	-------	----------	---

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene 100-41-4 ethylbenzene 7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

· 13CA (Toxic Substances Control Act).		
		ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
9004-36-8	cellulose acetate butyrate	ACTIVE
1330-20-7	xylene	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
	ethylbenzene	ACTIVE
	1-methoxy-2-propanol	ACTIVE
	2-methoxy-1-methylethyl acetate	ACTIVE
7664-38-2	phosphoric acid	ACTIVE

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

79-20-9 methyl acetate

(Contd. on page 12)



Page 12/14

## Safety Data Sheet according to HPR, Schedule 1

Reviewed on 07/29/2024 Printing date 10/16/2024

Trade name: 794C BASECOAT MET. COARSE

	(Contd. of page 11)		
	4-chloro-alpha,alpha,alpha-trifluorotoluene		
1330-20-7	xylene		
763-69-9	ethyl 3-ethoxypropionate		
8052-41-3	Stoddard solvent		
100-41-4	ethylbenzene		
107-98-2	1-methoxy-2-propanol		
108-65-6	2-methoxy-1-methylethyl acetate		
7664-38-2	phosphoric acid		
70657-70-4	2-methoxypropyl acetate		
· Canadian I	Canadian Non-Domestic Substances List (NDSL)		
None of the	e ingredients is listed.		
· Canadian I	· Canadian Ingredient Disclosure list (limit 0.1%)		
100-41-4 e	thylbenzene		
· Canadian I	ngredient Disclosure list (limit 1%)		
79-20-9	methyl acetate		
8052-41-3	Stoddard solvent		

### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







## · Signal word Danger

### · Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate Stoddard solvent ethylbenzene

### Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 13)



Page 13/14

# Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 12)

### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take actions to prevent static discharges.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 10/16/2024 / 1.0
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 14)



Page 14/14

## Safety Data Sheet according to HPR, Schedule 1

Printing date 10/16/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 13)

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

· \* Data compared to the previous version altered.