

Page 1/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

1 Identification

- · Product identifier
- · Trade name: <u>S2232 REDUCER NORMAL</u>
- · Article number: S2232
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product Safety Department

• Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard identification		
· Classification of the substance or mixture		
GHS02 Flame		
Flammable Liquids - Category 2	H225	Highly flammable liquid and vapour.
GHS07		
Skin Irritation - Category 2	H315	Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure - Category 3		May cause respiratory irritation. May cause drowsiness or dizziness.
 Label elements GHS label elements The product is classified and labeled according to the transformer of the product is classified and labeled according to the transformer of the trans		armonized System (GHS).
GHS02 GHS07		
· Signal word Danger		
· Hazard-determining components of labeling:		
n-butyl acetate		(Contd. on page 2)



Page 2/12

Safety Data Sheet according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

Solvent nerbibe (netroleum) light erem	(Contd. of page
Solvent naphtha (petroleum), light arom.	
· Hazard statements	
Highly flammable liquid and vapour.	
Causes skin irritation.	
May cause respiratory irritation. May cause drowsiness or dizziness.	
Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Keep away from heat, hot surfaces, sparks, open flames and other ignition	sources. No smoking.
Ground and bond container and receiving equipment.	
Use explosion-proof [electrical/ventilating/lighting] equipment.	
Use non-sparking tools.	
Take actions to prevent static discharges.	
Avoid breathing dust/fume/gas/mist/vapours/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse	
IF INHALED: Remove person to fresh air and keep comfortable for breathin	ng.
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/int	ternational regulations.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = 3	
$\frac{1}{0} Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{1} Health = 1$	
FIRE 3 Fire = 3	
REACTIVITY 0 Reactivity = 0	



Page 3/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

(Contd. of page 2)

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

•	•	
123-86-4	n-butyl acetate	15-40% w/w *
1330-20-7	xylene	10-30% w/w *
64742-95-6	Solvent naphtha (petroleum), light arom.	10-30% w/w *
108-65-6	2-methoxy-1-methylethyl acetate	10-30% w/w *
763-69-9	ethyl 3-ethoxypropionate	1-5% w/w *
* Actual con	centration ranges are withheld as a trade secret	

Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)



Page 4/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

(Contd. of page 3)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers(surface or ground)
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation. • **Reference to other sections**

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

CA



Page 5/12

Safety Data Sheet according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	ing at the workplace:
 123-86-4 n-butyl acetate EL STEL: 150 ppm TWA: 50 ppm EV STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm 1330-20-7 xylene EL STEL: 150 ppm TWA: 100 ppm EV STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm 108-65-6 2-methoxy-1-methylethyl acetate EL STEL: 75 ppm TWA: 50 ppm EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid duritional information: The lists that were valid duritional protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	ing at the workplace:
 EL STEL: 150 ppm TWA: 50 ppm EV STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm 1330-20-7 xylene EL STEL: 150 ppm TWA: 100 ppm EV STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm 108-65-6 2-methoxy-1-methylethyl acetate EL STEL: 75 ppm TWA: 50 ppm EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid durit Exposure controls Personal protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
TWA: 50 pmEVSTEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm1330-20-7 xyleneELSTEL: 150 ppm TWA: 100 ppmEVSTEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm108-65-6 2-methoxy-1-methylethyl acetateELSTEL: 75 ppm TWA: 50 ppmEVTWA: 270 mg/m³, 50 ppmF63-69-9 ethyl 3-ethoxypropionateEVTWA: 300 mg/m³, 50 ppm• Additional information: The lists that were valid duri• Exposure controls• Personal protective equipment:• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	
 EV STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm 1330-20-7 xylene EL STEL: 150 ppm TWA: 100 ppm EV STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm 108-65-6 2-methoxy-1-methylethyl acetate EL STEL: 75 ppm TWA: 50 ppm EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid durities Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
 EL STEL: 150 ppm TWA: 100 ppm EV STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm 108-65-6 2-methoxy-1-methylethyl acetate EL STEL: 75 ppm TWA: 50 ppm EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid duritional information: The lists that were valid durities Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
TWA: 100 ppmEVSTEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm108-65-6 2-methoxy-1-methylethyl acetateELSTEL: 75 ppm TWA: 50 ppmEVTWA: 270 mg/m³, 50 ppm763-69-9 ethyl 3-ethoxypropionateEVTWA: 300 mg/m³, 50 ppmAdditional information: The lists that were valid duritExposure controlsPersonal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	
TWA: 435 mg/m³, 100 ppm 108-65-6 2-methoxy-1-methylethyl acetate ELSTEL: 75 ppm TWA: 50 ppmEVTWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EVTWA: 300 mg/m³, 50 ppmAdditional information: The lists that were valid durit Exposure controlsPersonal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	
108-65-6 2-methoxy-1-methylethyl acetate EL STEL: 75 ppm TWA: 50 ppm EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm • Additional information: The lists that were valid durity • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	
TWA: 50 ppmEVTWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EVTWA: 300 mg/m³, 50 ppm• Additional information: The lists that were valid durity• Exposure controls• Personal protective equipment:• General protective and hygienic measures:Keep away from foodstuffs, beverages and feed.Immediately remove all soiled and contaminated clothWash hands before breaks and at the end of work.Avoid contact with the skin.	
 EV TWA: 270 mg/m³, 50 ppm 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid durity Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
 763-69-9 ethyl 3-ethoxypropionate EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid duritional information: The lists that were valid duritional protective equipment: Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
EV TWA: 300 mg/m³, 50 ppm Additional information: The lists that were valid durity Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth Wash hands before breaks and at the end of work. Avoid contact with the skin.	
 Additional information: The lists that were valid duries Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated cloth. Wash hands before breaks and at the end of work. Avoid contact with the skin. 	
Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respinent exposure use respiratory protective device that is index • Protection of hands:	ing. atory filter device. In case of intensive or longe
Protective gloves The glove material has to be impermeable and resistance Due to missing tests no recommendation to the g	
preparation/ the chemical mixture. Selection of the glove material on consideration of	the negative times we too of diffusion and th

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

CA



Page 6/12

(Contd. of page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

 Information on basic physical and General Information 	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C
Flash point:	14 °C
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	315 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
• Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.8 Vol %



Page 7/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

		(Contd. of page 6
· Vapor pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	0.8917 g/cm ³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
Coating VOC content:	100.00 %	
-	891.7 g/l / 7.44 lb/gal	
Material VOC content:	891.7 g/l / 7.44 lb/gal	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- Oral LD50 5,800 mg/kg (mouse)
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.

(Contd. on page 8)



Page 8/12

(Contd. of page 7)

3

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

(Contd. of page 8)

Page 9/12

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT/TDG, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT/TDG	Paint	
ADR	1263 Paint PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT/TDG (Transport dangerous goo	ods):	
Class	3 Flammable liquids	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT/TDĠ, ADR, IMDG, IATA	11	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Hazard identification number (Kemle		
EMS Number:	<i>F-E,<u>S-E</u></i>	
Stowage Category	В	
Transport in bulk according to Anne	x II of	



Page 10/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

	(Contd. of page
· Transport/Additional information:	
· DOT/TDG · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
 ADR Excepted quantities (EQ) 	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

None of th	e ingredients is listed.	
Section 3	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
TSCA (To	xic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIVE
1330-20-7	, xylene	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
Canadian	substance listings:	· · ·
Canadian	Domestic Substances List (DSL)	
123-86-4	n-butyl acetate	
1330-20-7	, xylene	
108-65-6	2-methoxy-1-methylethyl acetate	
763-69-9	ethyl 3-ethoxypropionate	



Page 11/12

Safety Data Sheet according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

Canadian Non-Domestic Substances List (N	(Contd. of page 1
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 0.1	%)
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 1%	
123-86-4 n-butyl acetate	
GHS label elements The product is classified and labeled according Hazard pictograms	to the Globally Harmonized System (GHS).
GHS02 GHS07	
Signal word Danger	
Hazard-determining components of labeling:	:
n-butyl acetate	
Solvent naphtha (petroleum), light arom.	
Hazard statements Highly flammable liquid and vapour.	
Causes skin irritation.	
May cause respiratory irritation. May cause drow	wsiness or dizziness
Precautionary statements	
If medical advice is needed, have product conta	ainer or label at hand.
Keep out of reach of children.	
Read label before use.	
	en flames and other ignition sources. No smoking.
Ground and bond container and receiving equip Use explosion-proof [electrical/ventilating/lightin	
Use non-sparking tools.	gj equipment.
Take actions to prevent static discharges.	
Avoid breathing dust/fume/gas/mist/vapours/spr	ray.
Wash thoroughly after handling.	,
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye p	
IF ON SKIN (or hair): Take off immediately all co IF INHALED: Remove person to fresh air and ke Call a poison center/doctor if you feel unwell.	ontaminated clothing. Rinse skin with water [or showe eep comfortable for breathing.
Specific treatment (see on this label).	
Take off contaminated clothing and wash it befo	pre reuse.
If skin irritation occurs: Get medical advice/atten	
	(Contd. on page 1



Page 12/12

Safety Data Sheet

according to HPR, Schedule 1

Printing date 07/18/2024

Reviewed on 07/18/2024

Trade name: S2232 REDUCER NORMAL

(Contd. of page 11)

In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of the latest revision of the safety data sheet 07/18/2024 / - Abbreviations and acronyms: ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative * Data compared to the previous version altered.