


Page 1/11

Safety data sheet according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024





Page 2/11

Safety data sheet according to UK REACH

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

Printing date 07.02.2025

	(Contd. of page
STUT SE 3	H336 May cause drowsiness or dizziness.
	lements ccording to Regulation (EC) No 1272/2008 t is classified and labelled according to the GB CLP regulation.
Hazard pict	tograms
▲ ·	▲ ▲
	\mathbf{A}
<u> (19</u>) (
	\checkmark
GHS02 G	H\$07
Signal word	d Warning
•	
	ermining components of labelling:
n-butyl acet	
Hazard stat	
	nable liquid and vapour.
	ause drowsiness or dizziness.
 Precautiona 	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source
	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse sk
	with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/nationa
	international regulations.
Additional	information:
	ethyl methacrylate. May produce an allergic reaction.
• 2.3 Other h	
	PBT and vPvB assessment
• PBT: Not ap	
r DI. NUL di	וויסאוכ.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB



Page 3/11

Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

	(0	Contd. of page
· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate line Flam. Liq. 3, H226; (1) STOT SE 3, H336	>10- <i>≤</i> 25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32		>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56		>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27		>2.5- <i>≤</i> 10%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate	<i>≤</i> 2.5%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)



Page 4/11

Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

(Contd. of page 3)

- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)

GB



Page 5/11

Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

тg/m³, 200 ррт ng/m³, 150 ррт
тg/m³, 100 ppm ng/m³, 50 ppm
ylethyl acetate
тg/m³, 100 ppm ng/m³, 50 ppm
e
тg/m³, 100 ррт ng/m³, 50 ррт
limit values:
nine shift opuric acid
5

osure controis

· Personal protective equipment:

• General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

GB



Page 6/11

Safety data sheet according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

(Contd. of page 5)

Trade name: 621 2K LUMINOUS GREEN

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9.1 Information on basic physical General Information	
Appearance:	
Form:	Liquid
Colour:	Green
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling	range: 124 °C
Flash point:	25 ℃
Flammability	Flammable.
Auto-ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosi air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %



Page 7/11

Safety data sheet according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

	(Contd. of pag	je 6
· Vapour pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	1.002 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	50.6 %	
VÕC (EC)	507.2 g/l	
Solids content:	49.1 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

- Oral LD50 4,300 mg/kg (rat)
- Dermal LD50 2,000 mg/kg (rabbit)

(Contd. on page 8)

GB



Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small guantities. Danger to drinking water if even extremely small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 9)

GB

(Contd. of page 7)

Page 8/11



Safety data sheet according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

(Contd. of page 8)

SECTION 14: Transport information	on
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids. F-E, <u>S-E</u> A
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
<i>ADR Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
Transport category Tunnel restriction code	3 D/E
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
	(Contd. on page 10

Page 9/11



Page 10/11

Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

Trade name: 621 2K LUMINOUS GREEN

· UN "Model Regulation":

UN 1263 PAINT, 3, III

(Contd. of page 9)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
Department issuing SDS: Product safety department

· Contact: N/A

(Contd. on page 11)

GB



Page 11/11

Safety data sheet according to UK REACH

Printing date 07.02.2025

Version number 1.1

Revision: 29.07.2024

(Contd. of page 10)

Trade name: 621 2K LUMINOUS GREEN

(Cond. of page 10)
· Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
• * Data compared to the previous version altered.
GB