



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** 721 BASECOAT LUMINOUS GREEN
 - **Article number:** 721
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
use as industrial paint
- **Sector of Use**

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**

PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**

Générale de Peinture
3 rue du Velay
91090 LISSES, France
 - www.gpccoatings.com
+33(0)160867765
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:**

During normal opening times:
+33(0)160867765

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

(Contd. on page 2)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 1)

*Skin Irrit. 2 H315 Causes skin irritation.**STOT SE 3 H336 May cause drowsiness or dizziness.***2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008***The product is classified and labelled according to the GB CLP regulation.***Hazard pictograms**

GHS02 GHS07

Signal word *Warning***Hazard-determining components of labelling:***n-butyl acetate***Hazard statements***H226 Flammable liquid and vapour.**H315 Causes skin irritation.**H336 May cause drowsiness or dizziness.***Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read carefully and follow all instructions.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P241 Use explosion-proof [electrical/ventilating/lighting] equipment.**P261 Avoid breathing dust/fume/gas/mist/vapours/spray.**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** *Not applicable.***vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures**Description:** *Mixture of substances listed below with nonhazardous additions.*

(Contd. on page 3)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 2)

· Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	>25-≤50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>10-≤25%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. ⚠ Acute Tox. 4, H332; STOT SE 3, H335	>2.5-≤10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information:** Immediately remove any clothing soiled by the product.
- After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media**· Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**· For safety reasons unsuitable extinguishing agents:** Water with full jet**· 5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

(Contd. on page 4)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep container tightly sealed.
 - **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 4)

· Ingredients with limit values that require monitoring at the workplace:**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

· Ingredients with biological limit values:**1330-20-7 xylene**

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: butoxyacetic acid

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Protective gloves

(Contd. on page 6)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Green

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 120 °C

- **Flash point:** 27 °C

- **Flammability** Flammable.

- **Auto-ignition temperature:** 370 °C

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

(Contd. on page 7)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 6)

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.984 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	66.8 %
VOC (EC)	657.6 g/l
Solids content:	33.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
- **123-86-4 n-butyl acetate**

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN**12.6 Other adverse effects** No further relevant information available.

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number**ADR, IMDG, IATA**

UN1263

14.2 UN proper shipping name**ADR**

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

NOT APPLICABLE

ADR, IMDG, IATA**Class**

3 Flammable liquids.

Label

3

14.4 Packing group**ADR, IMDG, IATA**

III

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user

Warning: Flammable liquids.

EMS Number:

F-E, S-E

Stowage Category

A

**14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code**

Not applicable.

(Contd. on page 10)

GB



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 9)

· Transport/Additional information:**· ADR****· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG**· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****· Poisons Act****· Regulated explosives precursors**

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P5c FLAMMABLE LIQUIDS****· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 11)



Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

Trade name: 721 BASECOAT LUMINOUS GREEN

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases**

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**