

Page 1/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### SECTION 1: Identification of the substance/mixture and of the company undertaking · 1.1 Product identifier Trade name: 739 BASECOAT BRILLIANT YELLOW · Article number: 739 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. use as industrial paint · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Application of the substance / the mixture refer to the relevant Technical Data Sheet · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Générale de Peinture 3 rue du Velay 91090 LISSES, France www.gpccoatings.com +33(0)160867765 · Further information obtainable from: Product Safety Department · 1.4 Emergency telephone number: During normal opening times: +33(0)160867765 SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878 GHS02 flame Flam. Lig. 3 H226 Flammable liquid and vapour. GHS07 (Contd. on page 2) GB



Page 2/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

international regulations. 2.3 Other hazards Results of PBT and vPvB assessment		(Contd. of pag
<ul> <li>2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms </li> <li> August Constraint of the GB CLP regulation. </li> <li> Hazard pictograms </li> <li> August Constraint of the GB CLP regulation. </li> <li> Hazard pictograms </li> <li> GHS02 GHS07 </li> <li> Signal word Warning </li> <li> Hazard-determining components of labelling: n-butyl acetate </li> <li> Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking. P241 Us explosion-proof [electrical/ventilating/lighting] equipment. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower]. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/nat international regulations. 2.3 Other hazards Results of PBT and vPvB assessment</li></ul>	Skin Irrit. 2	
<ul> <li>2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms </li> <li> August Constraint of the GB CLP regulation. </li> <li> Hazard pictograms </li> <li> August Constraint of the GB CLP regulation. </li> <li> Hazard pictograms </li> <li> GHS02 GHS07 </li> <li> Signal word Warning </li> <li> Hazard-determining components of labelling: n-butyl acetate </li> <li> Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking. P241 Us explosion-proof [electrical/ventilating/lighting] equipment. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower]. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/nat international regulations. 2.3 Other hazards Results of PBT and vPvB assessment</li></ul>	STOT SE 3	H336 May cause drowsiness or dizziness.
Labelling according to Regulation (EC) No 1272/2008         The product is classified and labelled according to the GB CLP regulation.         Hazard pictograms	221 ahol olo	monts
The product is classified and labelled according to the GB CLP regulation.         Hazard pictograms         View       View         GHS02       GHS07         Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/turme/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         23 Other hazards         Results of PBT and vPvB assessment		
Hazard pictograms		
View       View         GHS02       GHS07         Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         23 Other hazards       Results of PBT and vPvB assessment		
Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment	<b>^</b>	↓ ▲
Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment		
Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment	<u> </u>	
Signal word Warning         Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment		
Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment	GHS02 GH	S07
Hazard-determining components of labelling:         n-butyl acetate         Hazard statements         H226 Flammable liquid and vapour.         H315 Causes skin irritation.         H336 May cause drowsiness or dizziness.         Precautionary statements         P101       If medical advice is needed, have product container or label at hand.         P102       Keep out of reach of children.         P103       Read carefully and follow all instructions.         P210       Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.         P241       Use explosion-proof [electrical/ventilating/lighting] equipment.         P261       Avoid breathing dust/fume/gas/mist/vapours/spray.         P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].         P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment		
<ul> <li>n-butyl acetate</li> <li>Hazard statements</li> <li>H226 Flammable liquid and vapour.</li> <li>H315 Causes skin irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>Precautionary statements</li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>	Signal word	Warning
<ul> <li>n-butyl acetate</li> <li>Hazard statements</li> <li>H226 Flammable liquid and vapour.</li> <li>H315 Causes skin irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>Precautionary statements</li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>	Hazard-dete	rmining components of labelling.
Hazard statementsH226 Flammable liquid and vapour.H315 Causes skin irritation.H336 May cause drowsiness or dizziness.Precautionary statementsP101If medical advice is needed, have product container or label at hand.P102Keep out of reach of children.P103Read carefully and follow all instructions.P210Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.P241Use explosion-proof [electrical/ventilating/lighting] equipment.P261Avoid breathing dust/fume/gas/mist/vapours/spray.P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].P405Store locked up.P501Dispose of contents/container in accordance with local/regional/nat international regulations.2.3 Other hazardsResults of PBT and vPvB assessment		
<ul> <li>H226 Flammable liquid and vapour.</li> <li>H315 Causes skin irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li><b>Precautionary statements</b></li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li><b>2.3 Other hazards</b></li> <li><b>Results of PBT and vPvB assessment</b></li> </ul>		
<ul> <li>H315 Causes skin irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>Precautionary statements</li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
<ul> <li>H336 May cause drowsiness or dizziness.</li> <li>Precautionary statements</li> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
Precautionary statementsP101If medical advice is needed, have product container or label at hand.P102Keep out of reach of children.P103Read carefully and follow all instructions.P210Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.P241Use explosion-proof [electrical/ventilating/lighting] equipment.P261Avoid breathing dust/fume/gas/mist/vapours/spray.P303+P361+P353IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].P405Store locked up.P501Dispose of contents/container in accordance with local/regional/nat international regulations.2.3 Other hazardsResults of PBT and vPvB assessment		
<ul> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
<ul> <li>P102 Keep out of reach of children.</li> <li>P103 Read carefully and follow all instructions.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting] equipment.</li> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
P103Read carefully and follow all instructions.P210Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.P241Use explosion-proof [electrical/ventilating/lighting] equipment.P261Avoid breathing dust/fume/gas/mist/vapours/spray.P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].P405Store locked up.P501Dispose of contents/container in accordance with local/regional/nat international regulations.2.3 Other hazardsResults of PBT and vPvB assessment		
P210Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking.P241Use explosion-proof [electrical/ventilating/lighting] equipment.P261Avoid breathing dust/fume/gas/mist/vapours/spray.P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].P405Store locked up.P501Dispose of contents/container in accordance with local/regional/nat international regulations.2.3 Other hazardsResults of PBT and vPvB assessment		
No smoking.P241Use explosion-proof [electrical/ventilating/lighting] equipment.P261Avoid breathing dust/fume/gas/mist/vapours/spray.P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].P405Store locked up.P501Dispose of contents/container in accordance with local/regional/nat international regulations.2.3 Other hazards Results of PBT and vPvB assessment	P210	
<ul> <li>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
<ul> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rins with water [or shower].</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>	P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
with water [or shower]. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/nat international regulations. 2.3 Other hazards Results of PBT and vPvB assessment		
P405       Store locked up.         P501       Dispose of contents/container in accordance with local/regional/nat international regulations.         2.3 Other hazards         Results of PBT and vPvB assessment	P303+P361+	
<ul> <li>P501 Dispose of contents/container in accordance with local/regional/nat international regulations.</li> <li>2.3 Other hazards</li> <li>Results of PBT and vPvB assessment</li> </ul>		
international regulations. 2.3 Other hazards Results of PBT and vPvB assessment		
2.3 Other hazards Results of PBT and vPvB assessment	P501	Dispose of contents/container in accordance with local/regional/nation
Results of PBT and vPvB assessment		
DDT. Not applicable		
PBT: Not applicable. vPvB: Not applicable.		

### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

<sup>-</sup> GB



### Page 3/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

#### Trade name: 739 BASECOAT BRILLIANT YELLOW

	(0	Contd. of page
· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate line Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	>25- <i>≤</i> 50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32		>10- <i>≤</i> 25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56		>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. 〈〉 Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 111-76-2 EINECS: 203-905-0 Reg. pr : 01-2119475108-36	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 3, H331; 🚯 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<i>≤</i> 2.5%

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)



Page 4/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

(Contd. of page 3)

- $\cdot$  5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)

GB



### Page 5/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

Long-term 1330-20-7 xylen VEL Short-term Sk; BMGV 108-65-6 2-meth VEL Short-term Long-term Sk 111-76-2 2-buto VEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 966 mg/m³, 200 ppm value: 724 mg/m³, 150 ppm e value: 441 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm value: 274 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: e l/mol creatinine urine	
Long-term 1330-20-7 xylen VEL Short-term Sk; BMGV 108-65-6 2-meth VEL Short-term Long-term Sk 111-76-2 2-buto VEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 724 mg/m³, 150 ppm value: 724 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: value: 123 mg/m³, 25 ppm	
1330-20-7 xylen WEL Short-term Sk; BMGV 108-65-6 2-meth WEL Short-term Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 441 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm xyethanol value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: yethic creatinine yethic creatinine	
WEL Short-term Long-term Sk; BMGV 108-65-6 2-meth WEL Short-term Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 441 mg/m³, 100 ppm value: 220 mg/m³, 50 ppm oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: p l/mol creatinine urine	
Long-term Sk; BMGV 108-65-6 2-meth WEL Short-term Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 220 mg/m³, 50 ppm oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: p l/mol creatinine urine	
Sk; BMGV 108-65-6 2-meth NEL Short-term Sk 111-76-2 2-buto WEL Short-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	oxy-1-methylethyl acetate value: 548 mg/m³, 100 ppm value: 274 mg/m³, 50 ppm value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: e l/mol creatinine urine	
WEL Short-term Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mm Medium: Sampling	value: 548 mg/m <sup>3</sup> , 100 ppm value: 274 mg/m <sup>3</sup> , 50 ppm value: 246 mg/m <sup>3</sup> , 50 ppm value: 123 mg/m <sup>3</sup> , 25 ppm biological limit values: e l/mol creatinine urine	
Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 274 mg/m <sup>3</sup> , 50 ppm <b>xyethanol</b> value: 246 mg/m <sup>3</sup> , 50 ppm value: 123 mg/m <sup>3</sup> , 25 ppm <b>biological limit values:</b> <b>e</b> I/mol creatinine urine	
Long-term Sk 111-76-2 2-buto WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 274 mg/m <sup>3</sup> , 50 ppm <b>xyethanol</b> value: 246 mg/m <sup>3</sup> , 50 ppm value: 123 mg/m <sup>3</sup> , 25 ppm <b>biological limit values:</b> <b>e</b> I/mol creatinine urine	
<b>111-76-2 2-buto</b> WEL       Short-term         Long-term         Sk, BMGV         Ingredients with         1330-20-7 xylen         BMGV       650 mmong         BMGV       650 mmong         Sampling	value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: e I/mol creatinine urine	
WEL Short-term Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mm Medium: Sampling	value: 246 mg/m³, 50 ppm value: 123 mg/m³, 25 ppm biological limit values: e I/mol creatinine urine	
Long-term Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	value: 123 mg/m³, 25 ppm biological limit values: e I/mol creatinine urine	
Sk, BMGV Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	<i>biological limit values:</i> <i>e</i> <i>I/mol creatinine</i> <i>urine</i>	
Ingredients with 1330-20-7 xylen BMGV 650 mmo Medium: Sampling	e I/mol creatinine urine	
1 <b>330-20-7 xylen</b> BMGV 650 mmo Medium: Sampling	e I/mol creatinine urine	
BMGV 650 mmc Medium: Sampling	I/mol creatinine urine	
Medium: Sampling	urine	
Sampling		
	time: post shift	
Paramete	er: methyl hippuric acid	
111-76-2 2-buto	kyethanol	
BMGV 240 mma		
Medium:		
	time: post shift	
	er: butoxyacetic acid	
Additional infor	mation: The lists valid during the making were used as basis.	
8.2 Exposure co	ntrols	
	tive equipment:	
	ive and hygienic measures:	
	foodstuffs, beverages and feed.	
	ove all soiled and contaminated clothing	
	bre breaks and at the end of work.	
Avoid contact wit		
	h the eyes and skin.	
Respiratory pro		
n case of brief e	exposure or low pollution use respiratory filter device. In case of intensi f-contained respiratory protective device.	ive or lon



Page 6/11

## Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

(Contd. of page 5)

#### Trade name: 739 BASECOAT BRILLIANT YELLOW

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a	and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Yellow	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	ange: 120 °C	
Flash point:	27 °C	
Flammability	Flammable.	



### Page 7/11

## Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

	(Contd. of page 6
· Auto-ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.942 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	77.2 %
VOC (EC)	727.3 g/l
Solids content:	22.9 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)

GB



Page 8/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

(Contd. of page 7)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

### · 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)



Page 9/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 8)

### SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
   Recommendation
   Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

S	ECTI	ON 1	14: Ti	ransp	ort in	formati	on

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR	1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)	NOT APPLICABLE	
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG, IATA	<i>III</i>	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
EMS Number:	<i>F-E,<u>S-E</u></i>	
Stowage Category	A	
14.7 Transport in bulk according to Anne	ex II of	
Marpol and the IBC Code	Not applicable.	
		(Contd. on page



### Page 10/11

### Safety data sheet

according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

	(Contd. of page 9)
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	3 D/E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

### · Regulated explosives precursors

None of the ingredients is listed.

#### · Regulated poisons

None of the ingredients is listed.

#### · Reportable explosives precursors

None of the ingredients is listed.

#### · Reportable poisons

None of the ingredients is listed.

#### · Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)



Page 11/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025

Version number 1.2

Revision: 29.07.2024

### Trade name: 739 BASECOAT BRILLIANT YELLOW

(Contd. of page 10)

This infor	mation is based on our present knowledge. However, this shall not constitute a guarantee
any speci	fic product features and shall not establish a legally valid contractual relationship.
Relevant	
H226 Flai	nmable liquid and vapour.
H302 Har	mful if swallowed.
H311 Tox	ic in contact with skin.
H312 Har	mful in contact with skin.
H315 Cau	ises skin irritation.
	ises serious eye irritation.
	ic if inhaled.
	mful if inhaled.
	/ cause respiratory irritation.
	/ cause drowsiness or dizziness.
11550 May	cause drowsmess of dizziness.
Contact:	
	tions and acronyms:
	nent international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Conce onal Transport of Dangerous Goods by Rail)
	national Civil Aviation Organisation
	d relatif au transport international des marchandises dangereuses par route (European Agreement Concernin
	Carriage of Dangerous Goods by Road)
	national Maritime Code for Dangerous Goods
	ational Air Transport Association Ily Harmonised System of Classification and Labelling of Chemicals
	ropean Inventory of Existing Commercial Chemical Substances
	ropean List of Notified Chemical Substances
EINECS: EL	
EINECS: Eu ELINCS: Eu CAS: Chem	ical Abstracts Service (division of the American Chemical Society)
EINECS: Eu ELINCS: Eu CAS: Chem VOC: Volati	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU)
EINECS: Eu ELINCS: Eu CAS: Chem VOC: Volati LC50: Letha	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent
EINECS: Eu ELINCS: Eu CAS: Chem VOC: Volati LC50: Letha LD50: Letha	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent l dose, 50 percent
EINECS: EL ELINCS: Eu CAS: Chem VOC: Volatii LC50: Letha LD50: Letha PBT: Persis	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent l dose, 50 percent tent, Bioaccumulative and Toxic
EINECS: EL ELINCS: Eu CAS: Chem. VOC: Volatii LC50: Letha LD50: Letha PBT: Persis vPvB: very F Flam. Liq. 3.	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent l dose, 50 percent tent, Bioaccumulative and Toxic Persistent and very Bioaccumulative · Flammable liquids – Category 3
EINECS: Eu ELINCS: Eu CAS: Chem VOC: Volati LC50: Letha DBT: Persis VPVB: very F Flam. Liq. 3. Acute Tox. 3	ic <sup>2</sup> I Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) I concentration, 50 percent I dose, 50 percent etnt, Bioaccumulative and Toxic Persistent and very Bioaccumulative Flammable liquids – Category 3 3: Acute toxicity – Category 3
EINECS: Eu ELINCS: Eu CAS: Chem VOC: Volatii LC50: Letha LD50: Letha PBT: Persis vPvB: very I Flam. Liq. 3. Acute Tox. 4	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent l dose, 50 percent etent, Bioaccumulative and Toxic Persistent and very Bioaccumulative Flammable liquids – Category 3 3: Acute toxicity – Category 3 4: Acute toxicity – Category 4
EINECS: EL ELINCS: EU CAS: Chem. VOC: Volatii LC50: Letha DBT: Persis vPvB: very F Flam. Liq. 3. Acute Tox. 4 Skin Irrit. 2:	ic <sup>2</sup> I Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) I concentration, 50 percent I dose, 50 percent etent, Bioaccumulative and Toxic Persistent and very Bioaccumulative Flammable liquids – Category 3 8: Acute toxicity – Category 3 8: Acute toxicity – Category 4 Skin corrosion/irritation – Category 2
EINECS: Eu ELINCS: Eu CAS: Chem. VOC: Volatii LC50: Letha D50: Letha PBT: Persis vPvB: very F Flam. Liq. 3. Acute Tox. 2 Skin Irrit. 2: Eye Irrit. 2:	ic <sup>'</sup> al Abstracts Service (division of the American Chemical Society) le Organic Compounds (USA, EU) l concentration, 50 percent l dose, 50 percent etent, Bioaccumulative and Toxic Persistent and very Bioaccumulative Flammable liquids – Category 3 3: Acute toxicity – Category 3 4: Acute toxicity – Category 4