

Page 1/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

# SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: 772 BASECOAT PEARL WHITE
- · Article number: 772
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
  No further relevant information available.
  use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Générale de Peinture

3 rue du Velay

91090 LISSES, France

www.gpccoatings.com

- +33(0)160867765
- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

During normal opening times:

+33(0)160867765

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Lig. 3 H226 Flammable liquid and vapour.



(Contd. on page 2)



Page 2/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 2		
· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate  Tlam. Liq. 3, H226; STOT SE 3, H336	>50- <i>≤</i> 100%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene  Tilde Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom.  • Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene  This is a second of the second	≤2.5%
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 16.	

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)



Page 4/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 3)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

	(Contd. of page 4
· Ingre	dients with limit values that require monitoring at the workplace:
123-8	36-4 n-butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
1330-	-20-7 xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
100-4	11-4 ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
· Ingre	dients with biological limit values:
1330-	-20-7 xylene
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Parameter: methyl hippuric acid

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Page 6/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
<ul> <li>9.1 Information on basic physical a</li> <li>General Information</li> <li>Appearance:</li> </ul>		
Form: Colour:	Fluid According to product description	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/freezing point: Initial boiling point and boiling ra	Undetermined. ange: 124°C	
· Flash point:	27 °C	
· Flammability	Flammable.	
· Auto-ignition temperature:	370 °C	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> </ul>	0.965 g/cm³ Not determined. Not determined.	

(Contd. on page 7)





# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

	(Contd. of pag
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	72.0 %
VOC (EC)	694.7 g/l
Solids content:	28.0 %
· 9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification
123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 ma/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 7)

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR. IMDG. IATA

UN1263

(Contd. on page 9)



Page 9/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

	(Contd. of page
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es)	NOT APPLICABLE
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · EMS Number: · Stowage Category	Warning: Flammable liquids. F-E,S-E A
· 14.7 Transport in bulk according to An Marpol and the IBC Code	nnex II of Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n 3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r



Page 10/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 9)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

7664-38-2 phosphoric acid

30%

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 11)



Page 11/11

# Safety data sheet according to UK REACH

Printing date 12.02.2025 Version number 1.2 Revision: 29.07.2024

#### Trade name: 772 BASECOAT PEARL WHITE

(Contd. of page 10)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

· \* Data compared to the previous version altered.