

Page 1/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: 850 BASECOAT BINDER
- · Article number: 850
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 No further relevant information available.
 use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Générale de Peinture

3 rue du Velay

91090 LISSES, France

www.gpccoatings.com

- +33(0)160867765
- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

During normal opening times:

+33(0)160867765

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Lig. 3 H226 Flammable liquid and vapour.



(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 1)

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

	Contd. of page
n-butyl acetate The Flam. Liq. 3, H226; STOT SE 3, H336	>50- <i>≤</i> 100%
xylene ightharpoonup Flam. Liq. 3, H226; ightharpoonup Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>10- <i>≤</i> 25%
Solvent naphtha (petroleum), light arom. •• Acute Tox. 4, H332; STOT SE 3, H335	>2.5-≤10%
2-methoxy-1-methylethyl acetate Plam. Liq. 3, H226	>2.5-≤10%
ethylbenzene The Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	<i>≤</i> 2.5%
	n-butyl acetate ightharpoonup Flam. Liq. 3, H226; ightharpoonup STOT SE 3, H336 xylene ightharpoonup Flam. Liq. 3, H226; ightharpoonup Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Solvent naphtha (petroleum), light arom. ightharpoonup Acute Tox. 4, H332; STOT SE 3, H335 2-methoxy-1-methylethyl acetate ightharpoonup Flam. Liq. 3, H226 ethylbenzene ightharpoonup Flam. Liq. 2, H225; ightharpoonup STOT RE 2, H373; Asp. Tox. 1.

,

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)



Page 4/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

		(Contd. of page 4)
· Ingre	dients with limit values that require monitoring at the workplace:	, , , ,
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
1330-	20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
100-4	11-4 ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
· Ingre	dients with biological limit values:	
1330-	20-7 xylene	
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information	nn haeir	r nnveical	and c	homical	nronartiae
· J. I IIII OI III au OI I	. UII Dasit	, wiivsicai	and G	ICIIIICAI	DI UDEI HES

· General Information

· Appearance:

Form: Liquid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 124 °C

· Flash point: 27 °C

· Flammability Flammable.

· Auto-ignition temperature: 315 °C

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

	(Contd. of page 6
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.943 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	77.8 %
VÕC (EC)	733.4 g/l
Solids content:	22.2 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB



Page 8/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 9)



Page 9/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 8)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

ADR IMDG, IATA 1263 PAINT PAINT NOT APPLICABLE NOT APPLICABLE Class Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user EMS Number: Stowage Category NOT APPLICABLE NOT	· 14.1 UN-Number		
ADR 1263 PAINT PAINT 14.3 Transport hazard class(es) NOT APPLICABLE ADR, IMDG, IATA Class 3 Flammable liquids. 3 Label 3 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of	· ADR, IMDG, IATA	UN1263	
IMDG, IATA PAINT 14.3 Transport hazard class(es) NOT APPLICABLE ADR, IMDG, IATA Class Class Label 3 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user EMS Number: Stowage Category A 14.7 Transport in bulk according to Annex II of	· 14.2 UN proper shipping name		
14.3 Transport hazard class(es) ADR, IMDG, IATA Class Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: Mo 14.6 Special precautions for user EMS Number: Stowage Category 14.7 Transport in bulk according to Annex II of	7.27	1263 PAINT	
ADR, IMDG, IATA Class Class Label Class Label Class Label Class Label Class Label Class Label Class C	· IMDG, IATA	PAINT	
Class 3 Flammable liquids. Label 3 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of	· 14.3 Transport hazard class(es)	NOT APPLICABLE	
Label 3 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Warning: Flammable liquids. EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of	ADR, IMDG, IATA		
• 14.4 Packing group • ADR, IMDG, IATA • 14.5 Environmental hazards: • Marine pollutant: No • 14.6 Special precautions for user Warning: Flammable liquids. • EMS Number: F-E,S-E • Stowage Category A	Class	-	
ADR, IMDG, IATA 11.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of		3	
• 14.5 Environmental hazards: • Marine pollutant: • 14.6 Special precautions for user • EMS Number: • Stowage Category • 14.7 Transport in bulk according to Annex II of			
Marine pollutant: 14.6 Special precautions for user EMS Number: Stowage Category 14.7 Transport in bulk according to Annex II of	ADR, IMDG, IATA	III	
• 14.6 Special precautions for user • EMS Number: • Stowage Category • A • 14.7 Transport in bulk according to Annex II of	· 14.5 Environmental hazards:		
EMS Number: F-E,S-E Stowage Category A 14.7 Transport in bulk according to Annex II of	Marine pollutant:	No	
Stowage Category A 14.7 Transport in bulk according to Annex II of			
· 14.7 Transport in bulk according to Annex II of	•		
	Stowage Category	Α	
Marpol and the IBC Code Not applicable.		f	
	Marpol and the IBC Code	Not applicable.	



Page 10/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 9)

· Transport/Additional information:

ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

maximum net quantity per ec

· UN "Model Regulation": UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 18.02.2025 Version number 1.1 Revision: 16.10.2024

Trade name: 850 BASECOAT BINDER

(Contd. of page 10)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department

· Contact: N/A

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

· * Data compared to the previous version altered.