



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** 8805 UNIVERSAL PRIMER BLACK
 - **Article number:** 8805
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
use as industrial paint
- **Sector of Use**

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**

PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**

General Paint Company S.A.L.
P.O.Box 7623
Beirut, Lebanon
info@generalpaint.biz
www.generalpaint.biz
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:** +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

toluene

dioctyl phthalate

ethylbenzene

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 2)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	>10-≤25%
CAS: 78-93-3 EINECS: 201-159-0	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	>2.5-≤10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>2.5-≤10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	>2.5-≤10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	>2.5-≤10%
CAS: 117-84-0 EINECS: 204-214-7	dioctyl phthalate ⚠ Repr. 2, H361	>2.5-≤10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	≤2.5%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336	≤2.5%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%

(Contd. on page 4)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 3)

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 4)

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Additional information about design of technical facilities:** No further data; see section 7.**Ingredients with limit values that require monitoring at the workplace:****108-88-3 toluene**WEL Short-term value: 384 mg/m³, 100 ppmLong-term value: 191 mg/m³, 50 ppm

Sk

78-93-3 butanoneWEL Short-term value: 899 mg/m³, 300 ppmLong-term value: 600 mg/m³, 200 ppm

Sk, BMGV

(Contd. on page 6)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 5)

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm
Long-term value: 208 mg/m³, 50 ppm
Sk, BMGV

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

· Ingredients with biological limit values:**78-93-3 butanone**

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L
Medium: urine
Sampling time: post shift
Parameter: 4-methylpentan-2-one

(Contd. on page 7)



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 6)

111-76-2 2-butoxyethanol

BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid
------	---

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK**· Eye protection:**

(Contd. of page 7)



Tightly sealed goggles

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

Form:	Liquid
Colour:	Black
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.**· Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	79-80.5 °C

· Flash point: -5 °C**· Flammability (solid, gas):** Highly flammable.**· Auto-ignition temperature:** 370 °C**· Decomposition temperature:** Not determined.**· Ignition temperature:** Product is not selfigniting.**· Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**· Explosion limits:**

Lower:	1.2 Vol %
Upper:	7 Vol %

· Vapour pressure at 20 °C: 29 hPa**· Vapour pressure at 50 °C:** 124 hPa**· Density at 20 °C:** 1.245 g/cm³**· Relative density** Not determined.**· Vapour density** Not determined.**· Evaporation rate** Not determined.

(Contd. on page 9)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 8)

- | | |
|---|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity:
Dynamic:
Kinematic: | Not determined.
Not determined. |
| · Solvent content:
Organic solvents:
Water:
VOC (EC) | 44.7 %
0.1 %
557.2 g/l |
| Solids content: | 51.6 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 10)

GB



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 9)

- **Reproductive toxicity**
Suspected of damaging fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT

(Contd. on page 11)

GB



Safety data sheet according to UK REACH


Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 10)

· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	NOT APPLICABLE
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

GB

(Contd. on page 12)



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 11)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

- **Regulated explosives precursors**

7664-38-2	phosphoric acid	30%
-----------	-----------------	-----

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 13)



Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: 8805 UNIVERSAL PRIMER BLACK

(Contd. of page 12)

- **Department issuing SDS:** Product safety department

- **Contact:** N/A

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

- *** Data compared to the previous version altered.**