

Page 1/10


Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024



(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

	(Contd. of page
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H335 May cause respiratory irritation.
2.2 Label ele	ments
	cording to Regulation (EC) No 1272/2008
	s classified and labelled according to the CLP regulation.
Hazard picto	grams
	\mathbf{N}
< **>	
GHS02 GH	S07
Signal word	Warning
Hazard-deter	mining components of labelling:
	r of hexamethylene diisocyanate
Hazard state	
	able liquid and vapour.
	skin irritation.
	serious eye irritation.
	use respiratory irritation.
Precautional	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source.
D0 44	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
r3U3+P301+I	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse sk
D205, D251.	with water [or shower]. P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove conta
F300+F301+1	lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P405 P501	Dispose of contents/container in accordance with local/regional/nationa
1 001	international regulations.
2.3 Other haz	
Results of Pl	BT and vPvB assessment
PBT: Not app	licable.
	plicable.

(Contd. on page 3)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

(Contd. of page 2)

Page 3/10

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
28182-81-2	Homopolymer of hexamethylene diisocyanate	>50- <i>≤</i> 100%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
1330-20-7		>25- <i>≤</i> 50%
	Flam. Liq. 3, H226; (1) Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
· Additional	information: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

LB/AR



Page 4/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

Short-term value: 442 mg/m ³ , 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin

(Contd. on page 5)

LB/AR



Page 5/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

(Contd. of page 4)

Trade name: H800 2K HARDENER

123-86-4 n-butyl acetate

IOELV (EU) Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)

LB/AR



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

(Contd. of page 5)

Page 6/10

9.1 Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Liquid
Colour:	Liquid Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	25 °C
Flammability	Flammable.
Auto-ignition temperature:	500 °C
• •	
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosi air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	1.04578 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	39.5 %



Page 7/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

(Contd. of page 6)

Trade name: H800 2K HARDENER

VOC (EC)

60.4 %

413.2 g/l

Solids content: • 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)



Page 8/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

(Contd. of page 7)

Trade name: H800 2K HARDENER

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	
 14.3 Transport hazard class(es) 	NOT APPLICABLE	
· ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>	
		(Contd. on page 9)
		LB/AR



Page 9/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

	(Contd. of page 8)
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code 	f Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/F
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

LB/AR



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.11.2024

Version number 1.2

Revision: 12.11.2024

Trade name: H800 2K HARDENER

(Contd. of page 9)

	: Other information
	is based on our present knowledge. However, this shall not constitute a guarantee i duct features and shall not establish a legally valid contractual relationship.
Relevant phras	es
H226 Flammabl	e liquid and vapour.
H312 Harmful in	o contact with skin.
H315 Causes sh	kin irritation.
H319 Causes se	erious eye irritation.
H332 Harmful if	•
	e respiratory irritation.
1 1330 Iviay Cause	e drowsiness or dizziness.
Department iss	uing SDS: Product safety department
Contact: N/A	
Abbreviations a	and acronyms:
	rnational concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerni
	nsport of Dangerous Goods by Rail)
	Civil Aviation Organisation
	au transport international des marchandises dangereuses par route (European Agreement Concerning t
	re of Dangerous Goods by Road) Maritime Code for Dangerous Goods
	Air Transport Association
	nonised System of Classification and Labelling of Chemicals
	Inventory of Existing Commercial Chemical Substances
	List of Notified Chemical Substances
	tracts Service (division of the American Chemical Society)
	nic Compounds (USA, EU)
	accumulative and Toxic nt and very Bioaccumulative
	able liquids – Category 3
	toxicity – Category 4
	rosion/irritation – Category 2
Eye Irrit. 2: Serious	eye damage/eye irritation – Category 2
	c target organ toxicity (single exposure) – Category 3
* Data compare	ed to the previous version altered.