



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

1 Identification

- **Product identifier**
- **Trade name:** 9961 2K PRIMER HARDENER
- **Article number:** 9961
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. S.A.L.
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Sensitization - Respiratory 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word *Danger***· Hazard-determining components of labeling:**

Aromatic Polyisocyanate
n-butyl acetate
m-tolylidene diisocyanate
ethyl acetate

· Hazard statements

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 3)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 2)

If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 2
Fire = 3
Reactivity = 0

Other hazards**Results of PBT and vPvB assessment**

- PBT:** Not applicable.
- vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

123-86-4	n-butyl acetate	>25-≤50%
528598-79-0	Aromatic Polyisocyanate	>10-≤25%
53317-61-6	aromatic polyisocyanate	>10-≤25%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
1330-20-7	xylene	>2.5-≤10%
28182-81-2	Homopolymer of hexamethylene diisocyanate	>2.5-≤10%
141-78-6	ethyl acetate	>2.5-≤10%
112-07-2	2-butoxyethyl acetate	≤2.5%

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 3)

26471-62-5 m-tolylidene diisocyanate

≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 4)

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	7.8 mg/m ³
141-78-6	ethyl acetate	1,200 ppm
112-07-2	2-butoxyethyl acetate	15 ppm
26471-62-5	<i>m</i> -tolylidene diisocyanate	0.02 ppm
822-06-0	hexamethylene-di-isocyanate	0.018 ppm

· PAC-2:

123-86-4	<i>n</i> -butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	2.9 mg/m ³
141-78-6	ethyl acetate	1,700 ppm
112-07-2	2-butoxyethyl acetate	35 ppm
26471-62-5	<i>m</i> -tolylidene diisocyanate	0.083 ppm
822-06-0	hexamethylene-di-isocyanate	0.2 ppm

· PAC-3:

123-86-4	<i>n</i> -butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	17 mg/m ³
141-78-6	ethyl acetate	10000** ppm
112-07-2	2-butoxyethyl acetate	210 ppm
26471-62-5	<i>m</i> -tolylidene diisocyanate	0.51 ppm
822-06-0	hexamethylene-di-isocyanate	3 ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

(Contd. on page 6)

-US-



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 5)

- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m ³ , 400 ppm
REL	Long-term value: 1400 mg/m ³ , 400 ppm

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 6)

TLV	Long-term value: 400 ppm
112-07-2 2-butoxyethyl acetate	
REL	Long-term value: 33 mg/m ³ , 5 ppm
TLV	Long-term value: 20 ppm A3
26471-62-5 m-tolylidene diisocyanate	
PEL	Ceiling limit value: 0.14 mg/m ³ , 0.02 ppm
REL	LFC
TLV	Short-term value: (0.14) NIC-0.021* mg/m ³ , (0.02) NIC-0.003* ppm Long-term value: (0.036) NIC-0.007* mg/m ³ , (0.005) NIC-0.001* ppm *(IFV) SEN; NIC-Skin; A3
Ingredients with biological limit values:	
1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 7)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties**· General Information****· Appearance:****Form:**

Liquid

Color:

Colorless

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

75 °C (167 °F)

· Flash point:

5 °C (41 °F)

· Flammability:

Highly flammable.

· Auto igniting:

315 °C (599 °F)

· Decomposition temperature:

Not determined.

· Ignition temperature:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:**Lower:**

1.2 Vol %

Upper:

7.5 Vol %

· Vapor pressure at 20 °C (68 °F):

10.7 hPa (8 mm Hg)

· Density at 20 °C (68 °F):1.04275 g/cm³ (8.70175 lbs/gal)

(Contd. on page 9)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 8)

· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	55.6 %
Coating VOC content:	55.59 %
	579.6 g/l / 4.84 lb/gal
Material VOC content:	579.6 g/l / 4.84 lb/gal
Solids content:	44.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.

(Contd. on page 10)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 9)

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
Irritant

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

528598-79-0	Aromatic Polyisocyanate	2B
1330-20-7	xylene	3
26471-62-5	m-tolylidene diisocyanate	2B

NTP (National Toxicology Program)

528598-79-0	Aromatic Polyisocyanate	R
26471-62-5	m-tolylidene diisocyanate	R

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:**General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

US

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024



Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 10)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint related material
- **ADR** 1263 PAINT RELATED MATERIAL
- **IMDG, IATA** PAINT RELATED MATERIAL
- **Transport hazard class(es)** NOT APPLICABLE
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids

(Contd. on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 11)

- | | |
|--|--|
| • EMS Number: | <i>F-E, S-E</i> |
| • Stowage Category | <i>B</i> |
| • Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <i>Not applicable.</i> |
| • Transport/Additional information: | |
| • DOT | |
| • Quantity limitations | <i>On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L</i> |
| • ADR | |
| • Excepted quantities (EQ) | <i>Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml</i> |
| • IMDG | |
| • Limited quantities (LQ) | <i>5L</i> |
| • Excepted quantities (EQ) | <i>Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml</i> |
| • UN "Model Regulation": | <i>UN 1263 PAINT RELATED MATERIAL, 3</i> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

*528598-79-0 Aromatic Polyisocyanate**1330-20-7 xylene**112-07-2 2-butoxyethyl acetate**26471-62-5 m-tolylidene diisocyanate**822-06-0 hexamethylene-di-isocyanate*

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

1330-20-7 xylene

(Contd. on page 13)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 12)

822-06-0 hexamethylene-di-isocyanate

· Proposition 65**· Chemicals known to cause cancer:**

528598-79-0 Aromatic Polyisocyanate

26471-62-5 m-tolylidene diisocyanate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

· TLV (Threshold Limit Value)

528598-79-0 Aromatic Polyisocyanate

(A4)

1330-20-7 xylene

A4

112-07-2 2-butoxyethyl acetate

A3

26471-62-5 m-tolylidene diisocyanate

(A4)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

528598-79-0 Aromatic Polyisocyanate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labeling:**

Aromatic Polyisocyanate

n-butyl acetate

m-tolylidene diisocyanate

ethyl acetate

· Hazard statements

Highly flammable liquid and vapor.

(Contd. on page 14)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 13)

Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause drowsiness or dizziness.

• **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

(Contd. on page 15)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2024

Reviewed on 11/11/2024

Trade name: 9961 2K PRIMER HARDENER

(Contd. of page 14)

- **Contact:** N/A

- **Date of preparation / last revision** 11/11/2024 / 1.1

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation – Category 1

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**

US