

Page 1/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 10/23/2024

#### 1 Identification

- · Product identifier
- · Trade name: H7085 2K HARDENER NORMAL
- · Article number: H7085
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS07 GHS08

#### · Signal word Warning

### · Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene Homopolymer of hexamethylene diisocyanate n-butyl acetate

#### Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

(Contd. on page 3)



Page 3/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

#### Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 2)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25- <i>≤</i> 50%		
123-86-4	n-butyl acetate	>25-≤50%		
98-56-6	4-chloro-alpha,alpha-trifluorotoluene	>10- <i>≤</i> 25%		

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)





# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
28182-81-2	Homopolymer of hexamethylene diisocyanate	7.8 mg/m³
123-86-4	n-butyl acetate	5 ppm
822-06-0	hexamethylene-di-isocyanate	0.018 ppm
PAC-2:		
28182-81-2	Homopolymer of hexamethylene diisocyanate	2.9 mg/m3
123-86-4	n-butyl acetate	200 ppm
822-06-0	hexamethylene-di-isocyanate C	
PAC-3:		
28182-81-2	Homopolymer of hexamethylene diisocyanate	17 mg/m3
123-86-4	n-butyl acetate	3000* ppn
	1	(Contd. on page



Page 5/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

822-06-0 hexamethylene-di-isocyanate

(Contd. of page 4)

3 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 6)



Page 6/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 5)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 7)





# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

	(Contd. of pag		
Color:	Clear		
Odor: Odor threshold:	Characteristic Not determined.		
pH-value:	Not determined.		
Change in condition	Un de la main e d		
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 124 °C (255.2 °F)		
<u> </u>	•		
Flash point:	27 °C (80.6 °F)		
Flammability:	Flammable.		
Auto igniting:	370 °C (698 °F)		
Decomposition temperature:	Not determined.		
Ignition temperature:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive		
- ,	vapor mixtures are possible.		
Explosion limits:			
Lower:	1.2 Vol %		
Upper:	7.5 Vol %		
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)		
Density at 20 °C (68 °F):	1.09075 g/cm³ (9.10231 lbs/gal)		
Relative density	Not determined.		
Vapor density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water:	Not miscible or difficult to mix.		
Partition coefficient (n-octanol/water	er): Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Solvent content:			
Organic solvents:	57.0 %		
Coating VOC content:	37.46 %		
	485.6 g/l / 4.05 lb/gal		
Material VOC content:	408.6 g/l / 3.41 lb/gal		
Solids content:	42.9 %		

(Contd. on page 8)



Page 8/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 7)

· Other information

No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 9)



Page 9/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 8)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

a - 1	ransp	art in	torma:	han
				7 1 2 1 1 1

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint

· **ADR** 1263 PAINT PAINT

· Transport hazard class(es) NOT APPLICABLE

· DOT



· Class 3 Flammable liquids

(Contd. on page 10)





# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 9) · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E · Stowage Category Α · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT On passenger aircraft/rail: 60 L · Quantity limitations On cargo aircraft only: 220 L · ADR · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L · Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

#### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 11)



Page 11/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 10)

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

822-06-0 hexamethylene-di-isocyanate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

822-06-0 hexamethylene-di-isocyanate

· Proposition 65

· Chemicals known to cause cancer:

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

4-chloro-alpha, alpha, alpha-trifluorotoluene

(Contd. on page 12)



Page 12/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 11)

Homopolymer of hexamethylene diisocyanate n-butyl acetate

#### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause respiratory irritation. May cause drowsiness or dizziness.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 12/02/2024 / 1.0

(Contd. on page 13)



Page 13/13

### Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024 Reviewed on 10/23/2024

#### Trade name: H7085 2K HARDENER NORMAL

(Contd. of page 12)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

· \* Data compared to the previous version altered.