

Page 1/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

1 Identification

· Product identifier

- · Trade name: H909 GENPOX HARDENER
- · Article number: H909
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. GHS08 Health hazard Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to organs through prolonged or repeated exposure. 2 GHS07 H315 Causes skin irritation. Skin Irritation 2 Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Page 2/15

Trade name: H909 GENPOX HARDENER

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Danger · Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. (Contd. on page 3)



Safety Data Sheet


acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Page 3/15

Trade name: H909 GENPOX HARDENER



· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
25068-38-6	Epichlorhydrin : epoxy resin	>50- <i>≤</i> 100%	
67-63-0	propan-2-ol	>10- <i>≤</i> 25%	
108-88-3	toluene	>2.5- <i>≤</i> 10%	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 4)

[–] US



Page 4/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

(Contd. of page 3)

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. · Environmental precautions: Do not allow to enter sewers/ surface or ground water. · Methods and material for containment and cleaning up: Absorb with liguid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 25068-38-6 Epichlorhydrin : epoxy resin 90 mg/m³ 400 ppm 67-63-0 propan-2-ol 108-88-3 toluene 67 ppm (Contd. on page 5)



Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

		(Contd. of page 4)
· PAC-2:		
25068-38-6	Epichlorhydrin : epoxy resin	990 mg/m³
67-63-0	propan-2-ol	2000* ppm
108-88-3	toluene	560 ppm
· PAC-3:		
25068-38-6	Epichlorhydrin : epoxy resin	5,900 mg/m ³
67-63-0	propan-2-ol	12000** ppm
108-88-3	toluene	3700* ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
 Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• **Components with limit values that require monitoring at the workplace:** The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

(Contd. on page 6)

[—] US



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

67-6	3-0 propan-2-ol	Contd. of pag
	Long-term value: 980 mg/m³, 400 ppm	
	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4	
108-	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, OTO, A4	
Ingr	edients with biological limit values:	
67-6	3-0 propan-2-ol	
	Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)	
	88-3 toluene	
	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene	
	0.03 mg/L Medium: urine Time: end of shift	
	Parameter: Toluene	
	0.3 mg/g creatinine Medium: urine Time: end of shift	
Δdd	Parameter: o-Cresol with hydrolysis (background) itional information: The lists that were valid during the creation were used as basis.	
	osure controls	
Pers	onal protective equipment:	
	eral protective and hygienic measures:	

(Contd. on page 7)

US -



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Page 7/15

Trade name: H909 GENPOX HARDENER

(Contd. of page 6) Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles 9 Physical and chemical properties Information on basic physical and chemical properties · General Information

- · Appearance:
- Form:
- Color:
- · Odor:
- · Odor threshold:

Fluid According to product description Characteristic Not determined.

(Contd. on page 8)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

Change in condition Melting point/Boiling range: Undetermined. 82 °C (179.6 °F) Flash point: 4 °C (39.2 °F) Flash point: 4 °C (797 °F) Partition temperature: Not determined. Auto igniting: 425 °C (797 °F) Decomposition temperature: Not determined. Ignition temperature: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive a vapor mixtures are possible. Explosion limits: Lower: 2 Vol % Lower: 2 Vol % Vapor pressure at 20 °C (68 °F): 43 hPa (32.3 mm Hg) Density at 20 °C (68 °F): 1.055 g/cm³ (8.80398 lbs/gal) Relative density Not determined. Vapor pressure at 20 °C (68 °F): Not determined. Solubility in / Miscibility with Water: Water: Not determined. Vapor coefficient (n-octanol/water): Not determined. Solvent content: Val 84 % Organic solvents: 24.8 % Coating VOC content: 24.8 % Coating VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %	n II value	(Contd. of page
Metiting point/Melting range: Boiling point/Boiling range:Undetermined. 82 °C (179.6 °F)Flash point:4 °C (39.2 °F)Flammability:Highly flammable.Auto igniting:425 °C (797 °F)Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not selfigniting.Darger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits: Lower:2 Vol %Upper:12 Vol %Vapor pressure at 20 °C (68 °F):4.3 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not determined.Viscosity: Dynamic: 	•	Not determined.
Boiling point/Boiling range:82 °C (179.6 °F)Flash point:4 °C (39.2 °F)Flammability:Highly flammable.Auto igniting:425 °C (797 °F)Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits: Lower:2 Vol % 12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water): Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %		Undetermined
Flammability:Highly flammable.Auto igniting:425 °C (797 °F)Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits:Lower:Lower:2 Vol %Upper:12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Solubility in / Miscibility with Water:Not determined.Viscosity: Dynamic: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galSoluds content:24.8 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Auto igniting:425 °C (797 °F)Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits: Lower:2 Vol % Upper:Density at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal) Not determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not determined.Viscosity: Dynamic: Organic solvents:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %	Flash point:	4 °C (39.2 °F)
Decomposition temperature:Not determined.Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Lower:2 Vol %Upper:12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Vat determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %	Flammability:	Highly flammable.
Ignition temperature:Product is not selfigniting.Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits:Vapor mixtures are possible.Lower:2 Vol % Upper:Upper:12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal) Not determined.Relative densityNot determined.Vapor densityNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:24.84 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %	Auto igniting:	425 °C (797 °F)
Danger of explosion:Product is not explosive. However, formation of explosive a vapor mixtures are possible.Explosion limits: Lower: Upper:2 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal) Not determined.Relative density Vapor densityNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents: Coating VOC content:24.8 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %	Decomposition temperature:	Not determined.
vapor mixtures are possible.Explosion limits: Lower: Upper:2 Vol %2 Vol %12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F): Not determined.1.055 g/cm³ (8.80398 lbs/gal)Relative density Vapor density Vapor densityNot determined.Vapor density Water:Not determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents: Coating VOC content:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:24.8 4 % 262.1 g/l / 2.19 lb/galSolids content:75.2 %	Ignition temperature:	Product is not selfigniting.
Lower:2 Vol %Upper:12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity:Not determined.Dynamic:Not determined.Solvent content:Organic solvents:Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %	Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Upper:12 Vol %Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water): Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %	-	
Vapor pressure at 20 °C (68 °F):43 hPa (32.3 mm Hg)Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Density at 20 °C (68 °F):1.055 g/cm³ (8.80398 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:Not determined.Solvent content: Organic solvents:24.8 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water): Not determined.Viscosity:Not determined.Dynamic:Not determined.Kinematic:Not determined.Solvent content:24.8 %Organic solvents:24.8 %Coating VOC content:24.84 %262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %	Evaporation rate	Not determined.
Partition coefficient (n-octanol/water): Not determined. Viscosity: Not determined. Dynamic: Not determined. Kinematic: Not determined. Solvent content: 24.8 % Organic solvents: 24.8 % Coating VOC content: 24.84 % 262.1 g/l / 2.19 lb/gal Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %		
Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:24.8 % 24.84 % 262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %	Water:	Not miscible or difficult to mix.
Dynamic: Kinematic:Not determined.Not determined.Solvent content: Organic solvents:24.8 %Coating VOC content:24.84 %262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %	Partition coefficient (n-octanol/wat	er): Not determined.
Kinematic:Not determined.Solvent content:24.8 %Organic solvents:24.84 %Coating VOC content:262.1 g/l / 2.19 lb/galMaterial VOC content:262.1 g/l / 2.19 lb/galSolids content:75.2 %		
Solvent content: 24.8 % Organic solvents: 24.8 % Coating VOC content: 24.84 % 262.1 g/l / 2.19 lb/gal Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %		
Organic solvents: 24.8 % Coating VOC content: 24.84 % 262.1 g/l / 2.19 lb/gal Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %		NOT GETERMINEG.
Coating VOC content: 24.84 % 262.1 g/l / 2.19 lb/gal Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %		04.0.%
Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %		
Material VOC content: 262.1 g/l / 2.19 lb/gal Solids content: 75.2 %	Coaling VOC content:	
Solids content: 75.2 %	Material VOC content:	
Other information No further relevant information available	Solids content:	75.2 %
	Other information	No further relevant information available.

(Contd. on page 9)

Page 8/15



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

(Contd. of page 8)

Page 9/15

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

67-63-0 propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

67-63-0 propan-2-ol

108-88-3 toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 10)

3

3

119



Page 10/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

(Contd. of page 9)

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
DOT	Paint
ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
·IMDG	PAINT, MARINE POLLUTANT
·IATA	PAINT



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

	(Contd. of page 1
Transport hazard class(es)	NOT APPLICABLE
DOT	
T MALAT P COST	
Class	3 Flammable liquids
Label	3
ADR, IMDG	
Class	3 Flammable liquids
Label	3
ΙΑΤΑ	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	11
Environmental hazards:	Product contains environmentally hazardou substances: Epichlorhydrin : epoxy resin
Marine pollutant:	Yes
-	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user Hazard identification number (Kemle	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	x II of Not applicable.
	(Contd. on page 1



Page 12/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

	(Contd. of page
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
-	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara
- · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): 67-63-0 propan-2-ol 108-88-3 toluene · TSCA (Toxic Substances Control Act): All components have the value ACTIVE. · Hazardous Air Pollutants 108-88-3 toluene Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. (Contd. on page 13) US



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
- Carcinogenic categories - EPA (Environmental Protection Agency)	
108-88-3 toluene	
TLV (Threshold Limit Value)	
67-63-0 propan-2-ol	A
108-88-3 toluene	Α
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed. • GHS label elements	
GHS02 GHS07 GHS08	
Signal word Danger	
Signal word Danger Hazard-determining components of labeling:	
Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin	
Signal word Danger Hazard-determining components of labeling:	
• Signal word Danger • Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol • Hazard statements	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Precautionary statements 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. 	
 Signal word Danger Hazard-determining components of labeling: Epichlorhydrin : epoxy resin toluene propan-2-ol Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. 	



Page 14/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

(Contd. of page 13) Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 11/16/2024 / 1.0
- Abbreviations and acronyms:
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
 International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HIMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 (Contd. on page 15)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/12/2024

Trade name: H909 GENPOX HARDENER

(Contd. of page 14)

US

Page 15/15

	(Contd. of page 14)
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A	
Sensitization - Skin 1: Skin sensitisation – Category 1	
Toxic to Reproduction 2: Reproductive toxicity – Category 2	
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Categor	у З
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - C	ategory 2
* Data compared to the previous version altered.	