

Page 1/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

1 Identification

· Product identifier

- · Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER
- · Article number: 8340
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs 2 through prolonged or repeated exposure. GHS07 Acute Toxicity - Inhalation 4 H332 Harmful if inhaled. Skin Irritation 2 H315 Causes skin irritation. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Page 2/14

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: xylene ethylbenzene · Hazard statements Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Suspected of causing cancer. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

1

US



Safety Data Sheet


acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Page 3/14





· Chemical	characterization: Mixtures	
••	n : Mixture of the substances listed below with not	nhazardous additions.
-	s components:	
-	•	
1330-20-7	xylene	>50- <i>≤</i> 1009
1000 20 1		



· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

US



Page 4/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

· Information for doctor:

(Contd. of page 3)

- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

130 ppm
33 ppm
10 ppm
140 ppm
140 ppm
920* ppm
(Contd. on page 5)



Page 5/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

100 11 1	ethylbenzene	(Contd. of page 4) 1100* ppm
	chlorobenzene	150 ppm
	1,2,4-trimethylbenzene	360 ppm
108-67-8	mesitylene	360 ppm
· PAC-3:		
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
108-90-7	chlorobenzene	400 ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-67-8	mesitylene	480 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 6)



Page 6/14

Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

· Con	trol parameters	
	ponents with limit values that require monitoring at the workplace:	
1330	0-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
100-	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
· Ingre	edients with biological limit values:	
1330	0-20-7 xylene	
	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids	
	41-4 ethylbenzene	
	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)	
· Addi	itional information: The lists that were valid during the creation were used as basis.	
• Pers • Gene Keep Imme Wasi Store	osure controls conal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work. e protective clothing separately. d contact with the skin.	
Avoid	d contact with the eyes and skin. thing equipment:	
In ca	ase of brief exposure or low pollution use respiratory filter device. In case of intension use respiratory protective device that is independent of circulating air.	sive or lon
expu		



Page 7/14

(Contd. of page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties		
Appearance:			
Form:	Fluid		
Color:	Clear Characteristic		
· Odor:			
Odor threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	136 °C (276.8 °F)		
Flash point:	25 °C (77 °F)		
Flammability:	Flammable.		



Page 8/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

	(Contd. of page 2
Auto igniting:	500 °C (932 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
Density at 20 °C (68 °F):	0.885 g/cm³ (7.38533 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	94.4 %
Coating VOC content:	94.42 %
	835.6 g/l / 6.97 lb/gal
Material VOC content:	835.6 g/l / 6.97 lb/gal
Solids content:	5.5 %
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 9)

⁻ US



Page 9/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 8)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

man

· Carcinogenic categories

· IARC (International Agency for Research on Ca	ncer)
---	-------

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 10)

3

2B

US



Page 10/14

(Contd. of page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number	11014262	
· DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
·DOT	Paint	
ADR	1263 PAINT	
· IMDG, IATA	PAINT	
 Transport hazard class(es) 	NOT APPLICABLE	
· Class · Label	3 Flammable liquids 3	
· ADR, IMDG, IATA		



Page 11/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

	(Contd. of page 1
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	<i>III</i>
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user Hazard identification number (Kemler co EMS Number: Stowage Category 	Warning: Flammable liquids o de): 30 F-E, <u>S-E</u> A
• Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 12)

US



Page 12/14

Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

108-90-7	chlorobenzene	(Contd. of page 1
	aluminium	
	1,2,4-trimethylbenzene	
	xic Substances Control Act):	
1330-20-7	,	ACTIVE
	ethylbenzene	ACTIVE
	chlorobenzene	ACTIVE
7429-90-5	aluminium	ACTIVE
95-63-6	1,2,4-trimethylbenzene	ACTIVE
108-67-8	mesitylene	ACTIVE
Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
108-90-7	chlorobenzene	
Propositio	on 65	
Chemical	s known to cause cancer:	
100-41-4	ethylbenzene	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
Chemicals	s known to cause developmental toxicity:	
	e ingredients is listed.	
Carcinoge	enic categories	
-	ironmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	Ľ
108-90-7	chlorobenzene	L
95-63-6	1,2,4-trimethylbenzene	11
108-67-8	mesitylene	11
TLV (Thre	shold Limit Value)	
1330-20-7		A
100 11 1	ethylbenzene	AS
100-41-4		
	chlorobenzene	AS



Page 13/14

Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
GHS label elements	
The product is classified and labeled according to the Globally Harmonized Syste	em (GHS).
Hazard pictograms	
$\land \land \land$	
GHS02 GHS07 GHS08	
Signal word Warning	
Hazard-determining components of labeling:	
xylene	
ethylbenzene	
Hazard statements	
Flammable liquid and vapor.	
Harmful if inhaled.	
Causes skin irritation.	
Suspected of causing cancer. May cause damage to the hearing organs through prolonged or repeated exposu	Iro
Precautionary statements	<i>и</i> .с.
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	h water/ebower
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wit IF INHALED: Remove person to fresh air and keep comfortable for breathing.	II Walei/SIIUWEI.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
	(Contd. on page



Page 14/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 10/23/2024

Trade name: 8340 GENFLEX PLASTIC PRIMER SILVER

(Contd. of page 13)

Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 10/23/2024 / 1.1
- · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation - Category 2 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 * Data compared to the previous version altered.

US -