

Page 1/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

### 1 Identification

· Product identifier

· Trade name: 8620 2K ACCELERATOR

· Article number: 8620

· CAS Number:

123-86-4

· EC number:

204-658-1

· Index number:

607-025-00-1

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. S.A.L.

P.O. Box 7623

Beirut

**LEBANON** 

info@generalpaint.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 2 H341 Suspected of causing genetic defects.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure H372 Causes, damage, to the immune system.

Specific Target Organ Toxicity - Repeated Exposure H372 Causes damage to the immune system through prolonged or repeated exposure.



Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Page 2/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 1)

- · Label elements
- · GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

n-butyl acetate

dibutyltin dilaurate

Hazard statements

Flammable liquid and vapor.

Suspected of causing genetic defects.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the immune system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Page 3/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 2)

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*0
Fire = 3
Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description 123-86-4 n-butyl acetate

- · Identification number(s)
- EC number: 204-658-1
- · Index number: 607-025-00-1
- · Dangerous components:

77-58-7 dibutyltin dilaurate

≤2.5%

### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Page 4/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
77-58-7	dibutyItin dilaurate	1.1 mg/m³
· PAC-2:		
	n-butyl acetate	200 ppm
77-58-7	dibutyltin dilaurate	8 mg/m³
· PAC-3:		
	n-butyl acetate	3000* ppm
77-58-7	dibutyItin dilaurate	48 mg/m³

- US



Page 5/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 4)

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

### 123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm

Long-term value: 50 ppm

### 77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m<sup>3</sup>

as Sn

REL Long-term value: 0.1 mg/m<sup>3</sup>

as Šn, Skin

TLV Short-term value: 0.2 mg/m3

Long-term value: 0.1 mg/m<sup>3</sup>

as Sn; A4; Skin

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 6)



Page 6/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 5)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Clear

· Odor: Characteristic

(Contd. on page 7)





# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

	(Contd. of page
Odor threshold:	Not determined.
· pH-value:	5
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	-76 °C (-104.8 °F) 124-128 °C (255.2-262.4 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F):	10.7 hPa (8 mm Hg) 55 hPa (41.3 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.88193 g/cm³ (7.35971 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	5 g/l
· Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity: Dynamic at 20 °C (68 °F): Kinematic: Organic solvents: Coating VOC content:	0.7 mPas Not determined. 98.8 % 98.80 % 871.3 g/l / 7.27 lb/gal
Material VOC content:	871.3 g/l / 7.27 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.



Page 8/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 7)

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

### 123-86-4 n-butyl acetate

	-	
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	I C50/4 h	>21 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 9)



Page 9/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 8)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.00	100	10 de	rma a	tion
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint

· **ADR** 1263 PAINT · **IMDG, IATA** PAINT

· Transport hazard class(es) NOT APPLICABLE

· DOT



· Class 3 Flammable liquids

(Contd. on page 10)





# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 9) · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-D · Stowage Category Α · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · ADR · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L · Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 11)



Page 11/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 10)

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

77-58-7 dibutyltin dilaurate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

 Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 12)



Page 12/13

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 11)

dibutyltin dilaurate

#### · Hazard statements

Flammable liquid and vapor.

Suspected of causing genetic defects.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the immune system through prolonged or repeated exposure.

### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 10/23/2024 / 1.0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 13)



Page 13/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024 Reviewed on 07/30/2024

Trade name: 8620 2K ACCELERATOR

(Contd. of page 12)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Germ Cell Mutagenicity 2: Germ cell mutagenicity – Category 2 Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

· \* Data compared to the previous version altered.

US