

Page 1/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

1 Identification

- · Product identifier
- · Trade name: <u>CC5 BRIGHT MAROON</u>
- · Article number: CC5
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.

GHS07

Sensitization - Skin 1H317 May cause an allergic skin reaction.Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

• Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 2)

US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 1) methyl methacrylate 2-hydroxyethyl methacrylate · Hazard statements Flammable liquid and vapor. May cause an allergic skin reaction. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: · NFPA ratings (scale 0 - 4) Health = 0Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 0 Health = 0FIRE 3 Fire = 3Reactivity = 0REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

Page 2/13

(Contd. on page 3)

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

123-86-4 n-butyl acetate

80-62-6 methyl methacrylate

868-77-9 2-hydroxyethyl methacrylate

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.





(Contd. of page 2)

>25-*≤*50%

*≤*2.5%

*≤*2.5%

Page 3/13



Page 4/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 3)

6 Accidental release measures

	precautions, protective equipment and emergency procedures	
	tective equipment. Keep unprotected persons away.	
	nental precautions: Do not allow to enter sewers/ surface or ground water.	
	and material for containment and cleaning up:	ouduct)
	ith liquid-binding material (sand, diatomite, acid binders, universal binders, s contaminated material as waste according to section 13.	awuust).
	dequate ventilation.	
	e to other sections	
	on 7 for information on safe handling.	
	on 8 for information on personal protection equipment.	
See Secti	on 13 for disposal information.	
 Protectiv 	e Action Criteria for Chemicals	
· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
80-62-6	methyl methacrylate	17 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
80-62-6	methyl methacrylate	120 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m³
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
80-62-6	methyl methacrylate	570 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)

⁻ US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Page 5/13

(Contd. of page 4)

Trade name: CC5 BRIGHT MAROON

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

Atun	is time, the remaining constituent has no known exposure limits.			
123-	86-4 n-butyl acetate			
PEL	Long-term value: 710 mg/m³, 150 ppm			
REL	Short-term value: 950 mg/m³, 200 ppm			
	Long-term value: 710 mg/m³, 150 ppm			
TLV	Short-term value: 150 ppm			
	Long-term value: 50 ppm			
80-62	2-6 methyl methacrylate			
PEL	Long-term value: 410 mg/m³, 100 ppm			
REL	Long-term value: 410 mg/m³, 100 ppm			
TLV	Short-term value: 100 ppm			
	Long-term value: 50 ppm			
	DSEN, A4			
· Addi	itional information: The lists that were valid during the creation were used as basis.			
· Expo	osure controls			
	onal protective equipment:			
	eral protective and hygienic measures:			
	ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work.			
	thing equipment:			
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer			
exposure use respiratory protective device that is independent of circulating air.				
Prot	ection of hands:			
1117	Protective gloves			

(Contd. on page 6)

6) US



Page 6/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and chemical properties General Information 		
· Appearance:		
Form:	Liquid	
Color:	Brown	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124-128 °C (255.2-262.4 °F)	
· Flash point:	25 °C (77 °F)	
· Flammability:	Flammable.	
· Auto igniting:	315 °C (599 °F)	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
		(Contd. on page 7)



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Page 7/13

Trade name: CC5 BRIGHT MAROON

	(Contd. of page 6	
Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.	
• Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)	
· Density at 20 °C (68 °F):	1.043 g/cm³ (8.70384 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	40.1 %	
Coating VOC content:	40.11 %	
	418.3 g/l / 3.49 lb/gal	
Material VOC content:	418.3 g/l / 3.49 lb/gal	
Solids content:	59.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

US



Page 8/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 7)

· LD/LC50	icity: values tha	at are relevant for classification:		
123-86-4				
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>21 mg/l (rat)		
preparatio Irritant	The product shows the following dangers according to internally approved calculation methods for preparations: Irritant • Carcinogenic categories			
· IARC (Inte	ernational	Agency for Research on Cancer)		
	nethyl meti	hacrylate		
80-62-6 n	onal Toxi	cology Program)		
80-62-6 n NTP (Nati		None of the ingredients is listed.		
80-62-6 n NTP (Nati		nts is listed.		
80-62-6 n NTP (Nati None of th	e ingredie	nts is listed. tional Safety & Health Administration)		

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)

US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
 UN proper shipping name 		
·DOT	Paint	
ADR	1263 PAINT	
· IMDG, IATA	PAINT	
 Transport hazard class(es) 	NOT APPLICABLE	
· DOT		
· Class	3 Flammable liquids	
· Label	3	
· ADR, IMDG, IATA		
3		
V		
· Class	3 Flammable liquids	
· Label	3	

(Contd. of page 8)



Page 10/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

	(Contd. of page
Packing group DOT, ADR, IMDG, IATA	<i>III</i>
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	<i>I</i> I of Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

 Section 355 	(extremely	hazardous	substances):
---------------------------------	------------	-----------	--------------

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 11)

US



Page 11/13

(Contd. of page 10)

E, NL

A4

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

Hazardous	Air	Pollutants
nazaruous	~"	i onutanto

80-62-6 methyl methacrylate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

· TLV (Threshold Limit Value)

80-62-6 methyl methacrylate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labeling: n-butyl acetate*

methyl methacrylate

2-hydroxyethyl methacrylate

Hazard statements Flammable liquid and vapor. May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary statements
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.

(Contd. on page 12)



Page 12/13

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 11)

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 11/16/2024 / 1.0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transport Association IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 13)

US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: CC5 BRIGHT MAROON

(Contd. of page 12)

US

Page 13/13

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Sensitization - Skin 1: Skin sensitisation – Category 1 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.