

Page 1/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

1 Identification

- · Product identifier
- · Trade name: CC7 RADIANT RED
- · Article number: CC7
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 2)



Page 2/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 1)

methyl methacrylate

2-hydroxyethyl methacrylate

· Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)



Page 3/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangero | us components: | |
|-----------|-----------------------------|-------------------|
| 123-86-4 | n-butyl acetate | >25- <i>≤</i> 50% |
| 80-62-6 | methyl methacrylate | <i>≤</i> 2.5% |
| 868-77-9 | 2-hydroxyethyl methacrylate | <i>≤</i> 2.5% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

US



Page 4/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

| · PAC-1: | | |
|----------|-----------------------------|-------------------------|
| 123-86-4 | n-butyl acetate | 5 ppm |
| | methyl methacrylate | 17 ppm |
| 868-77-9 | 2-hydroxyethyl methacrylate | 1.9 mg/m ³ |
| · PAC-2: | | |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 80-62-6 | methyl methacrylate | 120 ppm |
| 868-77-9 | 2-hydroxyethyl methacrylate | 21 mg/m ³ |
| · PAC-3: | | |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 80-62-6 | methyl methacrylate | 570 ppm |
| 868-77-9 | 2-hydroxyethyl methacrylate | 1,000 mg/m ³ |

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)



Page 5/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 4)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

DSEN. A4

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



(Contd. on page 6)



Page 6/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

| General Information Appearance: Form: Color: Odor: Odor: Odor threshold: PH-value: Not determined. Change in condition Melting point/Melting range: Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
|--|
| Color: Odor: Odor threshold: Characteristic Not determined. PH-value: Not determined. Change in condition Melting point/Melting range: Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
| Odor: Odor threshold: PH-value: Characteristic Not determined. Change in condition Melting point/Melting range: Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
| Odor threshold: Not determined. pH-value: Not determined. Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
| PH-value: Not determined. Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) |
| Melting point/Melting range:Undetermined.Boiling point/Boiling range:124-128 °C (255.2-262.4 °F) |
| Float no int. 25 90 (77 95) |
| · Flash point: 25 °C (77 °F) |
| · Flammability: Flammable. |
| · Auto igniting: 315 °C (599 °F) |
| · Decomposition temperature: Not determined. |
| · Ignition temperature: Product is not selfigniting. |

(Contd. on page 7)



Page 7/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

| | (Contd. of page |
|---|--|
| · Danger of explosion: | Product is not explosive. However, formation of explosive a vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 10.7 hPa (8 mm Hg) |
| · Vapor pressure at 50 °C (122 °F): | 55 hPa (41.3 mm Hg) |
| · Density at 20 °C (68 °F): | 1.043 g/cm³ (8.70384 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/wate | er): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 40.1 % |
| Coating VOC content: | 40.11 % |
| - | 418.3 g/l / 3.49 lb/gal |
| Material VOC content: | 418.3 g/l / 3.49 lb/gal |
| Solids content: | 59.7 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

US



Page 8/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 7)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 | values th | hat are | relevant | for | classi | fication: |
|-----------|-----------|---------|----------|-----|--------|-----------|
| | | | | | | |

123-86-4 n-butyl acetate

| Oral | LD50 | 13,100 mg/kg (rat) |
|------------|----------|---|
| Dermal | LD50 | 13,100 mg/kg (rat) >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat) |

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)



Page 9/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 8)

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

- **DOT** Paint

· **ADR** 1263 PAINT • **IMDG, IATA** PAINT

· Transport hazard class(es) NOT APPLICABLE

· DOT



· Class 3 Flammable liquids

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label

(Contd. on page 10)





Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

| | (Contd. of p | |
|---|--|--|
| Packing group DOT, ADR, IMDG, IATA | III | |
| Environmental hazards: Marine pollutant: | No | |
| Special precautions for user EMS Number: Stowage Category | <i>Warning: Flammable liquids</i> F-E, <u>S-E</u> A | |
| Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. | |
| Transport/Additional information: | | |
| DOT Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L | |
| ADR Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml | |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml | |
| UN "Model Regulation": | UN 1263 PAINT, 3, III | |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 11)



Page 11/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 10)

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories
- · EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E, NL

· TLV (Threshold Limit Value)

80-62-6 methyl methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

n-butyl acetate methyl methacrylate 2-hydroxyethyl methacrylate

· Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

(Contd. on page 12)



Page 12/13

Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/16/2024 Printing date 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 11)

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 11/16/2024 / 1.0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 13)



Page 13/13

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024 Reviewed on 11/16/2024

Trade name: CC7 RADIANT RED

(Contd. of page 12)

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit
REL: Recommended Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Sensitization - Skin 1: Skin sensitisation – Category 1
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.