Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

*
1 Identification

· **Product identifier**

· **Trade name: 6000M 2K CLEAR MATT**

· **Article number:** 6000M
· **Application of the substance / the mixture** refer to the relevant Technical Data Sheet

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
General Paint Co. S.A.L
P.O. Box 7623
Beirut
LEBANON
info@gpccoatings.com
www.gpccoatings.com

· **Information department:** Product Safety Department
· **Emergency telephone number:** 1-800-535-5053 contract number (89244)

*
2 Hazard(s) identification

· **Classification of the substance or mixture**

GHS02 Flame

Flammable Liquids 3	H226 Flammable liquid and vapor.

GHS08 Health hazard

Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure.

GHS07

Skin Irritation 2	H315 Causes skin irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
ethylbenzene
2,3-epoxypropyl neodecanoate
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-
methyl methacrylate
n-butyl acrylate
methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

· **Hazard statements**
Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 2)

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	>10-≤25%
123-86-4	n-butyl acetate	>10-≤25%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
112926-00-8	Precipitated silica (Silica-Amorphous)	>2.5-≤10%
100-41-4	ethylbenzene	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	≤2.5%
80-62-6	methyl methacrylate	≤2.5%
26761-45-5	2,3-epoxypropyl neodecanoate	≤2.5%
141-32-2	n-butyl acrylate	≤2.5%
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	≤2.5%

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 3)

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 4)

· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50? ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m3
100-41-4	ethylbenzene	33 ppm
80-62-6	methyl methacrylate	17 ppm
141-32-2	n-butyl acrylate	8.3 ppm
103-11-7	2-ethylhexyl acrylate	38 mg/m3
872-50-4	N-methyl-2-pyrrolidone	80 mg/m3
79-41-4	methacrylic acid	6.7 ppm
868-77-9	2-hydroxyethyl methacrylate	33 mg/m3
78-83-1	butanol	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m3
7447-41-8	lithium chloride	1.6 mg/m3
556-67-2	octamethylcyclotetrasiloxane	360 ppm

· **PAC-2:**		
1330-20-7	xylene	920 ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1000? ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m3
100-41-4	ethylbenzene	1100 ppm
80-62-6	methyl methacrylate	120 ppm
141-32-2	n-butyl acrylate	130 ppm
103-11-7	2-ethylhexyl acrylate	190 mg/m3
872-50-4	N-methyl-2-pyrrolidone	170 mg/m3
79-41-4	methacrylic acid	61 ppm
868-77-9	2-hydroxyethyl methacrylate	170 mg/m3
78-83-1	butanol	1300 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m3
7447-41-8	lithium chloride	17 mg/m3
556-67-2	octamethylcyclotetrasiloxane	530 ppm

· **PAC-3:**		
1330-20-7	xylene	2500 ppm
123-86-4	n-butyl acetate	3000 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000?* ppm

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 5)

112926-00-8	Precipitated silica (Silica-Amorphous)	1200 mg/m3
100-41-4	ethylbenzene	1800 ppm
80-62-6	methyl methacrylate	570 ppm
141-32-2	n-butyl acrylate	480 ppm
103-11-7	2-ethylhexyl acrylate	1100 mg/m3
872-50-4	N-methyl-2-pyrrolidone	780 mg/m3
79-41-4	methacrylic acid	220 ppm
868-77-9	2-hydroxyethyl methacrylate	1000 mg/m3
78-83-1	butanol	8000* ppm
77-58-7	dibutyltin dilaurate	23 mg/m3
7447-41-8	lithium chloride	100 mg/m3
556-67-2	octamethylcyclotetrasiloxane	1600 ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
· **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 3
· **Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 6)

1330-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
112926-00-8 Precipitated silica (Silica-Amorphous)	
PEL	20mppcf or 80mg/m3 /%SiO2
REL	Long-term value: 6 mg/m³ See Pocket Guide App. C
TLV	TLV withdrawn
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3
80-62-6 methyl methacrylate	
PEL	Long-term value: 410 mg/m³, 100 ppm
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN, A4
141-32-2 n-butyl acrylate	
REL	Long-term value: 55 mg/m³, 10 ppm
TLV	Long-term value: 11 mg/m³, 2 ppm DSEN, A4

· **Ingredients with biological limit values:**

1330-20-7 xylene	
BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

(Contd. of page 7)

100-41-4 ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**

Tightly sealed goggles

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 8)

*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Liquid
Color:	Clear
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	124 °C (255.2 °F)
· **Flash point:**	25 °C (77 °F)
· **Flammability:**	Flammable.
· **Auto igniting:**	370 °C (698 °F)
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· **Explosion limits:**	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· **Vapor pressure at 20 °C (68 °F):**	10.7 hPa (8 mm Hg)
· **Density at 20 °C (68 °F):**	1.005 g/cm³ (8.38673 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	49.2 %
Coating VOC content:	49.16 % 494.1 g/l / 4.12 lb/gal

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 9)

Material VOC content:	494.1 g/l / 4.12 lb/gal
Solids content:	49.6 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

*
11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** No irritating effect.
· **Sensitization:** Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
1330-20-7	xylene	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
100-41-4	ethylbenzene	2B
80-62-6	methyl methacrylate	3
141-32-2	n-butyl acrylate	3
103-11-7	2-ethylhexyl acrylate	2B

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 10)

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

*
14 Transport information

· **UN-Number**	N/A
· **DOT, ADR, IMDG, IATA**	UN1263
· **UN proper shipping name**	N/A
· **DOT**	Paint
· **ADR**	1263 PAINT
· **IMDG, IATA**	PAINT

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 11)

· **Transport hazard class(es)**	NOT APPLICABLE
· **DOT**	
· **Class**	3 Flammable liquids
· **Label**	3
· **ADR, IMDG, IATA**	
· **Class**	3 Flammable liquids
· **Label**	3
· **Packing group**	NON APPLICABILE
· **DOT, ADR, IMDG, IATA**	III
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Flammable liquids
· **Hazard identification number (Kemler code):**	30
· **EMS Number:**	F-E,S-E
· **Stowage Category**	A
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· **ADR**	
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 12)

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
80-62-6	methyl methacrylate
141-32-2	n-butyl acrylate
872-50-4	N-methyl-2-pyrrolidone

· **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIVE
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	ACTIVE
80-62-6	methyl methacrylate	ACTIVE
26761-45-5	2,3-epoxypropyl neodecanoate	ACTIVE
141-32-2	n-butyl acrylate	ACTIVE
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	ACTIVE
103-11-7	2-ethylhexyl acrylate	ACTIVE
872-50-4	N-methyl-2-pyrrolidone	ACTIVE
79-41-4	methacrylic acid	ACTIVE
868-77-9	2-hydroxyethyl methacrylate	ACTIVE
78-83-1	butanol	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
7447-41-8	lithium chloride	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 13)

100-41-4	ethylbenzene
80-62-6	methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
103-11-7	2-ethylhexyl acrylate

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

872-50-4	N-methyl-2-pyrrolidone

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
80-62-6	methyl methacrylate	E, NL

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
80-62-6	methyl methacrylate	A4
141-32-2	n-butyl acrylate	A4
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

ethylbenzene
2,3-epoxypropyl neodecanoate
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 14)

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-
methyl methacrylate
n-butyl acrylate
methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

· **Hazard statements**
Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Product safety department*
· **Contact:** *N/A*
· **Date of preparation / last revision** *06/23/2026 / 1.2*
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 16)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 6000M 2K CLEAR MATT

(Contd. of page 15)

ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Skin Irritation 2: Skin corrosion/irritation – Category 2
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· **** Data compared to the previous version altered.***