

Page 1/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### 1 Identification

- · Product identifier
- · Trade name: 7200 L.E.CLEAR
- · Article number: 7200
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

· Signal word Warning

(Contd. on page 2)



Page 2/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 1)

#### · Hazard-determining components of labeling:

n-butyl acetate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

2-hydroxyethyl methacrylate

methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

#### · Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

#### Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Classification system:

#### · NFPA ratings (scale 0 - 4)



Health = 0 Fire = 3 Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



Health = 0Fire = 3Reactivity = 0

(Contd. on page 3)



Page 3/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous o	components:	
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%
110-43-0	2-Heptanone	>10- <i>≤</i> 25%
	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	<i>≤</i> 2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<i>≤</i> 2.5%
868-77-9	2-hydroxyethyl methacrylate	<i>≤</i> 2.5%
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	<i>≤</i> 2.5%

#### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

JS -



Page 4/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 3)

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

5 ppm 150 ppm 200 ppm 60 ppm 1.9 mg/m³ 50 ppm
200 ppm 60 ppm 1.9 mg/m <sup>2</sup> 50 ppm
60 ppm 1.9 mg/m 50 ppm
1.9 mg/m 50 ppm
50 ppm
1.5 ppm
17 ppm
19 mg/m <sup>3</sup>
1.1 mg/m
50 ppm
30 ppm
200 ppm

US



Page 5/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

110-43-0	2-Heptanone	(Contd. of page 4
	acetone	3200* ppm
71-36-3	butan-1-ol	800 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
122-99-6	2-phenoxyethanol	16 ppm
80-62-6	methyl methacrylate	120 ppm
97-88-1	n-butyl methacrylate	210 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	8 mg/m³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
110-43-0	2-Heptanone	4000* ppm
67-64-1	acetone	5700* ppm
71-36-3	butan-1-ol	8000** ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
122-99-6	2-phenoxyethanol	97 ppm
80-62-6	methyl methacrylate	570 ppm
97-88-1	n-butyl methacrylate	1,300 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	48 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 6)



Page 6/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 5)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

#### 110-43-0 2-Heptanone

PEL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 50 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)



Page 7/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

Information on basic physical and c     General Information	hemical properties
· Appearance: Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Undetermined. 127°C (260.6°F)
· Flash point:	24 °C (75.2 °F)
· Flammability:	Flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.

(Contd. on page 8)



Page 8/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

	(Contd. of page
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.975 g/cm³ (8.13638 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	44.6 %
Coating VOC content:	43.67 %
_	430.8 g/l / 3.60 lb/gal
Material VOC content:	425.8 g/l / 3.55 lb/gal
Solids content:	53.4 %
Other information	No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

JS •



Page 9/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 8)

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (In	ternational Agency for Research on Cancer)	
80-62-6	methyl methacrylate	3
97-88-1	n-butyl methacrylate	2B
· NTP (Na	tional Toxicology Program)	
None of	the ingredients is listed.	
· OSHA-C	Ca (Occupational Safety & Health Administration)	
None of	the ingredients is listed.	

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

US



Page 10/14

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 9)

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
  Recommendation: Disposal must be made according to official regulations.

UN-Number	18440.00	
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR IMDG, IATA	1263 PAINT PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		
POMINICAL GOLDO		
Class	3 Flammable liquids	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, ADR, IMDG, IATA	III	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	





# Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

	(Contd. of page
<ul> <li>Hazard identification number (Kemler code</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	e): 30 F-E, <u>S-E</u> A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara		
· Section 3	55 (extremely hazardous substances):	
None of the	ne ingredients is listed.	
· Section 3	13 (Specific toxic chemical listings):	
71-36-3	butan-1-ol	
122-99-6	2-phenoxyethanol	
80-62-6	methyl methacrylate	
104-68-7	Diethylene glycol monophenyl ether	
· TSCA (To	oxic Substances Control Act):	
	6-4 n-butyl acetate	ACTIVE
110-4	3-0 2-Heptanone	ACTIVE
67-6	4-1 acetone	ACTIVE

(Contd. on page 12)





# Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

71 26 2	butan-1-ol (Conto	d. of page
		_
	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	
	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIV
	2-hydroxyethyl methacrylate	ACTIV
	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
122-99-6	2-phenoxyethanol	ACTIV
80-62-6	methyl methacrylate	ACTIV
97-88-1	n-butyl methacrylate	ACTIV
77-58-7	dibutyltin dilaurate	ACTIV
104-68-7	Diethylene glycol monophenyl ether	ACTIV
<i>55</i> 6-67-2	octamethylcyclotetrasiloxane	ACTIV
· Hazardous A		
	hyl methacrylate	
<ul> <li>Proposition</li> </ul>		
· Chemicals k	nown to cause cancer:	
None of the i	ngredients is listed.	
· Chemicals k	nown to cause reproductive toxicity for females:	
None of the i	ngredients is listed.	
· Chemicals k	nown to cause reproductive toxicity for males:	
None of the i	ngredients is listed.	
· Chemicals k	nown to cause developmental toxicity:	
None of the i	ngredients is listed.	
· Carcinogeni	c categories	
· EPA (Enviro	nmental Protection Agency)	
67-64-1 acet	tone	1
71-36-3 buta	n-1-ol	D
80-62-6 met	hyl methacrylate	E, N
	old Limit Value)	
· TLV (Thresh		Α
• TLV (Thresh	tone	A
67-64-1 acet	tone hyl methacrylate	A
67-64-1 acet		



Page 13/14

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 12)

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

#### · Signal word Warning

#### · Hazard-determining components of labeling:

n-butyl acetate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

2-hydroxyethyl methacrylate

methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

#### · Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 14)



Page 14/14

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 7200 L.E.CLEAR

(Contd. of page 13)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Date of preparation / last revision 10/22/2024 / 1.1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Sensitization - Skin 1: Skin sensitisation - Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

· \* Data compared to the previous version altered.