



## Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

### 1 Identification

- **Product identifier**
- **Trade name:** GO935 OXIDE YELLOW
- **Article number:** GO935
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flammable liquids 4 H227 Combustible liquid.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**  
Combustible liquid.
- **Precautionary statements**  
Keep away from flames and hot surfaces. – No smoking.  
Wear protective gloves/protective clothing/eye protection/face protection.  
In case of fire: Use CO2, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 2  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0  
Fire = 2  
Reactivity = 0

(Contd. on page 2)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

111-76-2 2-butoxyethanol

&gt;2.5-≤10%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 2)

Dispose contaminated material as waste according to section 13.

• **Reference to other sections**

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

• **Protective Action Criteria for Chemicals**

• **PAC-1:**

111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
104-76-7	2-Ethyl-1-hexanol	0.1 ppm
140-88-5	ethyl acrylate	8.3 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>

• **PAC-2:**

111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
108-01-0	2-dimethylaminoethanol	12 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
140-88-5	ethyl acrylate	36 ppm
7447-41-8	lithium chloride	17 mg/m <sup>3</sup>

• **PAC-3:**

111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
104-76-7	2-Ethyl-1-hexanol	200 ppm
140-88-5	ethyl acrylate	240 ppm
7447-41-8	lithium chloride	100 mg/m <sup>3</sup>

### 7 Handling and storage

• **Handling:**

• **Precautions for safe handling** No special precautions are necessary if used correctly.

• **Information about protection against explosions and fires:** No special measures required.

• **Conditions for safe storage, including any incompatibilities**

• **Storage:**

• **Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 4)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 3)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** 10
- **Specific end use(s):** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

#### 111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m <sup>3</sup> , 50 ppm Skin
REL	Long-term value: 24 mg/m <sup>3</sup> , 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3

- **Ingredients with biological limit values:**

#### 111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 5)



## Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 4)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- Form:

Fluid

- Color:

According to product description

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value at 20 °C (68 °F):**

7.4-8.4

- **Change in condition**

- Melting point/Melting range:

Undetermined.

- Boiling point/Boiling range:

100 °C (212 °F)

- **Flash point:**

68 °C (154.4 °F)

- **Flammability:**

Not applicable.

- **Auto igniting:**

240 °C (464 °F)

- **Decomposition temperature:**

Not determined.

- **Ignition temperature:**

Product is not selfigniting.

- **Danger of explosion:**

Not determined.

- **Explosion limits:**

- Lower:

Not determined.

- Upper:

Not determined.

- **Vapor pressure at 20 °C (68 °F):**

23 hPa (17.3 mm Hg)

- **Density at 20 °C (68 °F):**

1.062 g/cm<sup>3</sup> (8.86239 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- Water:

Not miscible or difficult to mix.

(Contd. on page 6)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 5)

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

- **Solvent content:**

- **Organic solvents:** 8.8 %

- **Water:** 60.5 %

- **Coating VOC content:** 8.77 %

- 260.4 g/l / 2.17 lb/gal

- **Material VOC content:** 93.1 g/l / 0.78 lb/gal

- **Solids content:** 29.9 %

- **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.

- **Chemical stability**

- **Thermal decomposition / conditions to be avoided:**

- No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

- 111-76-2 2-butoxyethanol**

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

(Contd. on page 7)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 6)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
140-88-5	ethyl acrylate	2B

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number** NOT APPLICABLE
- **UN proper shipping name** NOT APPLICABLE
- **Transport hazard class(es)** NOT APPLICABLE  
NOT APPLICABLE
- **Packing group** NOT APPLICABLE
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Sara**

#### · **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

#### · **Section 313 (Specific toxic chemical listings):**

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

#### · **TSCA (Toxic Substances Control Act):**

7732-18-5 water, distilled, conductivity or of similar purity

ACTIVE

111-76-2 2-butoxyethanol

ACTIVE

67-63-0 propan-2-ol

ACTIVE

108-01-0 2-dimethylaminoethanol

ACTIVE

104-76-7 2-Ethyl-1-hexanol

ACTIVE

140-88-5 ethyl acrylate

ACTIVE

(Contd. on page 9)

US





## Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 8)

7447-41-8	lithium chloride	ACTIVE
-----------	------------------	--------

**· Hazardous Air Pollutants**

140-88-5	ethyl acrylate	
----------	----------------	--

**· Proposition 65****· Chemicals known to cause cancer:**

140-88-5	ethyl acrylate	
----------	----------------	--

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.		
------------------------------------	--	--

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.		
------------------------------------	--	--

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.		
------------------------------------	--	--

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

**· TLV (Threshold Limit Value)**

111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4
140-88-5	ethyl acrylate	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5	ethyl acrylate	
----------	----------------	--

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms** Void**· Signal word** Warning**· Hazard statements**

Combustible liquid.

**· Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 10)



## Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

**Trade name: GO935 OXIDE YELLOW**

(Contd. of page 9)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 11/16/2024 / 1.0
- **Abbreviations and acronyms:**
  - EINECS: European Inventory of Existing Commercial Chemical Substances*
  - ELINCS: European List of Notified Chemical Substances*
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)*
  - NFPA: National Fire Protection Association (USA)*
  - HMIS: Hazardous Materials Identification System (USA)*
  - VOC: Volatile Organic Compounds (USA, EU)*
  - LC50: Lethal concentration, 50 percent*
  - LD50: Lethal dose, 50 percent*
  - PBT: Persistent, Bioaccumulative and Toxic*
  - vPvB: very Persistent and very Bioaccumulative*
  - NIOSH: National Institute for Occupational Safety*
  - OSHA: Occupational Safety & Health*
  - TLV: Threshold Limit Value*
  - PEL: Permissible Exposure Limit*
  - REL: Recommended Exposure Limit*
  - BEI: Biological Exposure Limit*
  - Flammable liquids 4: Flammable liquids – Category 4*
- **\* Data compared to the previous version altered.**

US