



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

1 Identification

- **Product identifier**
- **Trade name:** GO936 MIXING YELLOW
- **Article number:** GO936
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. S.A.L.
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flammable liquids 4 H227 Combustible liquid.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
Combustible liquid.
- **Precautionary statements**
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

111-76-2	2-butoxyethanol	>2.5-≤10%
67-63-0	propan-2-ol	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 2)

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

• Reference to other sections

No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

• Protective Action Criteria for Chemicals**• PAC-1:**

111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
140-88-5	ethyl acrylate	8.3 ppm
104-76-7	2-Ethyl-1-hexanol	0.1 ppm
7447-41-8	lithium chloride	2.3 mg/m ³

• PAC-2:

111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
108-01-0	2-dimethylaminoethanol	12 ppm
140-88-5	ethyl acrylate	36 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
7447-41-8	lithium chloride	17 mg/m ³

• PAC-3:

111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
140-88-5	ethyl acrylate	240 ppm
104-76-7	2-Ethyl-1-hexanol	200 ppm
7447-41-8	lithium chloride	100 mg/m ³

7 Handling and storage

• Handling:

• Precautions for safe handling No special precautions are necessary if used correctly.

• Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

(Contd. on page 5)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 4)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Fluid

Color:

According to product description

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value at 20 °C (68 °F):**

7.4-8.4

- **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

100 °C (212 °F)

- **Flash point:**

68 °C (154.4 °F)

(Contd. on page 6)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 5)

· Flammability:	Not applicable.
· Auto igniting:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.05157 g/cm ³ (8.77535 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	8.6 %
Water:	64.6 %
Coating VOC content:	8.60 %
	281.7 g/l / 2.35 lb/gal
Material VOC content:	90.4 g/l / 0.75 lb/gal
· Solids content:	25.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 6)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
140-88-5	ethyl acrylate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|----------------------------------|
| · UN-Number | NOT APPLICABLE |
| · UN proper shipping name | NOT APPLICABLE |
| · Transport hazard class(es) | NOT APPLICABLE
NOT APPLICABLE |
| · Packing group | NOT APPLICABLE |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 9)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 8)

• Sara**• Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

• TSCA (Toxic Substances Control Act):

7732-18-5 water, distilled, conductivity or of similar purity

ACTIVE

111-76-2 2-butoxyethanol

ACTIVE

67-63-0 propan-2-ol

ACTIVE

108-01-0 2-dimethylaminoethanol

ACTIVE

140-88-5 ethyl acrylate

ACTIVE

104-76-7 2-Ethyl-1-hexanol

ACTIVE

7447-41-8 lithium chloride

ACTIVE

• Hazardous Air Pollutants

140-88-5 ethyl acrylate

• Proposition 65**• Chemicals known to cause cancer:**

140-88-5 ethyl acrylate

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

• Carcinogenic categories**• EPA (Environmental Protection Agency)**

111-76-2 2-butoxyethanol

NL

• TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

A3

67-63-0 propan-2-ol

A4

140-88-5 ethyl acrylate

A4

• NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5 ethyl acrylate

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO936 MIXING YELLOW

(Contd. of page 9)

• GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

• Hazard pictograms Void**• Signal word** Warning**• Hazard statements**

Combustible liquid.

• Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Product safety department**• Contact:** N/A**• Date of preparation / last revision** 11/16/2024 / 1.0**• Abbreviations and acronyms:**

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable liquids 4: Flammable liquids – Category 4

• * Data compared to the previous version altered.