Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

*

1 Identification

· **Product identifier**

· **Trade name: GO936 MIXING YELLOW**

· **Article number:** GO936
· **Application of the substance / the mixture** refer to the relevant Technical Data Sheet

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
General Paint Co. S.A.L
P.O. Box 7623
Beirut
LEBANON
info@gpccoatings.com
www.gpccoatings.com

· **Information department:** Product Safety Department
· **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· **Classification of the substance or mixture**
Flammable liquids 4 H227 Combustible liquid.

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms** Void
· **Signal word** Warning
· **Hazard statements**
Combustible liquid.
· **Precautionary statements**
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Classification system:**
· **NFPA ratings (scale 0 - 4)**

Health = 0
Fire = 2
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 0
Fire = 2
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 1)

· ***Other hazards***
· ***Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable*
· ***vPvB:*** *Not applicable*

3 Composition/information on ingredients

· ***Chemical characterization: Mixtures***
· ***Description:*** *Mixture of the substances listed below with nonhazardous additions.*

· **Dangerous components:**		
111-76-2	2-butoxyethanol	>2.5-≤10%
67-63-0	propan-2-ol	≤2.5%

4 First-aid measures

· ***Description of first aid measures***
· ***After inhalation:*** *Supply fresh air; consult doctor in case of complaints.*
· ***After skin contact:*** *Generally the product does not irritate the skin.*
· ***After eye contact:*** *Rinse opened eye for several minutes under running water.*
· ***After swallowing:*** *If symptoms persist consult doctor.*
· ***Information for doctor:***
· ***Most important symptoms and effects, both acute and delayed***
No further relevant information available.
· ***Indication of any immediate medical attention and special treatment needed***
No further relevant information available.

5 Fire-fighting measures

· ***Extinguishing media***
· ***Suitable extinguishing agents:***
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· ***Special hazards arising from the substance or mixture*** *No further relevant information available.*
· ***Advice for firefighters***
· ***Protective equipment:*** *No special measures required.*

*
6 Accidental release measures

· ***Personal precautions, protective equipment and emergency procedures*** *Not required*
· ***Environmental precautions:*** *Do not allow to enter sewers/ surface or ground water.*
· ***Methods and material for containment and cleaning up:***
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 2)

· **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
111-76-2	2-butoxyethanol	20 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	1.1 ppm
140-88-5	ethyl acrylate	8.3 ppm
107-21-1	ethanediol	50 ppm
50-00-0	formaldehyde	0.90 ppm
104-76-7	2-Ethyl-1-hexanol	0.1 ppm
7447-41-8	lithium chloride	1.6 mg/m3
67-56-1	methanol	530 ppm
10377-60-3	magnesium nitrate	9.4 mg/m3

· **PAC-2:**		
111-76-2	2-butoxyethanol	67 ppm
67-63-0	propan-2-ol	2000 ppm
108-01-0	2-dimethylaminoethanol	12 ppm
140-88-5	ethyl acrylate	36 ppm
107-21-1	ethanediol	400 ppm
50-00-0	formaldehyde	14 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
7447-41-8	lithium chloride	17 mg/m3
67-56-1	methanol	2100 ppm
10377-60-3	magnesium nitrate	100 mg/m3

· **PAC-3:**		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000 ppm
108-01-0	2-dimethylaminoethanol	72 ppm
140-88-5	ethyl acrylate	240 ppm
107-21-1	ethanediol	670 ppm
50-00-0	formaldehyde	56 ppm
104-76-7	2-Ethyl-1-hexanol	200 ppm
7447-41-8	lithium chloride	100 mg/m3
67-56-1	methanol	7200 ppm

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 3)

10377-60-3	magnesium nitrate	620 mg/m3

*
7 Handling and storage

· **Handling:**
· **Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** None.
· **Storage class:** 10
· **Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**	
111-76-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI, A3
67-63-0 propan-2-ol	
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm BEI, A4

· **Ingredients with biological limit values:**	
111-76-2 2-butoxyethanol	
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 4)

67-63-0 propan-2-ol	
BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
· **Breathing equipment:** Not required
· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:** Goggles recommended during refilling.

*
9 Physical and chemical properties

· **Information on basic physical and chemical properties**
· **General Information**
· **Appearance:**

Form:	Fluid
Color:	According to product description
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value at 20 °C (68 °F):**	7.4-8.4
· **Change in condition**	
Melting point/Melting range:	Undetermined

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 5)

Boiling point/Boiling range:	100 °C (212 °F)
· **Flash point:**	68 °C (154.4 °F)
· **Flammability:**	Not applicable
· **Auto igniting:**	240 °C (464 °F)
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Not determined
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure at 20 °C (68 °F):**	23 hPa (17.3 mm Hg)
· **Density at 20 °C (68 °F):**	1.05157 g/cm³ (8.77535 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	8.6 %
Water:	64.6 %
Coating VOC content:	8.60 % 281.6 g/l / 2.35 lb/gal
Material VOC content:	90.4 g/l / 0.75 lb/gal
Solids content:	25.8 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Trade name: GO936 MIXING YELLOW

(Contd. of page 6)

· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

*
11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
111-76-2 2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

· **Primary irritant effect:**
· **on the skin:** No irritant effect.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
140-88-5	ethyl acrylate	2B
50-00-0	formaldehyde	1

· **NTP (National Toxicology Program)**		
50-00-0	formaldehyde	K

· **OSHA-Ca (Occupational Safety & Health Administration)**	
50-00-0	formaldehyde

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Trade name: GO936 MIXING YELLOW

(Contd. of page 7)

· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

*
14 Transport information

· **UN-Number**	N/A NOT APPLICABLE
· **UN proper shipping name**	N/A NOT APPLICABLE
· **Transport hazard class(es)**	NOT APPLICABLE NOT APPLICABLE
· **Packing group**	NON APPLICABILE NOT APPLICABLE
· **Environmental hazards:** · **Marine pollutant:**	 No
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 8)

· **Sara**

· **Section 355 (extremely hazardous substances):**

50-00-0	formaldehyde

· **Section 313 (Specific toxic chemical listings):**

111-76-2	2-butoxyethanol
67-63-0	propan-2-ol
140-88-5	ethyl acrylate
107-21-1	ethanediol
50-00-0	formaldehyde
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
67-63-0	propan-2-ol	ACTIVE
108-01-0	2-dimethylaminoethanol	ACTIVE
140-88-5	ethyl acrylate	ACTIVE
107-21-1	ethanediol	ACTIVE
50-00-0	formaldehyde	ACTIVE
104-76-7	2-Ethyl-1-hexanol	ACTIVE
7447-41-8	lithium chloride	ACTIVE
67-56-1	methanol	ACTIVE
10377-60-3	magnesium nitrate	ACTIVE

· **Hazardous Air Pollutants**

140-88-5	ethyl acrylate
107-21-1	ethanediol
50-00-0	formaldehyde
67-56-1	methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

140-88-5	ethyl acrylate
50-00-0	formaldehyde

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

107-21-1	ethanediol

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 9)

67-56-1	methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**		
111-76-2	2-butoxyethanol	NL
50-00-0	formaldehyde	B1

· **TLV (Threshold Limit Value)**		
111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4
140-88-5	ethyl acrylate	A4
107-21-1	ethanediol	A4
50-00-0	formaldehyde	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**	
140-88-5	ethyl acrylate
50-00-0	formaldehyde

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms** Void
· **Signal word** Warning
· **Hazard statements**
Combustible liquid.
· **Precautionary statements**
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department
· **Contact:** N/A
· **Date of preparation / last revision** 06/24/2026 / 1.1
· **Abbreviations and acronyms:**
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/24/2026 Reviewed on 06/24/2026

Trade name: GO936 MIXING YELLOW

(Contd. of page 10)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable liquids 4: Flammable liquids – Category 4
· **** Data compared to the previous version altered.***