



Product Description

Complete high quality acrylic polyurethane basecoat product range. Plain or metallic colors, based on 58 base colors including 15 Pearlescent and iridescent colors and 6 xiralllic. High pigmented system, economy on the quantity of paint ready for use, greater coverage, time saving in application because 2 coats are sufficient. Minimal waiting time for the application of the top coat. The basecoat system can be used sometimes with 2K toners in quantities not exceeding 25%.

Suitable Substrates:

- Existing Finishes except TPA
- “GenMax” 2K primers
- OEM Primer or EDP, sanded
- “General” Polyester Putties
- Bare metal substrates must be pre-primed with wash primer 9700

Surface Preperation:

Old paint well sanded and surfaces well primed and prepared.

Product Application:



50% “GenMax” reducers



18-19 sec / DIN 4 mm / 20o C (68°F)



HVLP 1.3 – 1.4 mm
2.0 – 2.5 bar inlet pressure


Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



GenMax Basecoat



5 min. between coats. For metallic colors, a drop coat is recommended.



Wait until fully matt before applying top coat.

Product Characteristics

Flash Point:	23°C (73.4°F)
Solid Content:	21.2 – 39.0 % by weight
Coverage:	7 – 8 m ² /l at 25 micron dry thickness
Specific Gravity:	0.94 – 1.16 kg/cm ³ (7.82 – 9.66 lbs/gal)
SDS:	Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.