Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

*

1 Identification

· **Product identifier**

· **Trade name: 787 BASECOAT DEEP BLACK**

· **Article number:** 787
· **Application of the substance / the mixture** refer to the relevant Technical Data Sheet

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
General Paint Co. S.A.L
P.O. Box 7623
Beirut
LEBANON
info@gpccoatings.com
www.gpccoatings.com

· **Information department:** Product Safety Department
· **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· **Classification of the substance or mixture**

GHS02 Flame

Flammable Liquids 3	H226 Flammable liquid and vapor.

GHS08 Health hazard

Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure.

GHS07

Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
n-butyl acetate
ethylbenzene

· **Hazard statements**
Flammable liquid and vapor.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**

Health = 0
Fire = 3
Reactivity = 0

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH 0	Health = 0
FIRE 3	Fire = 3
REACTIVITY 0	Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-butyl acetate	>50-≤100%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
1330-20-7	xylene	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.
· **After skin contact:** Immediately rinse with water.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 3)

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50? ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm

· **PAC-2:**		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1000? ppm
100-41-4	ethylbenzene	1100 ppm
107-98-2	1-methoxy-2-propanol	160 ppm

· **PAC-3:**		
123-86-4	n-butyl acetate	3000 ppm
1330-20-7	xylene	2500 ppm

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 4)

108-65-6	2-methoxy-1-methylethyl acetate	5000?* ppm
100-41-4	ethylbenzene	1800 ppm
107-98-2	1-methoxy-2-propanol	660 ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
· **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 3
· **Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 5)

REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

· **Ingredients with biological limit values:**

1330-20-7 xylene	
BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
· **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

*
9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Liquid
Color:	Black
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
· **Flash point:**	27 °C (80.6 °F)
· **Flammability:**	Flammable.
· **Auto igniting:**	315 °C (599 °F)
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· **Explosion limits:**	
Lower:	1.2 Vol %

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 7)

Upper:	7.5 Vol %
· **Vapor pressure at 20 °C (68 °F):**	10.7 hPa (8 mm Hg)
· **Vapor pressure at 50 °C (122 °F):**	55 hPa (41.3 mm Hg)
· **Density at 20 °C (68 °F):**	0.938 g/cm³ (7.82761 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with Water:**	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	71.0 %
Coating VOC content:	71.01 % 666.1 g/l / 5.56 lb/gal
Material VOC content:	666.1 g/l / 5.56 lb/gal
Solids content:	25.3 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 8)

*

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· **Primary irritant effect:**
· **on the skin:** No irritant effect.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)
None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 9)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

*
14 Transport information

· **UN-Number**	N/A
· **DOT, ADR, IMDG, IATA**	UN1263
· **UN proper shipping name**	N/A
· **DOT**	Paint
· **ADR**	1263 PAINT
· **IMDG, IATA**	PAINT
· **Transport hazard class(es)**	NOT APPLICABLE

· **DOT**

· **Class**	3 Flammable liquids
· **Label**	3

· **ADR, IMDG, IATA**

· **Class**	3 Flammable liquids
· **Label**	3
· **Packing group**	NON APPLICABILE
· **DOT, IMDG, IATA**	III
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Flammable liquids

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 10)

· **Stowage Category**	A
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 1263 PAINT, 3

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
n-butyl acetate
ethylbenzene

· **Hazard statements**
Flammable liquid and vapor.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/23/2026 Reviewed on 06/16/2026

Trade name: 787 BASECOAT DEEP BLACK

(Contd. of page 12)

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· ***Chemical safety assessment:*** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· ***Department issuing SDS:*** *Product safety department*
· ***Contact:*** *N/A*
· ***Date of preparation / last revision*** *06/23/2026 / 1.2*
· ***Abbreviations and acronyms:***
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Carcinogenicity 2: Carcinogenicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
· **** Data compared to the previous version altered.***