

Page 1/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 794C BASECOAT MET. COARSE
- · Article number: 794C
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut **LEBANON**
- info@generalpaint.biz
- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H351 Carcinogenicity 2 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure H372-H373 Causes damage to the central nervous system through prolonged or

repeated exposure. May cause damage to the hearing organs through prolonged or repeated

exposure.



Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Page 2/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 1)

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene

methyl acetate

Stoddard solvent

ethylbenzene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

(Contd. on page 3)



acc. to OSHA HCS

Page 3/15

Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 2)

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Printing date 10/22/2024

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:	
79-20-9	methyl acetate	>25- <i>≤</i> 50%
	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25-≤50%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
7429-90-5	aluminium powder (stabilised)	>2.5- <i>≤</i> 10%
1330-20-7		>2.5- <i>≤</i> 10%
	ethyl 3-ethoxypropionate	<i>≤</i> 2.5%
8052-41-3	Stoddard solvent	<i>≤</i> 2.5%
	(C	ontd. on page 4)

US



Page 4/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

 (Contd. of page 3)

 100-41-4 ethylbenzene
 ≤2.5%

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- \cdot Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Page 5/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 4)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:							
79-20-9	methyl acetate	250 ppn					
1330-20-7	xylene	130 ppn					
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm					
100-41-4	ethylbenzene	33 ppm					
107-98-2	1-methoxy-2-propanol	100 ppn					
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm					
7664-38-2	phosphoric acid	3 mg/m ³					
70657-70-4	2-methoxypropyl acetate	50 ppm					
PAC-2:							
79-20-9	methyl acetate	1,700 ppm					
1330-20-7	xylene	920* ppm					
763-69-9	ethyl 3-ethoxypropionate	18 ppm					
100-41-4	ethylbenzene	1100* ppn					
107-98-2	1-methoxy-2-propanol	160 ppm					
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm					
7664-38-2	phosphoric acid	30 mg/m³					
70657-70-4	2-methoxypropyl acetate 1,00						
PAC-3:		·					
79-20-9	methyl acetate	10000* ppn					
1330-20-7	xylene	2500* ppm					
763-69-9	ethyl 3-ethoxypropionate	110 ppm					
100-41-4	ethylbenzene	1800* ppm					
107-98-2	1-methoxy-2-propanol	660 ppm					
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm					
7664-38-2	phosphoric acid	150 mg/m³					
70657-70-4	2-methoxypropyl acetate	5,000 ppm					

– US



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 5)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At th	is time, the other constituents have no known exposure limits.
79-20	0-9 methyl acetate
PEL	Long-term value: 610 mg/m³, 200 ppm
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm
TLV	Short-term value: 250 ppm Long-term value: 200 ppm
1330	-20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
	(Contd. on page 7)

(Contd. on page



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 6) TLV Long-term value: 20 ppm BEI. A4 8052-41-3 Stoddard solvent PEL Long-term value: 2900 mg/m³, 500 ppm REL Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min TLV Long-term value: 100 ppm 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 20 ppm OTO, BEI, A3 · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 8)



Page 8/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 7)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not determined.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Liquid
Color: Silver grey
Odor: Characteristic
Odor threshold: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:57 °C (134.6 °F)

· Flash point: -10 °C (14 °F)

· Flammability: Highly flammable.

(Contd. on page 9)



Page 9/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

	(Contd. of page
· Auto igniting:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
· Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
· Density at 20 °C (68 °F):	1.1 g/cm³ (9.1795 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	74.9 %
Coating VOC content:	12.79 %
	375.1 g/l / 3.13 lb/gal
Material VOC content:	140.7 g/l / 1.17 lb/gal
Solids content:	23.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 10)



Page 10/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 9)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

· Other adverse effects No further relevant information available.

(Contd. of page 10)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

147	ransp	ort in	form:	ation
	Tarrop			ation

· UN-Number

· **DOT, ADR, IMDG, IATA** UN1263

· UN proper shipping name

· **DOT** Paint

· **ADR** 1263 PAINT

· **IMDG, IATA** PAINT

· Transport hazard class(es) NOT APPLICABLE

· DOT



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA |||

(Contd. on page 12)





Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

	(Contd. of page
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information: DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

·S	ectio	n 355	(ext	reme	∍ly	haz	ard	ous	subs	stai	nces	:):							
٨	lone c	f the	ingre	dient	ts is	s list	ted.												
					_														
_					-														

Section 313 (Specific toxic chemical listings):

1330-20-7 xylene 100-41-4 ethylbenzene

7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

79-20-9methyl acetateACTIVE98-56-64-chloro-alpha,alpha,alpha-trifluorotolueneACTIVE

(Contd. on page 13)





Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

9004-36-8	cellulose acetate butyrate	(Contd. of page
1330-20-7	•	ACTIV
	ethyl 3-ethoxypropionate	ACTIV
	ethylbenzene	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
7664-38-2	phosphoric acid	ACTIV
· Hazardou	s Air Pollutants	
1330-20-7	xylene	
	ethylbenzene	
· Propositio	n 65	
	s known to cause cancer:	
	4-chloro-alpha,alpha,alpha-trifluorotoluene	
100-41-4	ethylbenzene	
· Chemicals	s known to cause reproductive toxicity for females);
None of th	e ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemicals	known to cause developmental toxicity:	
None of th	e ingredients is listed.	
_	nic categories	
•	ronmental Protection Agency)	
1330-20-7		
100-41-4	ethylbenzene	
· TLV (Thre	shold Limit Value)	
1330-20-7	xylene	,
100-41-4	ethylbenzene	,
· NIOSH-Ca	(National Institute for Occupational Safety and He	ealth)
None of th	e ingredients is listed.	
· GHS label	elements	



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 13)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene

methyl acetate

Stoddard solvent

ethylbenzene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 15)



Page 15/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 794C BASECOAT MET. COARSE

(Contd. of page 14)

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 10/22/2024 / 1.0
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

· * Data compared to the previous version altered.