



## Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

### 1 Identification

- **Product identifier**
- **Trade name:** G79 FIBRE GLASS PUTTY FINE
- **Article number:** G79
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1B

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1  
H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US



## Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** *Danger***· Hazard-determining components of labeling:***styrene***· Hazard statements***Flammable liquid and vapor.**Causes skin irritation.**Causes serious eye irritation.**May cause cancer.**Suspected of damaging fertility or the unborn child.**Causes damage to the hearing organs through prolonged or repeated exposure.***· Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**Get medical advice/attention if you feel unwell.**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**In case of fire: Use CO2, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*2  
Fire = 3  
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

7727-43-7	barium sulphate, natural	>10-≤25%
100-42-5	styrene	>10-≤25%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.

(Contd. on page 4)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 3)

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**PAC-1:**

7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
100-42-5	styrene	20 ppm
112945-52-5	silicon dioxide	18 mg/m <sup>3</sup>

**PAC-2:**

7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
100-42-5	styrene	130 ppm
112945-52-5	silicon dioxide	100 mg/m <sup>3</sup>

**PAC-3:**

7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
-----------	--------------------------	-----------------------

(Contd. on page 5)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 4)

100-42-5	styrene	1100* ppm
112945-52-5	silicon dioxide	630 mg/m <sup>3</sup>

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

**Components with limit values that require monitoring at the workplace:****7727-43-7 barium sulphate, natural**PEL Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fractionREL Long-term value: 10\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fractionTLV Long-term value: 5\* mg/m<sup>3</sup>  
\*inhalable fraction; E**100-42-5 styrene**PEL Long-term value: 100 ppm  
Ceiling limit value: 200; 600\* ppm  
\*5-min peak in any 3 hrs

(Contd. on page 6)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 5)

REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3

**Ingredients with biological limit values:****100-42-5 styrene**

BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	40 µg/L Medium: urine Time: end of shift Parameter: Styrene

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 6)

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Tightly sealed goggles

### 9 Physical and chemical properties

**· Information on basic physical and chemical properties****· General Information****· Appearance:**

<b>Form:</b>	putty
<b>Color:</b>	olive green
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

**· pH-value:** Not determined.**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	145 °C (293 °F)

**· Flash point:** 31 °C (87.8 °F)**· Flammability:** Flammable.**· Auto igniting:** 480 °C (896 °F)**· Decomposition temperature:** Not determined.**· Ignition temperature:** Product is not selfigniting.**· Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.**· Explosion limits:**

<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	8.9 Vol %

**· Vapor pressure at 20 °C (68 °F):** 6 hPa (4.5 mm Hg)**· Density at 20 °C (68 °F):** 1.49 g/cm<sup>3</sup> (12.43405 lbs/gal)**· Relative density** Not determined.**· Vapor density** Not determined.

(Contd. on page 8)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 7)

· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent content:</b> <b>Organic solvents:</b> <b>Coating VOC content:</b>  <b>Material VOC content:</b>	12.7 % 12.73 % 189.7 g/l / 1.58 lb/gal 189.7 g/l / 1.58 lb/gal
<b>Solids content:</b>	83.3 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 9)

- US -





## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 8)

**· Carcinogenic categories****· IARC (International Agency for Research on Cancer)**

14807-96-6	Talc ( $Mg_3H_2(SiO_3)_4$ )	3
100-42-5	styrene	2A

**· NTP (National Toxicology Program)**

100-42-5	styrene	R
----------	---------	---

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.		
------------------------------------	--	--

### 12 Ecological information

**· Toxicity****· Aquatic toxicity:** No further relevant information available.**· Persistence and degradability** No further relevant information available.**· Behavior in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**· Other adverse effects** No further relevant information available.

### 13 Disposal considerations

**· Waste treatment methods****· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:****· Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 10)



## Safety Data Sheet

acc. to OSHA HCS



Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 9)

### 14 Transport information

· <b>UN-Number</b>	UN1263
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Paint related material
· <b>DOT</b>	1263 PAINT RELATED MATERIAL
· <b>ADR</b>	PAINT RELATED MATERIAL
· <b>IMDG, IATA</b>	
· <b>Transport hazard class(es)</b>	NOT APPLICABLE
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	III
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

(Contd. on page 11)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 10)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

**Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulphate, natural

100-42-5 styrene

**TSCA (Toxic Substances Control Act):**14807-96-6 Talc ( $Mg_3H_2(SiO_3)_4$ ) ACTIVE

7727-43-7 barium sulphate, natural ACTIVE

100-42-5 styrene ACTIVE

38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol ACTIVE

**Hazardous Air Pollutants**

100-42-5 styrene

**Proposition 65****Chemicals known to cause cancer:**

100-42-5 styrene

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 12)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 11)

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**Carcinogenic categories****EPA (Environmental Protection Agency)**

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

**TLV (Threshold Limit Value)**14807-96-6 Talc ( $Mg_3H_2(SiO_3)_4$ )

A4

100-42-5 styrene

A4

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

GHS02 GHS07 GHS08

**Signal word Danger****Hazard-determining components of labeling:**

styrene

**Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the hearing organs through prolonged or repeated exposure.

**Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

(Contd. on page 13)

US



## Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 12)

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*If exposed or concerned: Get medical advice/attention.*

*Specific treatment (see on this label).*

*Get medical advice/attention if you feel unwell.*

*Take off contaminated clothing and wash it before reuse.*

*If skin irritation occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

• **National regulations:**

• **Information about limitation of use:**

*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 12/02/2024 / 1.0

• **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 14)



## Safety Data Sheet acc. to OSHA HCS

Printing date 12/02/2024

Reviewed on 12/02/2024

**Trade name: G79 FIBRE GLASS PUTTY FINE**

(Contd. of page 13)

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 1B: Carcinogenicity – Category 1B

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

· **\* Data compared to the previous version altered.**

US